

### DATASHEET

## **IGNITE NUCLEON**





#### **GENERAL**

| Art.Nr:                | G-1161-XXL/5XL |
|------------------------|----------------|
| GTIN:                  | 4030281008743  |
| E-class number:        | 40-02-01-02    |
| Customs tariff number: | 63079098       |

| Standards:    | EN 358:2018,EN 361:<br>2002 |
|---------------|-----------------------------|
| Net weight:   | 2.35 kg                     |
| Gross weight: | 0.00 kg                     |
|               |                             |



#### DATASHEET

### **IGNITE NUCLEON**

This full-featured fall arrest harness with sliding plate and climbing protection eyelet was specially developed for wind energy, but it is also used in many other telecommunication, areas such energy supply and construction where the highest demands on safety and functionality apply. IGNITE NUCLEON scores with a breathable hip pad that distributes the load evenly on the hip and is protected against abrasion from the outside with a protective sliding plate. The correct position of the sternal and dorsal fall arrest eyelet can be perfectly adjusted to the user. Leg pads are interchangeable if required. An integrated fall indicator and innovative stainless steel OKTALOCK buckles provide additional safety. Excess webbing is no longer a nuisance thanks to practical webbing fixation. The material loops and tool eyelets offer versatile options for accommodating tools.

- Lightweight and comfortable to wear
- Sliding against abrasion
- Breathable hip pads

#### **FEATURES**

| Attachment points:              | Sternal steel<br>attachment point,<br>Dorsal steel<br>attachment point, Side<br>steel attachment point,<br>Climbing protection<br>steel attachment point |
|---------------------------------|--|
| Number of material loops 7 kg:  | 2  |
| Number of material loops 10 kg: | 2  |
| Number of material loops 15 kg: | 0  |
| Application areas:              | Wind energy,<br>Steelwork, Telco<br>energy   |
| Colour:                         | Black, Orange,<br>Anthracite   |
| Harness features:               | Lanyard parking ring,<br>Fallindicator, Wind<br>plate  |
| Hand wash:                      | 40 °C  |
| Maximum lifetime:               | 10 years   |
| Maximum hip size:               | 130 cm   |
| Maximum leg size:               | 110 cm   |
| Maximum temperature:            | 40 °C  |
| Minimum hip size:               | 90 cm  |
| Minimum leg size:               | 85 cm  |
| Minimum temperature:            | -35 °C   |
| Padding:                        | Back padding, Leg<br>paddings removeable,<br>Removeable shoulder<br>paddings   |
| Buckles:                        | stick_buckle, oktalock   |



# DATASHEET **IGNITE NUCLEON**

Adjusting buckles:

Adjusting buckles shoulders, Adjusting buckles torso, Adjusting buckles hips, Adjusting buckles legs

**DIMENSIONS** 

Size: XXL-5XL

**MATERIAL** 

Polyester, Aluminium, Steel, Stainless Steel Material: