

## Data sheet

# LOOP 26 kN



### GENERAL

Art. no.:	L-0008-0,1	E-class number:	40-02-01-90
EAN:	4030281063360	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

### LOOP 26 kN

Belt sling with a load capacity of 26kN. Different lengths have different colours so that they can be easily distinguished. Is used in the rope access and rescue sector.

- Load capacity of 26kN
- Different lengths in different colours
- Rope access technology and rescues

#### FEATURES

Colour:	grey
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Fire brigade / Rescue / Special Forces, Rope Access / Rigging

#### DIMENSIONS

Size:	0,1m
Weight:	0,02 kg



## Data sheet

# LOOP 26 kN



### GENERAL

Art. no.:	L-0008-0,2	E-class number:	40-02-01-90
EAN:	4030281051893	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

### LOOP 26 kN

#### FEATURES

Colour:	grey
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Fire brigade / Rescue / Special Forces, Rope Access / Rigging

#### DIMENSIONS

Size:	0,2m
Weight:	0,03 kg



## Data sheet

# LOOP 26 kN



### GENERAL

Art. no.:	L-0008-0,4	E-class number:	40-02-01-90
EAN:	4030281042310	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

# LOOP 26 kN

### FEATURES

Colour:	red
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C

### DIMENSIONS

Size:	0,4m
Weight:	0,05 kg

### MATERIAL

Material:	Polyamide
-----------	-----------



Data sheet

## LOOP 26 kN



### GENERAL

Art. no.:	L-0008-0,6	E-class number:	40-02-01-90
EAN:	4030281042327	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

### LOOP 26 kN

#### FEATURES

Colour:	red
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Fire brigade / Rescue / Special Forces, Rope Access / Rigging

#### DIMENSIONS

Size:	0,6m
Weight:	0,06 kg



## Data sheet

# LOOP 26 kN



### GENERAL

Art. no.:	L-0008-0,8	E-class number:	40-02-01-90
EAN:	4030281042334	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

# LOOP 26 kN

### FEATURES

Colour:	grey
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Fire brigade / Rescue / Special Forces, Rope Access / Rigging

### DIMENSIONS

Size:	0,8m
Weight:	0,08 kg



Data sheet

## LOOP 26 kN



### GENERAL

Art. no.:	L-0008-1	E-class number:	40-02-01-90
EAN:	4030281042341	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

# LOOP 26 kN

### FEATURES

Colour:	grey
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Arborists, Fire brigade / Rescue / Special Forces, Rope Access / Rigging

### DIMENSIONS

Size:	1m
Weight:	0,1 kg





## Data sheet

# LOOP 26 kN



## GENERAL

Art. no.:	L-0008-1,2	E-class number:	40-02-01-90
EAN:	4030281042358	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

# LOOP 26 kN

### FEATURES

Colour:	yellow
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Fire brigade / Rescue / Special Forces, Rope Access / Rigging

### DIMENSIONS

Size:	1,2m
Weight:	0,12 kg



## Data sheet

# LOOP 26 kN



### GENERAL

Art. no.:	L-0008-1,5	E-class number:	40-02-01-90
EAN:	4030281042365	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

### LOOP 26 kN

#### FEATURES

Colour:	yellow
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Arborists, Fire brigade / Rescue / Special Forces, Rope Access / Rigging

#### DIMENSIONS

Size:	1,5m
Weight:	0,15 kg



## Data sheet

# LOOP 26 kN



### GENERAL

Art. no.:	L-0008-1,8	E-class number:	40-02-01-90
EAN:	4030281042433	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		



## Data sheet

### LOOP 26 kN

#### FEATURES

Colour:	blue
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C
Area of application:	Arborists, Fire brigade / Rescue / Special Forces, Rope Access / Rigging

#### DIMENSIONS

Size:	1,8m
Weight:	0,17 kg



Data sheet

## LOOP 26 kN



### GENERAL

Art. no.:	L-0008-2	E-class number:	40-02-01-90
EAN:	4030281042440	Customs no.:	63079098
Standard:	EN 354:2010 (MAX. 2M) EN 566:2017 EN 795-B:2012		

## Data sheet

# LOOP 26 kN

### FEATURES

Colour:	blue
Breaking load, major axis:	26,00 kN
Diameter:	25,00 mm
Hand-washing:	40 °C
Max. service life:	10 Years
Max. number of persons:	1
Temperature:	from 45 °C to -35 °C

### DIMENSIONS

Size:	2m
Weight:	0,19 kg

### MATERIAL

Material:	Polyamide
-----------	-----------