

DATASHEET

LOOP 35 KN



GENERAL

Art.Nr:	L-0010-SW-0,8
GTIN:	4030281047889
E-class number:	40-02-01-90
Customs tariff number:	63079098

Standards:	ANSI-ASSP Z359.18: 2017,CEN/TS 16415: 2013,CSA Z259.15-17 ED.,EN 354:2010,EN 566:2017,EN 795-B: 2012
Net weight:	0.25 kg
Gross weight:	0.25 kg

DATASHEET

LOOP 35 KN

The strap slings in the colours black and yellow made of polyamide can be used as a mobile anchor point. The two colours serve to distinguish the lengths more easily. The slings are available in the following lengths: 0.3m; 0.4m; 0.6m; 0.8m; 1m; 1.2m; 1.5m; 1.8m; 2m; 4m. They also have a diameter of 25mm and a load capacity of 35 kN and are mainly used in the construction industry.

- Mobile anchor point
- Available in different lengths
- Diameter 25mm; load capacity 35 kN
- Loop for 3 persons approved according to CEN/TS 16415

The thread color varies with the length of the LOOP:

- L-0010-SW-0,6: grey
- L-0010-SW-0,8: orange
- L-0010-SW-1: blue
- L-0010-SW-1,2: green
- L-0010-SW-2: purple

FEATURES

Application areas:	Roofers, Emergency, RBA rigging
Fallindicator:	No
Colour:	Black
Hand wash:	40 °C
Edge approved:	No
Maximum lifetime:	10 years
Maximum temperature:	45 °C
Minimum tensile strength:	35.00 kN
Minimum temperature:	-35 °C

DIMENSIONS

length_lanyard:	0.80 m
-----------------	--------

MATERIAL

Material:	Polyamide
-----------	-----------