





DIN 6330B

Zeskantmoeren

1,5 d hoog, veredeld, vastheidsklasse 10. Met gekogeld einde bruikbaar, direct op de kegelbak DIN 6319D of G. Met het vlakke einde bruikbaar voor schijven DIN 6340.



Best. nr.	Grootte	E	M	R	S	Verpakkings-eenheid (VE)	Gewicht [g]
82362	M6	11,05	9	9	10	100	5
82370	M8	14,40	12	12	13	100	9
82354	M10	17,80	15	15	16	50	14
82388	M10	18,90	15	15	*17	50	20
82347	M12	20,03	18	17	18	50	20
82396	M12	21,10	18	17	*19	50	28
82321	(M14)	23,40	21	20	21	50	34
82404	(M14)	24,50	21	20	*22	50	45
82412	M16	26,80	24	22	24	50	58
82420	(M18)	30,10	27	24	27	25	83
82438	M20	33,50	30	27	30	25	110
82339	(M22)	37,70	33	30	34	10	185
82446	(M22)	35,70	33	30	*32	10	130
82453	M24	40,00	36	32	36	10	195
82461	(M27)	45,60	40	36	41	-	280
82479	M30	51,30	45	41	46	-	405
82487	M36	61,30	54	50	55	-	715
82495	M42	72,60	63	58	65	-	1170
82503	M48	83,90	72	67	75	-	1800

* Oude DIN-norm.

() DIN uitgebreid.