





DIN 6331

Zeskantmoeren met kraag

1,5 d hoog, gerolde en gefreesd, veredeld, vastheidsklasse 10.



Best. nr.	Grootte	A	D1	E	M	S	Verpakkings-eenheid (VE)	Gewicht [g]
82529	M6	3,0	14	11,05	9	10	50	6
82537	M8	3,5	18	14,40	12	13	50	12
82222	M10	4,0	22	17,80	15	16	50	21
82545	M10	4,0	22	18,90	15	*17	50	25
82230	M12	4,0	25	20,03	18	18	25	30
82552	M12	4,0	25	21,10	18	*19	25	36
82248	(M14)	4,5	28	23,40	21	21	25	43
82560	(M14)	4,5	28	24,50	21	*22	25	51
82578	M16	5,0	31	26,80	24	24	25	70
82586	(M18)	5,0	34	30,10	27	27	25	95
82594	M20	6,0	37	33,50	30	30	25	130
82255	(M22)	6,0	40	37,70	33	34	10	200
82602	(M22)	6,0	40	35,70	33	*32	10	160
82610	M24	6,0	45	40,00	36	36	10	230
82628	M27	8,0	50	45,60	40	41	-	320
82636	M30	8,0	58	51,30	45	46	-	470
82644	M36	10,0	68	61,30	54	55	-	800
82511	M42	12,0	80	72,60	63	65	-	1340
82800	M48	14,0	92	83,90	72	75	-	2040

* Oude DIN-norm.

() DIN uitgebreid.