



Nr. 6334

Verlengmoeren

3,0 d hoog, veredeld, vastheidsklasse 10.



Best. nr.	Grootte	E	M	S	Verpakkingseenheid (VE)	Gewicht [g]
82651	M6	11,05	18	10	100	8
82669	M8	14,40	24	13	50	19
82271	M10	17,80	30	16	25	30
82677	M10	18,90	30	*17	25	42
82289	M12	20,03	36	18	25	48
82685	M12	21,10	36	*19	25	64
82297	M14	23,40	42	21	25	73
82693	M14	24,50	42	*22	25	95
82701	M16	26,80	48	24	25	120
82719	M18	30,10	54	27	20	170
82727	M20	33,50	60	30	10	240
82305	M22	37,70	66	34	10	390
82735	M22	35,70	66	*32	10	280
82743	M24	40,00	72	36	-	400
82750	M27	45,60	81	41	-	600
82768	M30	51,30	90	46	-	850
82776	M36	61,30	108	55	-	1470
82784	M42	72,60	126	65	-	2340
82792	M48	83,90	144	75	-	3600

* Oude DIN-norm.

Toepassing:

De verlengingsmoer nr. 6334 dient als optioneel verbindingselement tussen DIN 787 (schroef voor T-gleuf) en DIN 6379 (stiftbout) en is niet doorschroefbaar. Uit functionele en veiligheidsredenen moeten beide schroeven op halve moerhoogte worden ingeschroefd. Minimale inschroeflengte = 1 x diameter.