

Stainless steel toggle clamps

No. 6844NI

Push-pull type toggle clamp with red handle

short version. For push and pull-clamping.

Stainless steel, polished. Long rod-guide with attaching thread and nut. Shoulder screws pasted into thread. Bearings are prelubricated. Ergonomic, oil-resistant handle with large grip surface and soft components.

Supplied complete with stainless clamping screw no. 6880NI.

Also suitable for use in the food industry.



Order	Size	F1	F2	Clamping screw	Weight
1.0.		[kN]	[kN]		[g]
95349	2	1,0	1,0	M6x25	130
95364	3	2,5	2,5	M8x35	320
95380	5	4,0	4,0	M12x50	1200

Application:

Toggle for direct fit up in metal plates or fixtures, using its front attaching thread or by means of solid base angle no. 6843NI.

No. 6844NIY

Push-pull type toggle clamp with yellow handle





Order	Size	F1	F2	Clamping screw	Weight
no.		[kN]	[kN]		[g]
557289	2	1,0	1,0	M6x25	130
557290	3	2,5	2,5	M8x35	320
557291	5	4,0	4,0	M12x50	1200

No. 6844NIJ

Push-pull type toggle clamp with orange handle





Order	Size	F1	F2	Clamping screw	Weight
no.		[kN]	[kN]		[g]
557454	2	1,0	1,0	M6x25	130
557455	3	2,5	2,5 2,5 M8x35 4,0 4,0 M12x50		320
557456	5	4,0			1200

No. 6844NIE

Push-pull type toggle clamp with blue handle





Order	Size	F1	F2	Clamping screw	Weight
no.		[kN]	[kN]		[g]
557775	2	1,0	1,0	M6x25	130
557776	3	2,5	2,5	M8x35	320
557777	5	4,0	4,0	M12x50	1200

Subject to technical alterations.



Stainless steel toggle clamps

No. 6844NIG

Push-pull type toggle clamp with green handle



Order	Size	F1	F2	Clamping screw	Weight
no.		[kN]	[kN]		[g]
557611	2	1,0	1,0	M6x25	130
557612	3	2,5	2,5	M8x35	320
557613	5	4,0	4,0	M12x50	1200


No. 6844NIT

Push-pull type toggle clamp with black handle





Order	Size	F1	F2	Clamping screw	Weight
no.		[kN]	[kN]		[g]
558186	2	1,0	1,0	M6x25	130
558187	3	2,5	2,5	M8x35	320
558188	5	4,0	4,0	M12x50	1200





Recommendations







No. 6880NI, page 167

Dimensions:

Size	А	В	E	G	Н	H1	Stroke	HW min.	HW max.	L1	L2	L3	N
2	10	36	15	M16x1,5	24	73,0	21,5	17	27,0	68,5	13	69	30,5
3	12	57	25	M20x1,5	33	120,5	40,0	22	37,5	108,0	16	115	33,0
5	16	92	45	M24x1,5	37	149,0	67,0	30	50,0	175,0	24	139	49.0

No. 6843NI

Angle base, solid

for no. 6841NI and no. 6844NI.


Stainless steel, polished. Increased range of application due to enlarged height of center line. Fastening by means of 4 screws.







Order	Size	А	В	С	D	F	Н	I	К	L	М	Weight
no.												[g]
95091	0	30	9,0	16	4,5	30	13	23	10,2	3	15,5-20,5	35
95158	2	60	11,0	11-18	6,7	40	24	40	16,2	5	40	170
95174	3	65	14,5	19	6,7	44	33	50	20,2	6	41	260
95190	5	70	17,0	32	9,0	60	37	60	24,0	8	45	480
K			K 🌉			-	K			K	-	



Subject to technical alterations.