

### TECHNICAL DATA

#### Features

- Detects very low levels of microwave leakage
- Quick response and high accuracy
- Designed for one-handed operation
- Audible (beep) and visual (flashing LED) alarms at 5 mW/cm<sup>2</sup>
- 4-digit, backlit LCD display
- Max hold function and low battery indicator
- Zero button for quick adjustment
- Includes soft carrying case and battery

#### Specifications

Measuring Range:	0 to 9.99 mW/cm <sup>2</sup>
Accuracy:	±1mW/cm <sup>2</sup>
Resolution:	0.01 mW/cm <sup>2</sup>

#### General Specifications

Display:	4-digit LCD
Backlit Display:	Yes
Alarm:	Audible (buzzer) and Visual (LED Light)
Alarm Limit:	5 mW/cm <sup>2</sup>
Max Hold:	Yes
Zero Button:	Yes
Response Time:	2x per sec.
Power Supply:	9V Battery
Low Battery Indicator:	Yes
Product Certifications:	CE
Operating Temperature:	32 to 122°F (0 to 50°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity:	10-90%
Dimensions:	6.3 x 2.4 x 1.7" (160 x 60 x 42mm)
Weight:	5.3 oz (151g)



Model	Description
R9200	Microwave Leakage Detector
CA-52A	Soft Carrying Case