

SLOGGING RING WRENCH

EGA Master's slogging ring wrenches are designed to **tighten or loosen large screws and nuts** with the help of a mallet or hammer in heavy industry, shipbuilding, industrial plant maintenance, etc.




1. Manufactured in **special steel**.

2. In accordance with **DIN 7444** standard.



**From 5/8" to 6" and
from 17mm to 160mm!**


SLOGGING RING WRENCH MM



COD.	AF mm	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68927	17	145	32	12	7			
68928	19					0,2		
68929	22	155	38	13	8			
68930	24	165	42	14	9			
68931	27	175	46		10	0,3		
68932	30		50	16		0,4	5	•
68933	32	185	55		11	0,5		
68934	36	210	60	19		0,6		
68935	41	230	65	20	12	0,7		
68936	46	240	75	22	13	1		
68937	50	250	80	23		1,2		
68938	55		85	24	14	1,4		
68939	60	270	90	26	15	1,6		
68940	65	300	100	30	16	1,9		
68941	70	320	105	32	17	2,3		
68942	75	330	115	33	18	2,9		
68943	80	350	125	34	19	3,6		
68944	85	360	130	36	20	3,9		
68945	90	380	135	39	23	4,8	1	-
68946	100	410	148	43	25	5,8		
68947	110	450	170	45	28	8		
68948	120	480	180	50	30	10		
68949	130	510	200	55	31	12		
68950	140	520	210					
68951	150	570	220	60	32	14		
68952	160	590	240		33	16		

DIN 7444

SLOGGING RING WRENCH INCH.



COD.		L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68687	5/8							
68614	3/4	145	32	12	7			
68615	7/8	155	38	13	8			
68616	15/16	165	42	14	9			
68617	1							
68618	1.1/16	175	46		10	0,3		
68619	1.1/8			16				
68620	1.3/16	185	50			0,4	5	•
68621	1.1/4		55		11			
68622	1.5/16			18				
68623	1.3/8	210		19		0,5		
68624	1.7/16		60					
68625	1.1/2	220						
68626	1.9/16							
68627	1.5/8	230	65	20	12	0,7		
68628	1.11/16							
68629	1.3/4							
68630	1.13/16	240	75	22	13			
68631	1.7/8					1		
68632	1.15/16							
68633	2	250	80	23				
68634	2.1/16				14			
68635	2.1/8		85	24		1,4		
68636	2.3/16							
68637	2.1/4	270						
68638	2.5/16							
68639	2.3/8		90	26	15	1,6		
68640	2.7/16						1	-
68641	2.1/2							
68642	2.9/16	300	100	30	16	2,3		
68643	2.5/8							
68644	2.11/16							
68645	2.3/4	320	110	32	17	2,5		
68646	2.13/16							
68647	2.7/8							
68648	2.15/16	330	115	33	18	3,2		
68649	3							
68650	3.1/16							
68651	3.1/8	350	125	34	19	3,6		
68652	3.1/4							
68653	3.5/16	360	130	36	20	3,9		

COD.		L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68654	3.3/8	360	130	36	20	3,9		
68655	3.1/2							
68656	3.9/16	380	135			4,8		
68657	3.5/8			39	23			
68658	3.11/16	390	140			5,2		
68659	3.3/4							
68660	3.13/16							
68661	3.7/8	410	150			5,8		
68662	3.15/16			43	25			
68663	4							
68664	4.1/16	420	155			6,5		
68665	4.1/8							
68666	4.3/16							
68667	4.1/4		160			8		
68668	4.5/16	450		45	28		1	-
68669	4.3/8							
68670	4.1/2		170			9,6		
68671	4.9/16							
68672	4.5/8							
68673	4.11/16							
68674	4.3/4							
68675	4.13/16	480	180	50	30	11		
68676	4.7/8							
68677	4.15/16							
68678	5							
68679	5.1/4		200	55	31			
68680	5.5/16	520				12		
68681	5.3/8							
68682	5.1/2		210					
68683	5.3/4	570		60	32	14		
68684	6	590	220			16		

DIN 7444

TECHNICAL SPECIFICATION		
MATERIAL	Special steel	
GENERAL HARDNESS	From 17mm (5/8") to 46mm (1.3/4")"	34-40 HRC
	From 50mm (1.13/16") to 160mm (6")	30-36 HRC
FINISHING	PAINTED IN EPOXI POWDER MATT BLACK COLOR SEMI-TEXTURIZED	