

Adjustable Skates CM series

▲ The adjustable skates are actually 2 skates each, they are connected by two steel rods making one skate adjustable from 500mm to 1400mm (model CM60) and 720mm to 1500mm (model CM120 and CM240).



i-Lift No.		1910601	1910602	1910603
Model		CM60	CM120	CM240
Capacity	kg(lb.)	6000(13200)	12000(26400)	24000(52800)
Type of Roller		nylon	nylon	steel
No. of Roller	(pcs)	8	12	16
Skate Dimensions	LxWxH (mm)(in.)	300x250x110(11.8x10x4.4)	360x220x110(14.2x8.7x4.4)	360x220x110(14.2x8.7x4.5)
Net Weight	kg(lb.)	30(66)	38(84)	65(143)

Steerable Skates ST series

▲ They incorporate a 1 meter drawbar and a platform that swivels on a thrust bearing allowing movement around bends.



i-Lift No.		1910701	1910702	1910703
Model		ST30	ST60	ST120
Capacity	kg(lb.)	3000(6600)	6000(13200)	12000(26400)
Type of Roller		nylon	nylon	steel
No. of Roller	(pcs)	4	8	8
Roller Size	ΦxW (mm)(in.)	Φ85x90(3x3.5)	Φ85x90(3x3.5)	Φ83x85(3x3.3)
Dimensions	LxWxH (mm)(in.)	310x255x105(12.2x10x4.1)	630x400x115(24.8x15.7x4.5)	630x440x115(24.8x15.7x4.5)
Net Weight	kg(lb.)	15(33)	50(110)	66(145)