

# 49-U-B Screw extractor set with twist drills, drill socket, for Ø M5 - M16



## DETAIL IMAGE



## DESCRIPTION

The 25-piece screw extractor set with drills and drill sockets is used for universal extraction of broken bolts and screws. The screw extractors are an indispensable tool that neither hobbyists nor professional craftsmen can do without. The set includes screw extractors for screw threads from M5 to M16.

## APPLICATION AREA

For the universal extraction of broken bolts and screws.

## BENEFIT

- Application-oriented assembly for universal use
- Through the shared storage, the completeness of the set can be easily overseen.
- The fine meshing of the rotating pins prevents the bolt from expanding and jamming.

## OPERATION

- File broken screw flush
- Center punch with a punch
- Drill a centered hole in the screw
- Drill out the hole depending on the thread size (see table on the cover cardboard)
- Tap the appropriate turning pin into the hole
- Push the extractor nut onto the turning pin as far down as possible
- Screw out the broken screw using a wrench without getting stuck

## MASTER DATA

GTIN [EAN]	4021176799136
Country of origin	DE
Case material	Tool steel
Series	49-U-B
Net weight [kg]	0,85 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

## SPARE PARTS

- twist drill
- twist drill
- twist drill
- twist drill
- twist drill
- 49-1152\_ screw-on nut SW 10 mm
- 49-1157\_Profile Pin 3.2 mm
- 49-1252\_ screw-on nut SW 11 mm
- 49-1257\_Profile Pin 4.8mm
- 49-1352\_ screw-on nut SW 13 mm
- 49-1357\_Profile Pin 6.4 mm
- 49-1452\_ screw-on nut SW 14 mm
- 49-1457\_Profile pin 8.0 mm
- 49-1552\_ screw-on nut SW 17 mm
- 49-1557\_Profile Pin 8.7 mm
- 49-27-A\_drill socket 6 mm / 3.2 mm
- 49-27-B drill socket 8 mm / 3.2 mm
- 49-27-C drill socket 9 mm / 3.2 mm

- 49-27-D drill socket 10 mm / 3.2 mm
- 49-27-E\_Drill Socket 10 mm / 4.8 mm
- 49-27-F drill socket 11 mm / 4.8 mm
- 49-27-G drill socket 12 mm / 4.8 mm
- 49-27-H drill socket 13 mm / 4.8 mm
- 49-27-I drill socket 13 mm / 6.4 mm
- 49-27-K drill socket 14 mm / 6.4 mm