

30-10-SP 3-jaw universal puller with narrow jaws in set, up to 130 mm spread, 350 mm reach



DESCRIPTION

The 3-jaw universal puller with narrow, adjustable jaws is used for safely pulling bearings, gears, and discs. The inclusion of three pairs of jaws in various lengths allows for pulling operations with different combinations and depths. This makes it possible to release any component that sits on a shaft and is freely accessible from the outside. The narrow jaws ensure that even tight and hard-to-reach spaces are accessible. The 3-jaw design guarantees an even load distribution and thus a particularly secure grip on the part being pulled.

APPLICATION AREA

For the safe extraction of bearings, gears and pulleys

BENEFIT

- The extremely slim design of the jaws optimally engages in extremely tight and hard-to-reach spots.
- 3-jaw ensures an even distribution of force and allows for greater pulling forces.
- The screw connection allows for easy loosening and especially tight fastening of the jaws with an allen key
- Application also for eccentric components through freely movable, sliding jaws on the crossbar.
- Hexagonal profile on the crossbar for secure counter-holding
- Variable adjustment to any span between 8 mm – 130 mm
- Anti-slip safety suspension of the claw in the sliding piece (Armlock Technology)
- Safe setup of the spindle through a swivel spindle tip on both smooth surfaces and during centering (Switch Technology)
- Optional convertible from an External Puller to an Internal Extractor by flipping the jaws.
- Anti-slip safety (spindle neck) at the spindle head for safe work with wrench.
- Spindle outlet for thread protection
- By combining the hooks, a maximum reach of 350 mm can be achieved.

OPERATION

- Position the jaws externally on the part to be pulled
- Slide the claws under the component
- Use a wrench to secure the hooks
- Manually pull the spindle to fix it under pressure
- Move the hexagon drive (male) on the spindle head with a ratchet or a ring spanner until the component is released

MASTER DATA



GTIN [EAN]	4021176463839
Country of origin	DE
Case material	Tool steel
Series	30-SP
Net weight [kg]	5,11 kg
Package contents	1 set
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 1-191-S_Jaws Puller Set


- 1-251-S_Jaws (set)
- 1-91-S_Jaws Puller Set
- 1-V-100-S_3 puller extensions (set)
- 1-V-150-S_3 puller extensions (set)
- 30-10-T_Crossbar
- 612140_Double-sided spindle tip
- 614135_Mechanical Drive Spindle

3-jaw universal puller with narrow jaws in set, up to 130 mm spread, 350 mm reach



Abbreviation	Attribut	Wert
X	Total width [mm]	174 mm
Y	Total depth [mm]	174 mm
Z	Total height [mm]	158 mm
A	Clamping depth outside pull-off [mm]	350 mm
S1	Width across flats [mm]	17 mm
Cmin	Span outside pull-off (min.) [mm]	8 mm
Cmax	Span outside pull-off (max.) [mm]	130 mm
A1	Clamping depth of external pull-off A1 [mm]	200 mm
A2	Clamping depth outside pull-off A2 [mm]	250 mm
A3	Clamping depth external pull-off A3 [mm]	350 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	30 mm
O	Hook base depth usable (claw depth usable O) [mm]	9,5 mm
H	Total hook root depth (total claw depth H) [mm]	13 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	2,6 mm
Emin	Span inside pull-out (min.) [mm]	70 mm
Emax	Span inside pull-out (max.) [mm]	180 mm
Tmax	Max. torque [Nm]	40 Nm
Fmax	Max. tractive force [t]	3 t
Fmax	Max. tensile force [kN]	30 kN

Abbreviation	Attribut	Wert
X	Total width [mm]	174 mm
Y	Total depth [mm]	174 mm
Z	Total height [mm]	158 mm
A	Clamping depth outside pull-off [mm]	350 mm
S1	Width across flats [mm]	17 mm
Cmin	Span outside pull-off (min.) [mm]	8 mm
Cmax	Span outside pull-off (max.) [mm]	130 mm
A1	Clamping depth of external pull-off A1 [mm]	200 mm
A2	Clamping depth outside pull-off A2 [mm]	250 mm
A3	Clamping depth external pull-off A3 [mm]	350 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	30 mm
O	Hook base depth usable (claw depth usable O) [mm]	9,5 mm
H	Total hook root depth (total claw depth H) [mm]	13 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	2,6 mm
Emin	Span inside pull-out (min.) [mm]	70 mm
Emax	Span inside pull-out (max.) [mm]	180 mm
Tmax	Max. torque [Nm]	40 Nm
Fmax	Max. tractive force [t]	3 t
Fmax	Max. tensile force [kN]	30 kN



Abbreviation	Attribut	Wert
X	Total width [mm]	174 mm
Y	Total depth [mm]	174 mm
Z	Total height [mm]	158 mm
A	Clamping depth outside pull-off [mm]	350 mm
S1	Width across flats [mm]	17 mm
Cmin	Span outside pull-off (min.) [mm]	8 mm
Cmax	Span outside pull-off (max.) [mm]	130 mm
A1	Clamping depth of external pull-off A1 [mm]	200 mm
A2	Clamping depth outside pull-off A2 [mm]	250 mm
A3	Clamping depth external pull-off A3 [mm]	350 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	30 mm
O	Hook base depth usable (claw depth usable O) [mm]	9,5 mm
H	Total hook root depth (total claw depth H) [mm]	13 mm
L	Total claw thickness (L+1mm) (claw distance to base surface) [mm]	2,6 mm
Emin	Span inside pull-out (min.) [mm]	70 mm
Emax	Span inside pull-out (max.) [mm]	180 mm
Tmax	Max. torque [Nm]	40 Nm
Fmax	Max. tractive force [t]	3 t
Fmax	Max. tensile force [kN]	30 kN