

12-7 3-jaw puller with presettable jaws for internal, external extraction, up to 650 mm spread, 350 mm reach



DETAIL IMAGE



DESCRIPTION

The 3-jaw puller with adjustable puller jaws for external and internal extraction is used for pulling bearings, gears, discs, etc. in all common sizes for crafts, workshops, and industry. This allows for the loosening of any component that either sits on a shaft and is freely accessible from the outside or is fitted internally and thus needs to be pulled differently. The models are equipped with one jaw support on the inside and the outside, allowing them to be used for both external pulling and internal extraction.

APPLICATION AREA

For pulling off bearings, gears, washers, etc

BENEFIT

- The cross hooks ensure maximum stability for suspending the jaws in the sliding piece (Armlock Technology)
- The three-jaw design ensures even load distribution and a particularly secure hold.
- Smooth adjustment of the symmetrically tensioning arms to the required spread with a key allows for variable application.
- Also usable as a mobile press

OPERATION

- Center the spindle on the shaft
- Clamp the key until the jaws securely grip the part to be removed
- Manually pull the spindle to secure it
- Use a ratchet or a box-end wrench to move the hexagon at the spindle head until the component is loosened
- Alternatively, adjust the hook support, insert the puller into the bore, and safely pull out the component by tightening the hexagon

MASTER DATA

GTIN [EAN]	4021176850844
Country of origin	DE
Case material	Tool steel
Series	12-A
Net weight [kg]	4 kg
Package contents	1 piece
Packaging Act	PP 05
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 12-6-8_Schlüssele
- 12-7-206_Crossbar's inner bushings with spindle
- 12-7-350-E_1 jaws (single)
- 12-7-T_Crossbar
- 633370_Double-sided spindle tip