

209-02 3-jaw tab puller "Economy" with oscillating, height-adjustable jaws, up to 230 mm spread, 150 mm reach



209-01
209-02

209-0

209-2-B

APPLICATION IMAGE



DESCRIPTION

The 3-jaw puller "Economy" with oscillating and height-adjustable jaws is used for pulling bearings, gears, and discs in all common sizes for craft, workshop, and industry. The oscillating and curved jaws adapt to any installation situation and are universally applicable due to the adjustability of the reach and spread. The 3-jaw design ensures an even load distribution, providing a particularly secure hold on the part being pulled.

APPLICATION AREA

For pulling off bearings, gears and pulleys

BENEFIT

- Adjustable puller jaws for individual adjustment of the reach due to multiple drilling in the puller jaws
- Oscillating puller jaws offer a variety of adjustment options
- Secure setup of the spindle through a rotatable spindle tip both on smooth surfaces and during centering (Switch Technology)
- 3-jaw ensures an even distribution of force and allows for greater pulling forces.
- Anti-slip safety (spindle neck) at the spindle head for safe working with wrench.
- Spindle outlet to protect the thread

OPERATION

- Position the puller jaws from the outside onto the part to be removed
- Swing the jaws under the component
- Manually pull the spindle to fix it in place
- Use a ratchet or a ring spanner to turn the hexagon at the spindle head until the component is loosened

MASTER DATA

GTIN [EAN]	4021176432736
Country of origin	DE
Case material	Tool steel
Series	209
Net weight [kg]	3,1 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 202-2-T_Crossbar
- 209-02-190-S_3 puller jaws (set)
- 621220_Mechanical pressure spindle