

225-2 3-jaw puller with self-centering jaws, up to 90 mm spread, 35 mm reach



DETAIL IMAGE



DESCRIPTION

The 3-jaw puller with self-centering jaws is used for extracting bearings, gears, and discs. It allows for the removal of any component that is mounted on a shaft and is freely accessible from the outside. The specially shaped jaws are connected to a spring. This ensures self-tensioning of the jaws and prevents possible slipping during the extraction process. Thanks to the quick-release mechanism, the jaws can be attached to the component to be pulled in no time. The 3-jaw design guarantees even load distribution and thus a particularly secure grip on the part being extracted.

APPLICATION AREA

For pulling off bearings, gears and pulleys

BENEFIT

- The spring ensures self-tensioning of the jaws.
- Steckbolts ensure a quick exchange of the jaws.
- 3-jaw provides an even distribution of force and allows for greater pulling forces.

OPERATION

- Press the quick release to open the jaws
- Place the jaws on the component to be removed
- Release the quick release to enable automatic self-tensioning
- Connect the puller to a sliding hammer or a counter stay to disassemble the component

MASTER DATA

GTIN [EAN]	4021176123412
Country of origin	DE
Case material	Tool steel
Series	225-0
Net weight [kg]	1,235 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 225-2-70-S_3 puller set
- 225-2-A_thread adapter Ag M12 / Ag 15/16 G
- 225-57-S_Set (3 pieces) stud bolts for 225-1/-2/-3 and 225-Sk