

70-2 Ball bearing puller without claw with wrench size 17 mm, total height 270 mm



DETAIL IMAGE



DESCRIPTION

The ball bearing pullers of series 70 are used for non-destructive removal of deep groove ball bearings without disassembling the shaft in crafts, industry, and workshops. With these pullers, bearings that are seated simultaneously in a housing and on a shaft can be removed easily and quickly, and can be reused if they are not already damaged. The series 70 impresses with its specifically developed jaws for precise installation in the bearing raceways. Various jaw sets are available for each puller size.

APPLICATION AREA

For non-destructive extraction of deep groove ball bearings without dismantling the shaft

BENEFIT

- Suitable for a variety of groove diameters through infinitely adjustable hooks and internationally applicable.
- Self-damaged bearings can be grasped by the adjustable hooks.
- The claw shape ensures a secure grip, allowing for high pulling forces to be developed.
- The puller is also suitable for removing sealed bearings from housing bores.
- Quick and secure selection by marking the storage adapter
- The puller is rotatable 360° on the crossbar ring.

OPERATION

- Choose the appropriate puller and hooks
- Place a possibly suitable support ring on the inner ring of the bearing
- Insert hooks between the balls in the outer bearing ring
- Compress the hooks at the top, tighten the clamping disc securely, and remove the ball bearing by tightening the center spindle

MASTER DATA

GTIN [EAN]	4021176021213
Country of origin	DE
Case material	Tool steel
Series	70
Net weight [kg]	0,67 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SUITABLE FOR

- 70-721_Puller Hook Set
- 70-722_Puller Set

SPARE PARTS

- 07020020_spindle socket
- 614250_Mechanical spindle
- 70-02-R_Ring set for 70-02
- 70-721_Puller Hook Set
- 70-722_Puller Set