

# 129-2 Ball joint press with force-amplifying lever, universal for cars, vans, trucks, with 16 mm jaw opening, 3 t



## DESCRIPTION

The ball joint extractor with lever translation of series 129 is used for pressing out the ball pins when removing ball joints as well as tie rod ends on tie rods, universally for passenger cars, vans, and medium trucks. Due to its lever translation, the ball joint extractor can also apply much force where there is little access space available. Series 129 impresses with its variety of applications. The lever clamping range is adjustable via the thread of the center spindle.

## APPLICATION AREA

For pushing out the ball studs when removing ball joints as well as tie rod knobs on tie rods, universal for cars, vans and medium trucks

## BENEFIT

- The ball joint puller is universally applicable through three jaw widths.
- The bolt can be adjusted to flexibly adapt the clamping range.

## OPERATION

- Attach press between ball joint and component
- Tighten spindle with torque wrench
- Thread pin of the ball joint is pressed out of the component

## MASTER DATA

GTIN [EAN]	4021176024771
Country of origin	DE
Case material	Tool steel
Series	129-2
Net weight [kg]	1,13 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

## SPARE PARTS

- 129214\_Body
- 129226\_Adjusting screw
- 129231\_Pull Lever
- 616038\_Center spindle