

129-1 Ball joint press with extractor lever for cars, light vans, with 22 mm jaw opening, 3 t max. tension force



APPLICATION IMAGE



DESCRIPTION

The ball joint puller with lever translation of series 129 is used to press out the ball pins when removing ball joints and tie rod ends on steering rods for cars and light commercial vehicles. Due to its lever translation, the ball joint puller can also apply a lot of force where there is little access space. Series 129 impresses with its application variety. Within the series, there are various sizes of ball joint pullers with different jaw openings. The lever clamping range is adjustable via the thread of the center spindle.

APPLICATION AREA

For pushing out the ball studs when removing ball joints as well as tie rod knobs on tie rods for cars and light vans

BENEFIT

- The bolt can be adjusted to flexibly adapt the clamping range.

OPERATION

- Attach press between ball joint and component
- Tighten spindle with torque wrench
- Thread pin of the ball joint is pressed out of the component

MASTER DATA

GTIN [EAN]	4021176024696
Country of origin	DE
Case material	Tool steel
Series	129-1
Net weight [kg]	0,72 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 129114_Body
- 129126_Adjusting screw
- 129131_Clamping lever
- 614048_Center spindle