

118-1 Puller for camshaft gears, up to 115 mm spread, 43 mm reach, with 4 claws



DESCRIPTION

The camshaft puller with sliding, always parallel puller jaws is used for pulling spoke camshaft wheels in the automotive workshop. Equipped with four special puller jaws, the external puller guarantees particularly safe, non-destructive disassembly.

APPLICATION AREA

For pulling off spoke camshaft gears

BENEFIT

- Special puller jaws for ideal fitting on camshaft gears
- Anti-slip safety (spindle neck) at the spindle head for safe work with wrench.
- Spindle outlet to protect the thread

OPERATION

- Set the puller jaws from the outside on the part to be removed
- Slide the claws under the component
- Manually pull the spindle for fixation
- Move the hexagon at the spindle head with a ratchet or an open-end wrench until the component is loosened

APPLICATION IMAGE



DETAIL IMAGE



MASTER DATA

GTIN [EAN]	4021176989636
Country of origin	DE
Case material	Tool steel
Series	118
Net weight [kg]	1,28 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 118-100-A_2-jaw (A)
- 118-100-B_2-jaw (B)
- 614051_spindle