

# 124-K Puller set for all vehicle types



## DETAIL IMAGE



## DESCRIPTION

The car pulley puller set for all vehicle types is used for removing multi-ribbed pulleys with a diameter of up to 195 mm in automotive applications. The 2-jaw design allows for space-saving work, which functions in any position and even under full load, thanks to the parallel puller jaws.

## APPLICATION AREA

For pulling off multi-grooved pulleys up to a diameter of 195 mm

## BENEFIT

- Universally applicable for most vehicle types
- The flange of the spindle neck prevents the slipping of the key.
- The included hook extensions allow adjustment to all given installation conditions.

## OPERATION

- Place puller hooks behind the pulley for pulleys without threaded holes
- For pulleys with diameters over 132 mm, install the provided additional crossbar and screw suitable commercially available screws into the threaded holes of the pulley
- Set the hexagon on the spindle head in motion with a ratchet or a ring spanner until the component is released

## MASTER DATA

GTIN [EAN]	4021176736841
Country of origin	DE
Case material	Tool steel
Series	124-K
Net weight [kg]	2,52 kg
Package contents	1 piece
Packaging Act	PAP 21
Global sales capability given	Yes (REACH, RoHS, POP, PROP65, TSCA)

## SPARE PARTS

- 124-K-06\_Spindle