



1076 MAX.2X400 E40 IP67 WB HST HIT -O- M24-12.5

Floodlight seamless housing of deep drawn stainless steel ASIS 316. The housing is powder coated white and enamelled up to 70-80 µm thickness. The floodlights provide extreme corrosion resistance and high light output. Ballast unit to be ordered separately for floodlights without ballast included.

Item Number	1076009000
GTIN	6947764645983
Stock status	M



Technical specifications

Certificates

Marine Approved	True
-----------------	------

Technical Data

Minimum ambient temperature (°C)	-20
Maximum ambient temperature (°C)	45
IP classification	67

Light Technical Data

Light source	HI-HS
Number of lamps	2
Power consumption light source (W)	400
Lamp base	E40
Light source included	False

Optic

Optic	WB - Wide beam
Material of diffuser	Tempered glass
Colour of reflector	Silver
Material of reflector	Aluminium

Housing

Main body material	Stainless steel
Body colour	White
Main body colour name	Traffic white
Main body colour surface	Powder coated
Main body colour RAL code	RAL 9016

Dimensions

Length (mm)	533
Width (mm)	165
Height (mm)	548
Net weight (kg)	13.859984

Cable Inlet

Number of cable glands	2
Max cable diameter (mm)	12
Min cable diameter (mm)	10

Logistic Data

Net weight (kg)	13.859984
-----------------	-----------

Illustrations

