




### Cross-connectors, Cu, solid conductor type



- ▶ For single-stranded round conductors, e.g. to DIN EN 60228 Cl. 1
- ▶ Also pre-rounded sector shaped conductors
- ▶ Safe and secure connecting of solid conductors
- ▶ Special version for double cable tap conductors

#### Characteristics

- Annealed material optimises material and crimping properties
- Simple cable entry due to internal chamfer

#### Material

- Copper (EN13600)

#### Surface

- Tin-plated to protect against corrosion

#### Technical instructions

- Tool: see page 44

Nominal cross section mm <sup>2</sup>	Part No.	Dimension mm				Draht-Ø mm	Weight/100 pcs. ~ kg	Packing unit/pcs
		d1	d4	l	l1			
1.5-2.5	<b>SKV1525</b>	1.9	3.9	30	12	1.38/1.78	0.47	25
4	<b>SKV4</b>	2.4	4.4	30	12	2.25	0.56	25
6	<b>SKV6</b>	3.0	5.0	30	12	2.75	0.67	25
10	<b>SKV10</b>	4.0	6.0	35	14	3.55	0.92	25
16	<b>SKV16</b>	5.0	8.0	35	14	4.5	1.86	25
25	<b>SKV25</b>	6.2	10.0	50	21	5.65	4.20	15
35	<b>SKV35</b>	7.0	10.0	55	23	6.7	3.80	15
50	<b>SKV50</b>	8.5	12.0	76	32	8	7.35	15