


## Compression joint to DIN, Al



- ▶ For non-tension connections of aluminium conductors to DIN EN 60228 and aluminium cables to DIN EN 50182
- ▶ To DIN 46267, Part 2
- ▶ With code number for clear tool assignment
- ▶ Filled with contact grease for optimum crimp characteristics
- ▶ For pre-rounded sector shaped conductors

### Characteristics

- Easy to process due to crimp markings
- Simple cable entry due to internal chamfer
- Simple and safe processing due to butt mark

### Material

- E-aluminium

### Surface

- Bright


### Technical instructions

- Tool: see page 103

### Additional information

- re = round single solid wire, rm = round multi-stranded, se = sector shaped single solid wire, sm = sector shaped multi-stranded, sector shaped conductors must be pre-rounded
- 16 - 500 mm<sup>2</sup> IEC-tested
- \* = not standardised

Part No.	Nominal cross section mm <sup>2</sup>		Hint	Code	Dimension mm			Number of crimps		Weight 100 pcs. ~kg	Packing unit/ pcs
	rm/sm	re/se			d1	d4	l	Al (7 mm)	Al (wide)		
222R	10	16	*	10	5.0	10.0	55	3/3	--	0.95	10
223R	16	25	*	12	5.8	12.0	55	3/3	--	1.40	10
224R	25	35		12	6.8	12.0	70	4/4	2/2	1.60	10
225R	35	50		14	8.0	14.0	85	5/5	2/2	2.60	10
226R	50	70		16	10.0	16.0	85	5/5	2/2	3.20	10
227R	70	95		18	11.5	18.5	105	6/6	3/3	5.30	10
228R	95	120		22	13.5	22.0	105	6/6	3/3	7.60	10
229R	120	150		22	15.0	23.0	105	6/6	3/3	7.80	10
230R	150	185		25	16.5	25.0	125	6/6	3/3	10.70	10
231R	185	240		28	18.5	28.5	125	6/6	3/3	14.30	5
232R	240	300		32	21.0	32.0	145	8/8	3/3	20.30	5
233R	300	--		34	23.3	34.0	145	8/8	3/3	22.20	1
234R	400	--		38	26.0	38.5	210	--	5/5	40.80	1
235R	500	--		44	29.0	44.0	210	--	5/5	56.00	1



## Tool application chart

### Compression cable lugs and connectors made from E-AI

#### Compression cable lugs for full-tension connections from AI conductors DIN EN 50182, 16 - 95 mm<sup>2</sup>

Tool type	Crimping range corresponds to nominal cross-section mm <sup>2</sup>	Crimping Tool		Catalogue page		Crimp profile
		Part No.	Crimping head / adapter	Crimping Tool	Crimping die	
Mechanical, electrical, pneumatic crimping tools with interchangeable die / head	10 - 70	K354		236	317	
	10 - 185	K18		238	325	
	10 - 300	K22		240	330	
Hand hydraulic crimping tools	10 - 185	HK6018		280	325	
		HK60UNV	+UA18	465	325	
	10 - 300	HK6022		282	330	
		HK60UNV	+UA22	465	330	
		HK12030		286	336	
		HK12042		288	336	
		HK120U		290	336	
Battery powered crimping tools	10 - 70	EK354ML		250	317	
		EK354		256	317	
	10 - 150	EK505		258	321	
	10 - 185	EK5018		260	325	
		EK60UNV	+UA18	468	325	
		EKM60UNV	+UA18	467	325	
	10 - 300	EK6022		264	330	
		EKM6022		262	330	
		50 - 240	EKM60ID*		268	
	10 - 300	EK60UNV	+UA22	468	330	
		EKM60UNV	+UA22	467	330	
		EK120UNV		469		
		EK12032		270	336	
		EK12042		272	336	
		EK120U	+UA15T	274	336	
		EK135FT	+UA12T	276	336	
Hydraulic crimping systems		10 - 185	THK18		294	325
	10 - 300	THK22		296	330	
		THK120		300	336	
	10 - 500	HK252	+25A13	308	336 + 340	
	150 - 500	HK45		309	342	
Hydraulic crimping heads	10 - 185	PK18		294	325	
		PK60UNV	+UA18	466	325	
	10 - 300	PK22		296	330	
		PK60UNV	+UA22	466	330	
		PK12042		300	336	
		PK120U		302	336	
	10 - 500	PK252	+25A13	304	336 + 340	
	50 - 240	PK60ID*		299		
	150 - 500	PK45		306	342	

\* Not suitable for full-tension connections