
## **Insulated butt connectors**







- ▶ For fine and superfine stranded conductors, e.g. to DIN EN 60228 Cl. 5 and 6
- ▶ Simple and safe connecting owed to butt mark
- Fast processing as no additional insulation of the crimped connection is required
- Insulation sleeve halogen-free



#### **Characteristics**

- Cross-section-dependent colour-coding
- Heat resistant to 105° C



#### Material

- Copper (ETP)
- Insulation sleeve: PA

#### **Surface**

- Tin-plated to protect against corrosion

#### **Technical instructions**

- Tool: see page 173


#### **Additional information**

- 0.1 - 0.4 mm<sup>2</sup> not CSA-tested

| Nominal cross section mm <sup>2</sup> | Part<br>No. | Colour |     | Dimension mm |    |                 |                  |
|---------------------------------------|-------------|--------|-----|--------------|----|-----------------|------------------|
|                                       |             |        | d1  | l1           | 12 | Weight/pcs. ~kg | Packing unit/pcs |
| 0.1 - 0.4                             | 669         |        | 1.2 | 20           | 12 | 0.030           | 100              |
| 0.5 - 1                               | 670         |        | 1.6 | 25           | 15 | 0.090           | 100              |
| 1.5 - 2.5                             | 680         |        | 2.3 | 25           | 15 | 0.115           | 100              |
| 4 - 6                                 | 700         |        | 3.6 | 27           | 15 | 0.250           | 100              |

## Insulated butt connectors with heat shrink insulation









- Simple and safe processing due to butt mark
- ► Fast processing as no additional insulation of the crimped connection is required

▶ For fine and superfine stranded conductors, e.g. to DIN EN 60228 Cl. 5 and 6

► Insulation sleeve halogen-free



#### Characteristics

- Cross-section-dependent colour-coding
- Special crimping tool required
- Heat resistant to 105° C

#### Material

- Copper (ETP)
- Insulation sleeve: PE

#### Surface

Tin-plated to protect against corrosion

#### **Technical instructions**

- Tool: see page 173

| Name in all annual and in a           | Dowt        |        |     | Dimension mm |    |                 |                  |
|---------------------------------------|-------------|--------|-----|--------------|----|-----------------|------------------|
| Nominal cross section mm <sup>2</sup> | Part<br>No. | Colour | d1  | l1           | 12 | Weight/pcs. ~kg | Packing unit/pcs |
| 0.5 - 1                               | 670WS       |        | 1.6 | 36           | 15 | 0.12            | 100              |
| 1.5 - 2.5                             | 680WS       |        | 2.3 | 36           | 15 | 0.15            | 100              |
| 4 - 6                                 | 700WS       |        | 3.4 | 41           | 15 | 0.25            | 100              |





# **Tool application chart**

## Insulated cable connections

|  | Crimping range                                       | Crimping Tool |                         | Catalogue page |              |               |
|--|--|---------------|-------------------------|----------------|--------------|---------------|
| Tool type  | corresponds to nominal cross-section mm <sup>2</sup> | Part No.      | Crimping head / adapter | Crimping Tool  | Crimping die | Crimp profile |
| Mechanical crimping tools                                      | 0,1 - 1  | K80           |                         | 218            |              | $\circ$       |
|  | 0,5 - 6  | K82           |                         | 219            |              | 0             |
|  | 0,5 - 6  | K82T          |                         | 220            |              | 0             |
| Mechanical, electrical,  | 0,1 - 16   | K50           |                         | 235            | 313          | 0             |
| pneumatic crimping tools<br>with interchangeable<br>die / head |  | EK50ML        |                         | 244            | 313          | 0             |
|  | 0,5 - 6  | K507          |                         | 234            |              | 0             |
| Battery powered crimping tools                                 | 0,1 - 16   | EK1550ML      |                         | 248            | 313          | 0             |



# **Tool application chart**

# Butt connectors with heat shrink insulation

|   | Crimping range                                       | Crimping Tool |                         | Catalogue page |              |               |
|---|--|---------------|-------------------------|----------------|--------------|---------------|
| Tool type   | corresponds to nominal cross-section mm <sup>2</sup> | Part No.      | Crimping head / adapter | Crimping Tool  | Crimping die | Crimp profile |
| Mechanical, electrical,<br>pneumatic crimping tools<br>with interchangeable<br>die / head | 0,1 - 16   | K50           |                         | 235            | 313          | $\circ$       |
|   |  | EK50ML        |                         | 244            | 313          | $\overline{}$ |
|   | 0,5 - 6  | K82T          |                         | 220            |              | $\overline{}$ |
| Battery powered crimping tools  | 0,1 - 16   | EK1550ML      |                         | 248            | 313          | 0             |