




## Flexible connector, tab width 2.8 mm, 4.8 mm and 6.3 mm

► No additional insulation required



### Characteristics

- With tabs 2.8, 4.8 or 6.3 x 0.8 mm
- 1, 2 and 12-poles
- Further poles on request



Part No.	Tab Thickn.	Tab Width	Poles	Dimension mm				Insulation material	Bolt size mm		Weight/ pcs. ~kg	Packing unit/pcs
				b	l	h	s		Distance	Diameter		
Tab Width 2.8 mm												
<b>8101</b>	0.8	2.8	1	7.5	35	5.5	0.8	PVC	--	--	0.2	100
<b>8102</b>	0.8	2.8	2	15.0	35	5.5	0.8	PVC	--	2.7	0.3	50
<b>81012</b>	0.8	2.8	12	88.0	35	5.5	0.8	PVC	75	2.7	1.6	10
Tab Width 4.8 mm												
<b>8051</b>	0.8	4.8	1	12.5	28	6.6	0.8	PVC	--	--	0.25	100
<b>8052</b>	0.8	4.8	2	25.0	28	6.6	0.8	PVC	--	3.2	0.50	50
<b>80512</b>	0.8	4.8	12	142.0	28	6.6	0.8	PVC	120	3.2	2.80	10
Tab Width 6.3 mm												
<b>8001</b>	0.8	6.3	1	12.5	28	6.6	0.8	PVC	--	--	0.30	100
<b>8002</b>	0.8	6.3	2	25.0	28	6.6	0.8	PVC	--	3.7	0.55	50
<b>80012</b>	0.8	6.3	12	142.0	28	6.6	0.8	PVC	120	3.7	3.20	10