



Fatigue-Step Grit Top

Fatigue relief with superior slip resistance



- 'Grit' top surface provides exceptional grip even in oily conditions.
- Extremely robust interlocking tiles for heavy-duty use.
- Open holes allow efficient drainage of spilt liquids.
- Provides high levels of comfort underfoot to relieve fatigue.
- Made from nitrile for excellent resistance to oils and chemicals.
- Slip tested to DIN 51130.
- Optional ramped edging in yellow or black.



Parts

Part Number	Size	Colour	Weight (kg)
SS010001G	0.9 m x 0.9 m	Black	9.95

Technical Specifications

Material	Rubber mix, including >50% recycled material
Surface Finish	Carbide bonded to rubber with holes to allow drainage
Product Height	18 mm
Hole Size	22 mm
Min. Operating Temperature	-20°C
Max. Operating Temperature	+130°C
Resistance to Chemicals	NBR offers excellent resistance to oils and chemicals

Environmental Resistance	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking tiles
Accessories	Bevelled corner edges
Cleaning Method	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
COO (Country of Origin)	IN
Tensile Strength	2.5 to 4 MPa
Notes	Silicone is used in the production process of the mats and a residue will possibly be left on the mat
Slip Tested to	DIN 51130 - R13

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com