





Tough-Lock

Easy to install Interlocking PVC tiles, perfect for a quick solution to damaged floors




- The resilient PVC material is suitable for both heavy and light industrial use, including withstanding the weight of most forklift trucks.
- Tiles are easy to install, with a simple interlocking system.
- Bevelled edging is available to add that finishing touch.
- ESD and Anti-Static versions are available to help protect personnel and components.
- Available as a studded or textured tile.
- We can incorporate almost any logo or symbol into your Tough-Lock floor to create a permanent and highly visual message. Logo tiles are cut by CNC water jet for precision.
- Fire tested to EN 13501-1:2007 B_{fl} – s1




Styles Available




Studded Black




Studded Yellow




Studded Red




Studded Grey




Studded Green




Studded Blue




Textured Yellow




Textured Red




Textured Grey



Textured Green



Textured Blue



Textured Black

Parts

Part Number	Size	Colour	Weight (kg)
TLC010003		Black	
TLC030003		Red	
TLC070003		Yellow	
TLC090003		Grey	
TLE010003		Black	
TLE030003		Red	
TLE070003		Yellow	
TLE090003		Grey	
TLS010002H	0.5 m x 0.5 m x 7 mm	Black	
TLS020002H	0.5 m x 0.5 m x 7 mm	Blue	
TLS030002H	0.5 m x 0.5 m x 7 mm	Red	
TLS040002H	0.5 m x 0.5 m x 7 mm	Green	
TLS060002H	0.5 m x 0.5 m x 7 mm	Grey	
TLS070002H	0.5 m x 0.5 m x 7 mm	Yellow	
TLT010002H	0.5 m x 0.5 m x 7 mm	Black	
TLT010003H	0.5 m x 0.5 m x 5 mm	Black	
TLT020002H	0.5 m x 0.5 m x 7 mm	Blue	
TLT030002H	0.5 m x 0.5 m x 7 mm	Red	
TLT030003H	0.5 m x 0.5 m x 5 mm	Red	
TLT040002H	0.5 m x 0.5 m x 7 mm	Green	

Technical Specifications

Material	PVC
Surface Finish	Studded/Textured
Product Height	5 mm, 7 mm
Product Weight	5 mm = 1.5 kg , 7 mm = 2.2 kg
Min. Operating Temperature	-15°C
Max. Operating Temperature	+30°C
Resistance to Chemicals	Resistant to most chemicals
Environmental Resistance	Suitable for indoor environments
Typical Applications	General industrial, Office, Retail
Installation Method	Interlocking tiles - loose lay or bonded
Accessories	Bevelled edging
COO (Country of Origin)	UK (N.Ire.)
Manufacturing process	Injection Moulding

Part Number	Size	Colour	Weight (kg)
TLT040003H	0.5 m x 0.5 m x 5 mm	Green	
TLT060002H	0.5 m x 0.5 m x 7 mm	Grey	
TLT060003H	0.5 m x 0.5 m x 5 mm	Grey	
TLT070002H	0.5 m x 0.5 m x 7 mm	Yellow	
TLT070003H	0.5 m x 0.5 m x 5 mm	Yellow	

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com