



Vyna-Plush

The perfect low-cost doormat to scrape dirt and wipe moisture

- Budget doormat offering all-round performance to prevent slips and trips.
- 100% polypropylene fibres provide effective 'scraping' surface.
- Slip and stain-resistant PVC backing to keep your mat securely in place.
- Available in rolls for larger entrance areas.
- Range of bright colours available, to match interior theming.



Styles Available

Black/Red

Black/Steel

Black/Brown

Black/Blue

Parts

Technical Specifications

Material

PP

Part Number	Size	Colour	Weight (kg)
VP010201	0.6 m x 0.9 m	Black/Blue	1.6
VP010202	0.9 m x 1.5 m	Black/Blue	3.8
VP010203	1.2 m x 1.8 m	Black/Blue	6.05
VP010204	0.9 m x 1.2 m	Black/Blue	2.85
VP010207C	0.9 m x per linear metre (max. 25 m)	Black/Blue	2.6
VP010208C	1.2 m x per linear metre (max. 25 m)	Black/Blue	3.43
VP010301	0.6 m x 0.9 m	Black/Red	1.6
VP010302	0.9 m x 1.5 m	Black/Red	3.8
VP010303	1.2 m x 1.8 m	Black/Red	6.05
VP010304	0.9 m x 1.2 m	Black/Red	2.85
VP010307C	0.9 m x per linear metre (max. 25 m)	Black/Red	2.6
VP010308C	1.2 m x per linear metre (max. 25 m)	Black/Red	3.43
VP010501	0.6 m x 0.9 m	Black/Brown	1.6
VP010502	0.9 m x 1.5 m	Black/Brown	3.8
VP010503	1.2 m x 1.8 m	Black/Brown	6.05
VP010504	0.9 m x 1.2 m	Black/Brown	2.85
VP010506	750 mm x 400 mm	Black/Brown	1
VP010507C	0.9 m x per linear metre (max. 25 m)	Black/Brown	2.6
VP010508C	1.2 m x per linear metre (max. 25 m)	Black/Brown	3.43
VP010601	0.6 m x 0.9 m	Black/Steel	1.6
VP010602	0.9 m x 1.5 m	Black/Steel	3.8
VP010603	1.2 m x 1.8 m	Black/Steel	6.05
VP010604	0.9 m x 1.2 m	Black/Steel	2.85
VP010606	750 mm x 400 mm	Black/Steel	1
VP010607C	0.9 m x per linear metre (max. 25 m)	Black/Steel	2.6
VP010608C	1.2 m x per linear metre (max. 25 m)	Black/Steel	3.43

Backing	Vinyl
Surface Finish	Cutpile
Product Height	7 mm
Product Weight	2.9 kg / m ² ± 100g / m ²
Roll Length	25 m
Pile Height	5 mm
Absorbency	0.6 l/m ²
Pile Yarn Composition	100% PP
Pile Weight	0.43 kg / m ²
Min. Operating Temperature	-10°C
Max. Operating Temperature	+50°C
Resistance to Chemicals	Good
Environmental Resistance	Suitable for indoor environments only
Typical Applications	Entrance areas
Installation Method	Loose lay
Cleaning Method	Vacuum top surface
COO (Country of Origin)	BE
Coating Thickness	2 mm
Tuft density	63,000 / m ²
Manufacturing process	Tufting 5/32'

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com