



Ringmat Octomat

Extremely tough rubber matting for outdoor use

- Highly durable entrance mat ideal for use outdoors.
- Raised surface design ensures grip in wet conditions while scraping away dirt and debris.
- Large holes allow dirt and debris to fall through, keeping it trapped.
- Option of brush inserts for enhanced scraping, ideal for more heavy-duty environments where debris is a factor.



Parts

Part Number	Size	Colour	Weight (kg)
RM010001B		Black	0.01
RM010003	1 m x 1.5 m (22 mm)	Black	15
RM010004		Black	0.01
RM010012	0.4 m x 0.6 m (17 mm)	Black	2.1
RM010013	0.5 m x 1 m (22 mm)	Black	7.5

Technical Specifications

Material	Rubber mix, including >50% recycled material.
Surface Finish	Octagonal pattern surface with holes
Product Height	17 mm, 22 mm
Product Weight	10 kg / m ²
Min. Operating Temperature	-20°C
Max. Operating	+130°C

Part Number	Size	Colour	Weight (kg)
RM020001B		Blue	0.01
RM030001B		Red	0.01
RM040001B		Green	0.01
RM060001B		Grey	0.01
RM070001B		Yellow	0.01

Temperature	
Environmental Resistance	Suitable for indoor and outdoor environments
UV Resistance	Yes
Typical Applications	Entrance areas, Bars, Ski areas
Installation Method	Loose lay
Cleaning Method	Wash with cold water, use vacuum cleaner or use pressure pump to remove dirt
COO (Country of Origin)	IN
Tensile Strength	2.75 to 3.25 MPa

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@cobaeurope.com

www.cobaeurope.com