

TEST PIPE STOPPERS

The test pipe stoppers are mainly used to seal or plug pipes and to divert the flow in case of pipe inspection, cleaning, damage or repair. They are effective tool for performing the air leak test or the water leak test. All the pipe stoppers have quickcouplings and flanges that enable connecting various accessories.

The test pipe stoppers **PU** have robust stainless steel flowthrough core with rubberized fabric mantle on it. In case of damage the mantle can be replaced. The flexible test pipe stoppers **PU-F** have flexible design where the flowthrough is ensured by a flexible hose. This enables their easy installation.

These basic product lines together cover the range of pipe diameters from 70 mm to 1600 mm.



Flexible Test Pipe Stoppers PU-F

Type		PU 7/15 F	PU 10/20 F	PU 15/30 F	PU 20/40 F	PU 20/50 F	PU 30/60 FL	PU 30/60 F	PU 40/80 F	PU 50/100 F	PU 60/120 F	PU 100/160 F
Part-No.		1216	1214	1215	1213	1235	1218	1210	1238	1211	1212	1217
Pipe diameter	mm	70–150	100–200	150–300	200–400	200–500	300–600	300–600	400–800	500–1000	600–1200	1000–1600
Operating pressure	bar	2,5	2,5	2,5	2,5	2,5	2,5	1,5	2,5	2,5	1,5	1,0
Back pressure	bar	1,0	1,0	1,0	1,0	1,0	1,0	0,5	1,0	1,0	0,5	0,5
Diameter	mm	67	96	135	190	190	270	270	360	450	560	850
Cylinder length	mm	330	510	550	580	740	730	730	1000	1050	1290	1900
Total length	mm	420	600	640	670	830	820	820	1100	1150	1390	2000
Weight	kg	1,5	2,4	3,8	6,6	7,4	12,6	13,4	24	39	58	112
Bypass		1"	1"	1"	2"	2"	2"	2x2"	2"	2x2"	2x2"	2x2"

Test Pipe Stoppers PU

Type		PU 7/15	PU 10/20	PU 20/50	PU 50/80	PU 50/120
Part-No.		1201	1202	1203	1204	1205
Pipe diameter	mm	70–150	100–200	200–500	500–800	500–1200
Operating pressure	bar	1,5	1,5	1,5	1,5	1,5
Back pressure	bar	0,5	0,5	0,5	0,5	0,5
Diameter	mm	67	96	190	450	450
Cylinder length	mm	330	510	580	680	1000
Total length	mm	450	610	690	720	1060
Weight	kg	2,1	4,7	12,5	40	52
Bypass		1"	1"	1x1" 1x2"	2x1" 1x2,5"	2x1" 1x2,5"

