

SHORT PIPE STOPPERS

Thanks to their short length, these pipe stoppers are suitable especially for sealing sewer connections. They are also used in pipe leak tests.

As well as the other pipe stoppers they are made of high-quality rubber and the metal parts are made of corrosion-resistant materials.

The basic product line covers pipe diameters from 50 mm to 400 mm.



Short pipe stoppers UK

Type		UK 5/7	UK 7/10	UK 10	UK 10/15	UK 11/17	UK 15	UK 15/20	UK 20	UK 20/25	UK 25/30	UK 30/40
Part-No.		1404	1411	1401	1406	1416	1402	1409	1403	1410	1407	1418
Pipe diameter	mm	50–70	70–100	100	100–150	110–170	150	150–200	200	200–250	250–300	300–400
Operating pressure	bar	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5
Back pressure	bar	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Diameter	mm	46	67	90	90	100	140	140	180	180	240	290
Cylinder length	mm	125	130	160	160	180	220	220	260	260	290	270
Total length	mm	190	185	210	220	230	280	280	320	320	360	330
Weight	kg	0,3	0,5	0,7	0,7	0,8	1,3	1,3	2,3	2,4	4,2	5,4

Short Bypass Pipe Stoppers PUK

Type		PUK 5/7	PUK 7/10	PUK 10/15	PUK 11/17	PUK 15/20	PUK 20/25	PUK 25/30	PUK 30/40
Part-No.		1415	1405	1408	1417	1412	1413	1414	1420
Pipe diameter	mm	50–70	70–100	100–150	110–170	150–200	200–250	250–300	300–400
Operating pressure	bar	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5
Back pressure	bar	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Diameter	mm	46	67	90	100	140	180	240	290
Cylinder length	mm	125	130	160	180	220	260	290	270
Total length	mm	190	195	195	240	270	320	350	350
Weight	kg	0,3	0,4	0,8	1	2	3,6	5,9	7,5
Bypass		1/4"	1/2"	1/2"	1/2"	1"	2"	2"	2"

