

BYPASS PIPE STOPPERS



Bypass Pipe Stoppers PU-G

The use of these pipe stoppers is advantageous if a higher rate of flow is required. The water passes through the stainless-steel centre part. The rubberized-fabric cover is put on this part and is exchangeable in case of defect. The diameter of the standard product line ranges from 100 to 1200 millimetres.

Type		PU 10 2 G	PU 10/15 2 G	PU 10/20 2 G	PU 15 2 G	PU 15/20 2 G	PU 15/30 3 G	PU 20/50 4 G	PU 50/80 4 G	PU 50/80 6 G	PU 50/80 12 G	PU 50/120 4 G	PU 50/120 6 G	PU 50/120 12 G
Part-No.		1220	1221	1206	1222	1223	1243	1207	1239	1240	1209	1241	1242	1219
Pipe diameter	mm	100	100-150	100-200	150	150-200	150-300	200-500	500-800	500-800	500-800	500-1200	500-1200	500-1200
Operating pressure	bar	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5	1,5
Back pressure	bar	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Diameter	mm	90	90	90	115	115	135	185	450	450	450	450	450	450
Cylinder length	mm	230	300	550	230	290	520	610	680	680	680	970	970	970
Total length	mm	320	420	650	320	380	620	750	830	830	830	1120	1120	1120
Weight	kg	2,3	2,9	4,0	3	3,4	6,6	12,5	40	40	42	53	53	55
Bypass		2"	2"	2"	2"	2"	3"	4"	4"	6"	12"	4"	6"	12"