

EGG-SHAPED PIPE STOPPERS

These pipe stoppers are used to seal the egg-shaped profiles. Leak test can also be done with them. They are manufactured in two versions. The design **UV**, **PUV** and **PUV-F**, which copies the profile of the egg-shaped pipe, is used for smaller pipe profiles. For larger profiles, the pillow version **UVP** and **PUVP** is used. Its advantage is that it is flexible and that it can be inserted through a common shaft.



Egg-shaped Pipe Stoppers UV, UVP

Type		UV 30/45 40/60	UV 50/75 60/90	UV 70/105 90/135	UVP 50/75 60/90	UVP 70/105 90/135
Part-No.		1601	1602	1603	1604	1605
Sealing cross-section	mm	300–400 450–600	500–600 750–900	700–900 1050–1350	500–600 750–900	700–900 1050–1350
Operating pressure	bar	1,0	1,0	1,0	1,0	1,0
Back pressure	bar	0,5	0,5	0,5	0,5	0,5
Dimensions (w x h x l)	mm	270 x 380 x 800	470 x 690 x 1060	650 x 960 x 1360	700 x 2100	1000 x 2500
Weight	kg	12	32	60	23	39

Egg-shaped Test Pipe Stoppers PUV, PUV-F and PUVP

Type		PUV 30/45 40/60	PUV 50/75 60/90	PUV 70/105 90/135	PUV 30/45 40/60 F	PUV 50/75 60/90 F	PUV 70/105 90/135 F	PUVP 50/75 60/90	PUVP 70/105 90/135
Part-No.		1303	1301	1302	1304	1305	1306	1307	1308
Sealing cross-section	mm	300–400 450–600	500–600 750–900	700–900 1050–1350	300–400 450–600	500–600 750–900	700–900 1050–1350	500–600 750–900	700–900 1050–1350
Operating pressure	bar	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0
Back pressure	bar	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Dimensions (w x h x l)	mm	280 x 410 x 750	470 x 690 x 880	650 x 960 x 1060	270 x 380 x 800	470 x 690 x 1060	650 x 960 x 1360	700 x 2100	1000 x 2500
Weight	kg	25	51	78	19	51	98	31	48
Bypass		1x1" 1x2"	1x1" 1x2,5"	1x1" 1x2,5"	1x1" 1x2"	2x2"	2x2"	2"	2"