



PUP

UP

Pillow Pipe Stoppers UP, PUP

| Type | | UP 100/140 | UP 140/180 | UP 180/220 | PUP 100/140 | PUP 140/180 | PUP 180/220 |
|--------------------|-----|------------|------------|------------|-------------|-------------|-------------|
| Part-No. | | 1110 | 1111 | 1112 | 1225 | 1226 | 1227 |
| Pipe diameter | mm | 1000–1400 | 1400–1800 | 1800–2200 | 1000–1400 | 1400–1800 | 1800–2200 |
| Operating pressure | bar | 0,7 | 0,6 | 0,5 | 0,7 | 0,6 | 0,5 |
| Back pressure | bar | 0,5 | 0,5 | 0,5 | 0,5 | 0,5 | 0,5 |
| Width of pillow | mm | 1450 | 2050 | 2650 | 1450 | 2050 | 2650 |
| Length of pillow | mm | 2300 | 3200 | 3900 | 2300 | 3200 | 3900 |
| Weight | kg | 52 | 94 | 141 | 63 | 106 | 155 |
| Bypass | | – | – | – | 2,5" | 2,5" | 2,5" |

These pipe stoppers are mainly used in various sewers and storm sewers. Their advantage is in their ability to be inserted into the sewer through the standard gullies. The special Kevlar reinforcement enables us to manufacture these stoppers in large diameters. The standard product line ranges from 1000 to 2200 millimetres.



US



US-L

Test Stoppers for Gullies US, US-L

| Type | | US 60/65 | US 60/65 L | US 80/85 L | US 100/105 L |
|--------------------|-----|----------|------------|------------|--------------|
| Part-No. | | 9028 | 9038 | 9116 | 9117 |
| Pipe diameter | mm | 600–650 | 600–650 | 800–850 | 1000–1050 |
| Operating pressure | bar | 1,5 | 1,0 | 1,0 | 1,0 |
| Diameter | mm | 560 | 580 | 780 | 980 |
| Cylinder length | mm | 300 | 200 | 200 | 200 |
| Weight | kg | 19 | 5,5 | 7,3 | 9 |
| Bypass | | 2" | 2" | 2" | 2" |