

Cone pipe stoppers have in comparison with classical pipe stoppers different construction but their use is the same. They are mainly used during repair and maintenance work, accidents and the leak tests of pipelines. This construction allows their use for all profiles, also egg-shaped, rectangular and many others. These pipe stoppers are made of quality rubber. Therefore they have good chemical resistance, high age-resistance, low weight, and they are simply repairable. The diameter of standard product line ranges from 150 to 2200 mm.



ULK



PULK

Cone Pipe Stoppers ULK

Type		ULK 15/40	ULK 25/60	ULK 30/80	ULK 40/100	ULK 50/120	ULK 60/140	ULK 70/160	ULK 80/180	ULK 120/220
Part-No.		1125	1120	1139	1121	1126	1122	1123	1138	1124
Pipe diameter	mm	150–400	250–600	300–800	400–1000	500–1200	600–1400	700–1600	800–1800	1200–2200
Operating pressure	bar	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0
Back pressure	bar	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Total length	mm	900	1100	1550	1950	2100	2450	2600	3000	3450
Weight	kg	2,9	4,0	10	13	17	27	35	38	71

Cone Test Pipe Stoppers PULK

Type		PULK 15/40	PULK 25/60	PULK 30/80	PULK 40/100	PULK 50/120	PULK 60/140	PULK 70/160	PULK 80/180	PULK 120/220
Part-No.		1233	1228	1246	1229	1234	1230	1231	1245	1232
Pipe diameter	mm	150–400	250–600	300–800	400–1000	500–1200	600–1400	700–1600	800–1800	1200–2200
Operating pressure	bar	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0
Back pressure	bar	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5	0,5
Total length	mm	1000	1200	1650	2050	2200	2550	2700	3100	3550
Weight	kg	3,9	11	21	24	28	40	49	52	86
Bypass		1"	2"	2"	2,5"	2,5"	2,5"	2,5"	2,5"	2,5"

Cone Pipe Stoppers ULK–2 bar

Type		ULK 15/40	ULK 25/60	ULK 30/80	ULK 40/100
Part-No.		1140	1141	1142	1143
Pipe diameter	mm	150–400	250–600	300–800	400–1000
Operating pressure	bar	2,0	2,0	2,0	2,0
Back pressure	bar	1,0	1,0	1,0	1,0
Total length	mm	900	1100	1550	1950
Weight	kg	3	4,3	10,5	14

Cone Test Pipe Stoppers PULK–2 bar

Type		PULK 15/40	PULK 25/60	PULK 30/80	PULK 40/100
Part-No.		1247	1248	1249	1250
Pipe diameter	mm	150–400	250–600	300–800	400–1000
Operating pressure	bar	2,0	2,0	2,0	2,0
Back pressure	bar	1,0	1,0	1,0	1,0
Total length	mm	1000	1200	1650	2050
Weight	kg	4	11,3	21,5	25
Bypass		1"	2"	2"	2,5"