

PIPE STOPPERS WITH EYES ON BOTH SIDES



The design of these stoppers is basically the same like the pipe stoppers type **U**, but they have extra handling eye on the back side. This supports easier manipulation and securing against being pushed out.

Pipe Stoppers with Eyes on Both Sides 2 0

Type		U 4/7	U 5/10	U 7/15	U 10/20	U 15/30	U 20/40	U 20/50	U 30/60	U 40/80	U 50/100	U 60/120
Part-No.		11278	11018	11028	11038	11078	11048	11288	11058	11348	11068	11088
Pipe diameter	mm	40–70	50–100	70–150	100–200	150–300	200–400	200–500	300–600	400–800	500–1000	600–1200
Operating pressure	bar	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	1,5
Back pressure	bar	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0	1,0	0,5
Diameter	mm	38	47	67	96	135	190	190	270	360	450	560
Length	mm	160	340	330	510	550	580	740	730	1000	1050	1290
Total length	mm	210	390	365	555	595	625	785	775	1070	1120	1360
Weight	kg	0,3	0,5	0,5	1,2	2,1	3,9	4,5	7,6	18	25	38

MULTITEST STOPPERS

These stoppers are used for pipe joints air leak test. The air leak test pressure is 0,001 MPa (100 mm of water column).



Multitest Stoppers MTU

Type		MTU 30/50	MTU 50/70	MTU 70/90
Part-No.		9228	9239	9259
Pipe diameter	mm	300–500	500–700	700–900
Operating pressure	bar	1,5	1,5	1,5
Back pressure	bar	0,5	0,5	0,5
Diameter	mm	290	480	680
Total length	mm	300	300	270
Weight	kg	8	11,5	17