

## IBS-Spezialreiniger WAS 30.100



**SKU:** 30.100

Alkaline high-performance concentrate. For gentle removal of heavy oil and grease soiling, with gloss and beading effect. For use as intensive cleaning in high-pressure cleaning and pre-spraying equipment, foam lance/cannon, wash station/wash holder, gantry system.



### Areas of application

- High pressure cleaning
- very suitable for pre-spraying
- Wiping method
- Wash bay / wash hall

### Suitable for

- Machine, equipment and vehicle exterior cleaning
- Industry, manufacturing trade
- Rail vehicles, vehicles with superstructures of all kinds
- Construction industry, road construction, agriculture, municipal enterprises
- all parts and surfaces of all branches, engines
- General basic cleaning
- Commercial vehicle tarpaulins and plastic casings - with gloss effect
- Hall and workshop floors

### Removes the following soiling

- Intensive pre-spray cleaner - strong for coarse soiling
- Grease, oil, incrustations and soot particles
- Easily removes hydraulic and engine oils

### Dosage

The product is a concentrate that must be diluted with sufficient water.

Our recommendation for the dosage:

- Light to normal soiling 3 - 5% 1:30
- particularly heavy soiling 6 - 10% 1:15

### Advantages

- cleans with gloss effect, beading effect — for polishing up, for the perfect finishing!
- remaining protective film protects the surface: water is repelled, the cleaned areas stay clean longer

- All in one — no separate drying aid necessary
- with integrated drying or drainage aid (no water and limescale residues)
- very good foam adhesion for better action and intensive cleaning
- protective of materials — also suitable for sensitive surfaces and workpieces (painted surfaces, copper, aluminium ...)
- demulsifying — therefore suitable for &ol;lab separators, tested separator friendliness
- fulfils the requirements of ÖNORM B 5104, B 5105 and B 5106 with regard to waste water
- Energy and cost-saving
- Strong action for pre-cleaning thanks to excellent foam adhesion
- environmentally compatible and user-friendly, surfactants easily biodegradable (according to OECD criteria)

## Technical data

Container size:	20 L, 200 L, 1000 L
PH value:	> 12,5
Colour:	gelb
Smell:	mild - charakteristisch
Foaming behaviour:	Haftschaum
Application concentration:	3 - 10 %
Operating temperature:	20° - 60° C
Density:	1,03 - 1,08 g/cm <sup>3</sup>