

Enclosed series    Ø max 1/2" - up to 20 m length  
 Ø max 3/8" - up to 25 m length

Automatic rewind, spring-driven hose reel, **enclosed series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 20 m length (Ø hose 1/2") or max 25 m length (Ø hose 3/8"). The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts. The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water.

Please see catalogue pages 164 and 165 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit**; please add suffix **"/HB"** to the article number (f. ex. 35300/HB)


**Please note: the spring brake kit is available only for art.nos. 35300-38310.**



Art.no. **39507**



Art.no. **39508**



Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 1/4" - 1/2"	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (D)	Weight
<b>35300</b>	Painted steel	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	15 m - 10 m	39507	9951	215x530x470	120 mm	26 Kg
<b>35400</b>		600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	20 m - 15 m				27 Kg	
<b>35300B</b>		100 bar	1" (M) - 3/4" (F)	20 mm	3/4"	8 m			245x530x470	150 mm	26 Kg
<b>35600</b>		600 bar	1/2" (M) - 1/2" (F)	10 mm	3/8"	25 m				29 Kg	
<b>38330</b>	Stainless steel AISI 304	100 bar	1" (M) - 3/4" (F)	20 mm	3/4"	8 m	39508	9968	245x530x470	150 mm	26 Kg
<b>38310</b>		200 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	15 m - 10 m				215x530x470	120 mm
<b>38320</b>		200 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	20 m - 15 m			245x530x470		150 mm
<b>38340</b>		200 bar	1/2" (M) - 1/2" (F)	10 mm	3/8"	25 m				29 Kg	