

LS series Ø max 1/2" - up to 20 m length



Art.no. **36271** Art.no. **36272**

LS series, automatic rewind, spring-driven hose reel, in black painted steel, suitable for hoses of max 20m length with diam. <1/2".

Reels are supplied as standard without the hose and are compatible with hoses for oil, antifreeze, grease, compressed air and water at low and high pressure.

Please see catalogue pages 164 and 165 for the selection of the required hoses.





Art.no. 39535

Art.no. 39502

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose	Spool width	Weight	Included swivel joint	Dimensions (LxWxH) (mm)
36271	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	15 m	120 mm	12 kg	39535	280x490x480
36272	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	20 m	150 mm	14 kg	39502	300x490x480

LS series Ø max 1" - up to 8 m length



Art.no. **36270**

LS series, automatic rewind, spring-driven hose reel, in black painted steel, suitable for hoses of max 8m length with diam. <1".

Reels are supplied as standard without the hose and are compatible with hoses for oil, antifreeze, grease, compressed air and water at low and high pressure.

Please see catalogue pages 164 and 165 for the selection of the required hoses.



Art.no. **39502**

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose	Spool width	Weight	Included swivel joint	Dimensions (LxWxH) (mm)
36270	20 bar	1" (M) - 1 (M)	20 mm	1"	8 m	150 mm	14 kg	39502	300x490x480