

Art.no. **36490**



Big series dual-spring hose reel with mechanical hoseguide system, designed for applications requiring hose lengths up to 60m (1/2" diam. hose).

This device, composed of steel housing with a worm drive inside, allows even long hoses to be correctly wound without becoming entangled.

The reel may be used to wind hoses for oil, antifreeze, air and water at low and high pressure.

In order to set up the hose guide correctly, the reel will only be supplied complete with the hose.

Please see catalogue pages 164 and 165 for the selection of the required hoses.

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose	Spool width	Weight	Dimensions (LxWxH) (mm)
<b>36490</b>	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	60 m	400 mm	69 kg	625x670x640

Art.no. **37490**



Big series dual-spring hose reel with mechanical hoseguide system, designed for applications requiring hose lengths up to 60m (1/2" diam. hose).

This device, composed of steel housing with a worm drive inside, allows even long hoses to be correctly wound without becoming entangled. The reel may be used to wind hoses for oil, antifreeze, air and water at low and high pressure.

In order to set up the hose guide correctly, the reel will only be supplied complete with the hose.

Please see catalogue pages 164 and 165 for the selection of the required hoses.

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose	Spool width	Weight	Dimensions (LxWxH) (mm)
<b>37490</b>	200 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	60 m	400 mm	69 kg	625x670x640