

LS series Ø max 1/2" up to 50 m length and Ø 1" up to 20 m length

Art.no. **38150 - 38160 - 38155 - 38165**



Manual, hand crank hose reel, **LS series**, in painted steel, suitable for hoses of max 50 m length in 1/2".

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water at low and high pressure.

Please see catalogue pages 164 and 165 for the selection of the required hoses.



Art.no. **39535**
Art.no. **39502**

Art.no. **38180**



Manual, hand crank hose reel, **LS series**, in painted steel, suitable for hoses of max 12 m length in 1" or max 15 m length in 3/4".

The hose reel is supplied without hoses and can be used with hoses for the supply of diesel, compressed air and water at low pressure.

Please see catalogue pages 164 and 165 for the selection of the required hoses.



Art.no. **39604**

Art.no. **38190**



Manual, hand crank hose reel, **LS series**, in painted steel, suitable for hoses of max 20 m length in 1" or max 25 m length in 3/4".

The hose reel is supplied without hoses and can be used with hoses for the supply of diesel, compressed air and water at low pressure.

Please see catalogue pages 164 and 165 for the selection of the required hoses.

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 1/4" - 3/8" - 1/2"	Spool width	Suitable pivoting wall bracket	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
38150	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	25 m - 20 m - 15 m	120 mm	39535	9951	8 kg	280 x 530 x 480
38160					50 m - 35 m - 25 m	150 mm	39502		9 kg	
38155					70 m - 50 m - 35 m	200 mm	39604		12 kg	320 x 530 x 480
38165					100 m - 70 m - 50 m	400 mm	-		15 kg	

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Spool width	Suitable pivoting wall bracket	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
38180	100 bar	1" (M) - 1" (M)	20 mm	1"	15 m - 12 m	200 mm	39604	9970F	12 kg	320 x 530 x 480
38190					25 m - 20 m	400 mm	-		15 kg	