

LSX series Ø max 1/2" up to 50 m length and Ø 1" up to 20 m length

Art.no. **38100 - 38115 - 38110 - 38130**



Manual, hand crank hose reel, **LSX series**, in stainless steel AISI 304, suitable for hoses of max. 50 m length in 1/2".

The hose reel is supplied without hoses and is recommended for the use with water at high and low pressure and with water-based fluids.

Please see catalogue pages 164 and 165 for the selection of the required hoses.



Art.no. **39600**
Art.no. **39601**

Art.no. **38120**



Manual, hand crank hose reel, **LSX series**, in stainless steel AISI 304, suitable for hoses of max. 12 m length in 1" or max. 15 m length in 3/4".

The hose reel is supplied without hoses and is recommended for the use with water at medium and low pressure and with water-based fluids.

Please see catalogue pages 164 and 165 for the selection of the required hoses.



Art.no. **39601**

Art.no. **39140**



Manual, hand crank hose reel, **LSX series**, in stainless steel AISI 304, suitable for hoses of max. 20 m length in 1" or max. 25 m length in 3/4".

The hose reel is supplied without hoses and is recommended for the use with water at medium and low pressure and with water-based fluids.

Please see catalogue pages 164 and 165 for the selection of the required hoses.

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 1/4" - 3/8" - 1/2"	Spool width	Suitable pivoting wall bracket	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
38100	200 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	25 m - 20 m - 15 m	120 mm	39600	9968	8 kg	280 x 530 x 480
38115					50 m - 35 m - 25 m	150 mm	39601		9 kg	
38110					70 m - 50 m - 35 m	200 mm	39601		12 kg	320 x 530 x 480
38130					100 m - 70 m - 50 m	400 mm	-		15 kg	

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Spool width	Suitable pivoting wall bracket	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
38120	100 bar	1" (M) - 1" (M)	20 mm	1"	15 m - 12 m	200 mm	39601	9970	12 kg	320 x 530 x 480
39140					25 m - 20 m	400 mm	-		15 kg	480 x 530 x 480