

Art.no. **37497-37496-37494-37495**



Hose reel, available in painted or in stainless steel AISI 304, with hydraulic **motor with hydraulic motor for hose rewind**. Suitable for hoses of max 100 m length in 1/2" or max 40 m length in 1".

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, grease, antifreeze, diesel, compressed air and water.

Art.no.	Hose reel material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 1/4" - 3/8" - 1/2"	Spool width	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
<b>37497</b>	Painted steel	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	130 - 120 - 100 m	400 mm	9951	50 kg	800x620x630
<b>37494</b>	Stainless steel AISI 304	200 bar						9968		
Art.no.	Hose reel material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Spool width	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
<b>37496</b>	Painted steel	20 bar	1" (M) - 3/4" (F)	20 mm	1"	50 m - 40 m	400 mm	9970F	50 kg	800x620x630
<b>37495</b>	Stainless steel AISI 304							9970		

Art.no. **37400**

Electro-hydraulic control kit, provided for the installation on the hydraulic motor of hose reels art. nos. 37497 - 37496 - 37494 - 37495, composed of electric gear pump, electric control switchboard, 5 m inlet and outlet hoses, 16 l - container and pressure regulating valve.



Pressure regulating valve for the control of the rewind strength.



Art. no.	Rewind pressure	Adjustment range	Voltage	Capacity oil container	Weight
<b>37400</b>	20 bar	0.5 - 20 bar	230 VAC	16 l	16 kg