

TOP-LINE cable reel

- reel body made of break-resistant, exceptionally flexible plastic.
- galvanized steel tube frame for optimal corrosion protection or powder-coated double tube frame
- no cable slipping behind the reel due to the special shape
- equipped with our patented cable guide as standard
- the built-in thermal overload protection switch with protection against restarting features a double safety system that helps prevent accidents
- safety plug (Schuko)
- 3 professional safety sockets (Schuko) with hinged lid
- 230 V / 16 A max. 3,500 W
- safety: tested according to EN 61242, DIN VDE 0620-1, DIN EN 50525-2

Bracket frame

Description	ø mm	Metre	Colour	Item-No.	PU
H07RN-F 3G1.5	240	25	black	40205	1
Empty reel up to 50 m H07RN-F 3G1.5 cable	290			40253	1
H07RN-F 3G1.5	290	40	black	40206	1
H07RN-F 3G2.5	290	25	black	40254	1
H07BQ-F 3G1.5	290	40	orange	40255	1
H07BQ-F 3G1.5	290	50	orange	40256	1
H07BQ-F 3G2.5	290	33	orange	40257	1

Double tube frame

Description	ø mm	Metre	Colour	Item-No.	PU
Empty reel up to 50 m H07RN-F 3G1.5 cable	290			40271	1
H07RN-F 3G1.5	290	25	black	40260	1
H07RN-F 3G1.5	290	40	black	40261	1
H07RN-F 3G1.5	290	50	black	40262	1
H07RN-F 3G2.5	290	25	black	40263	1
H07RN-F 3G2.5	290	33	black	40264	1
H07BQ-F 3G1.5	290	40	orange	40265	1
H07BQ-F 3G1.5	290	50	orange	40266	1
H07BQ-F 3G2.5	290	33	orange	40267	1
Empty reel up to 40 m H07RN-F 3G2.5 cable	310			40268	1
H07BQ-F 3G2.5	310	40	orange	40269	1



IP44



IP44

