

## TOP-LINE appliance reel

- reel body made of highly break-resistant, exceptionally flexible plastic
- powder-coated double-tube frame
- equipped with our patented cable guide as standard
- the built-in thermal overload protection switch with protection against restarting features a double safety system that helps prevent accidents.
- with front-end reel
- safety plug (Schuko) with 1.5 m supply cable on front-end reel and protective contact extension cable with 3-fold solid rubber coupling with self-closing hinged lids
- 230 V / 16 A max. 3,500 W
- safety: tested according to EN 61242, DIN VDE 0620-1, DIN EN 50525-2

| Description   | ø mm | Metre | Item-No. | PU |
|---------------|------|-------|----------|----|
| H07RN-F 3G1.5 | 290  | 25    | 40058    | 1  |
| H07RN-F 3G1.5 | 290  | 40    | 40059    | 1  |
| H07RN-F 3G2.5 | 290  | 25    | 40060    | 1  |
| H07RN-F 3G2.5 | 310  | 40    | 40061    | 1  |



IP44 CE



## TOP-LINE cable reel with PRCD

- reel body made of highly break-resistant, exceptionally flexible plastic
- galvanised steel tube bracket frame for optimum corrosion protection
- equipped with our patented cable guide as standard
- the built-in thermal overload protection switch with protection against restarting features a double safety system that helps prevent accidents
- 3 professional safety sockets (Schuko) with hinged lid
- with personal safety plug 30 mA
- 230 V / 16 A max. 3,500 W
- safety: tested according to EN 61242, DIN VDE 0620-1, DIN EN 50525-2, VDE 0661, VDE 0661-1 (HD63951)

| Description   | ø mm | Metre | Colour | Item-No. | PU |
|---------------|------|-------|--------|----------|----|
| H07RN-F 3G1.5 | 240  | 25    | black  | 40062    | 1  |
| H07BQ-F 3G1.5 | 240  | 25    | orange | 40063    | 1  |
| H07RN-F 3G1.5 | 290  | 40    | black  | 40064    | 1  |
| H07BQ-F 3G1.5 | 290  | 40    | orange | 40065    | 1  |



IP44 CE



LEITUNGSBESCHRIFTUNG siehe S.3