

TOP-LINE cable reel

- reelbody made of highly break-resistant, exceptionally flexible plastic
- galvanized steel tube frame for optimal corrosion protection or powder-coated double tube frame
- no slipping of the cable behind the reel due to the special design
- equipped with our patented cable guide as standard
- the built-in thermal overload protection switch with protection against restarting provides double safety that helps prevent accidents
- 1 CEE socket 400 V / 16 A, 5-pin +
2 professional safety sockets (Schuko) with hinged lid
- CEEplug supply cable 400 V / 16 A, 5-pin
- 230 V / 400 V / 16 A max. 10,500 W
- safety: tested according to EN 61242, DIN VDE 0620-1, EN 60309, DIN EN 50525-2

Bracket frame

Description	ø mm	Metre	Colour	Item-No.	PU
Empty reel up to 25 m H07RN-F 5G1.5-CEE cable	290			40066	1
H07RN-F 5G1.5-CEE	290	25	black	40600	1
H07RN-F 5G2.5-CEE	290	25	black	40602	1
H07BQ-F 5G1.5-CEE	290	25	orange	40069	1



IP44



Double tube frame

Description	ø mm	Metre	Colour	Item-No.	PU
H07RN-F 5G1.5-CEE	290	25	black	40071	1
H07RN-F 5G2.5-CEE	290	25	black	40072	1
Empty reel up to 33 m H07RN-F 5G2.5-CEE cable	310			40076	1
H07RN-F 5G1.5-CEE	310	40	black	40245	1
H07RN-F 5G2.5-CEE	310	33	black	40074	1



IP44

