



CLEANERS



LUBRICANTS



RELEASE AGENTS



ANTI-CORROSION




PAINTS



SPECIALTY



WELDING



ADHESIVES



ACCESSORIES



INDUSTRIAL PRODUCTS

MRO CHEMICAL SOLUTIONS





CLEANERS



LUBRICANTS



RELEASE AGENT



ANTI-CORROSION




PAINTS



SPECIALTY



WELDING



ADHESIVES



ACCESSORIES

CRC Industries is a worldwide supplier of chemical products for the industry, automotive and electro segments. The company consists of five operating groups headquartered in the United States, Belgium, the United Kingdom, Australia and South Africa . CRC Industries Europe is ISO 9001 certified.

We manufacture and supply cleaners, lubricants, anti-corrosion products, adhesives, welding products, additives, moulding products and other specialty products...all for the European, African and Middle East areas.

We guarantee high quality products by following strict guidelines in all facets of research, development and production. We try to meet today's most stringent environmental and safety standards. Furthermore CRC develops new products and continues to adapt existing products to meet the needs of our customers.

For detailed product information, Technical Data and Material Safety Data, please consult our website: **www.crcind.com**

“SEE FOR YOURSELF THAT CRC IS THE BEST SOLUTION!”

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend our products to be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

Note: The CRC product range is country-related. It is possible that some products, listed in the catalogue, might not be available. Product pictures not binding. Actual product may be different from picture due to change-over to new design.



CONTENT

MY CRC - WEB STORE	4-5
PICTOGRAMS - R2M	6-7
FPS (FOOD PROCESSING SAFE)	8-9
HACCP - ECO FRIENDLY PRODUCTS	10-11
CLEANERS	12-23
Overview	12-13
Precision	14-17
Industrial Degreasers	18-19
Ink, Glue, Paint, Plastic & Oxide removers	20-21
Handcleaners, Wipes & Disinfectants	22-23
LUBRICANTS	24-39
Overview	24-25
Cutting fluids	26-27
Oils	28-31
Dry	32
Greases	33-36
Pastes	37
Technical info	38
Polymer Processing	39
RELEASE AGENTS	40-48
Overview	40
Non Silicone Based Release Agents	41-43
Silicone Based Released Agents	44
Release Agents	45
Selection Guide	46-48
ANTI-CORROSION PRODUCTS	49-55
Overview	49
Temporary	50
Long-term	51-52
Specialty	53
Diagram	54
Polymer Processing	55
PAINTS	56-65
Overview	56
Marking & Signalisation	57-58
Other	59
Acryl	60-65
SPECIALTY PRODUCTS	66-68
WELDING PRODUCTS	70-75
Overview	70
Spatter release & Cleaners	71-72
Non-Destructive Testing (NDT)	73-75
ADHESIVES	76-77
Locking - Sealing	76
Bonding	77
ACCESSORIES	78
DISPLAYS	79
GLOSSARY	80
FPS PRODUCT SELECTION GUIDE	81
INDEX	82-83

MY CRC

AUTOMATIC TDS & MSDS UPDATES



A service offered to CRC end-users and distributors as a means to automate the task of updating Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS), reducing the burden on staff having to remember, schedule, and undertake this HSE requirement.

By using My CRC, the end-user can ensure 100% compliance, automatically when there is a change to the datasheets, whether due to legislative changes such as hazard classifications or amendments to European law. These changes do not affect the product performance or availability, but in a highly regulated industry - up to date compliance is essential to avoid prosecution. The ongoing REACH legislation will affect all processors, distributors, and users of chemicals throughout Europe, however, many people are unaware of what this means. Using My CRC ensures that such changes will be incorporated into the MSDS and TDS, with updates sent automatically.

Offered through the CRC website (www.crcind.com) a simple registration process provides access to the complete CRC product range where selection of relevant products takes place - receive only relevant products updates. The system remembers the selection, and will automatically generate an email notification when a significant change occurs to either the TDS or MSDS, keeping relevant management and user personnel up-to-date.

A unique service, making compliance easy!

- 24/7 availability on-line.
- Removes the potential to 'forget' to check for updates.
- Saves time & easy to use.
- Legislation changes frequently, do you always know when it has? Receive updates automatically in your mailbox.
- All information held securely.

MY CRC - DIRECTIONS

1. Navigate to [**www.crcind.com/crc**](http://www.crcind.com/crc).
2. Click on the My CRC logo.
3. Select the link "New User".
4. Fill in company details.
5. The unique log-in ID and password will be emailed to you.
6. Enter the log-in ID and password on My CRC.
7. Once logged in, select the country from the drop-down list at the top of the page. The complete list of CRC products will now be displayed - using the selection boxes on the right, both MSDS and TDS updates can be selected.
8. Please confirm your selection, My CRC instantly updates which boxes have been selected.
9. Once all products of interest have been selected, simply close your internet browser - the process is now finished.
10. If product selection needs to be modified, simply log-in to My CRC and change the update options (click on the My CRC logo to update email preferences).

CRC WEB STORE LIVE!

**24/7 ORDERING WHEN
YOU NEED IT**



SAFETY FLEXIBILITY SPEED



**24-7
ORDERING**



**LIVE STOCK
CHECK**



**INSTANT
PRODUCT
INFORMATION**



**SECURE
LOGIN**



**FAST-TRACK
ORDER
TEMPLATES**



**ORDER
HISTORY**



**MULTI-
BRANCH
SUPPORT**



**PERSONAL
SERVICE**

PICTOGRAMS



360° spray system

Use your CRC product in any required angle.
Can also be used upside down.



Clever-Straw

Wide spray in the DOWN-position, precise application in the UP-position.
(see p.28)



LOW GWP - Climate friendly

To avoid use and emissions of HFCs (R134a), CRC is proud to announce their climate-friendly HFO products. The new Low GWP (Global Warming Potential) icon will be displayed on all relevant packaging.




H₂O Based

These products are water based products.



Propane/butane
propellant

Active product



CO₂ propellant
Maximum 5%

Minimum 95%
Active product

More product, less propellant

We respect the environment and if it's technically possible, we fill the majority of our aerosols with CO₂. Besides the environmental aspect, this ensures you have on average over 40% more product.

MULTI-LANGUAGE CANS

- Depending on the market version, aerosol products display either 3 l languages per can or 8 languages as standard.
- This ensures foreign employees can use products and understand risk phrases
- CRC products can be exported globally for international branches and end-users
- Reduces risk of workplace accidents or inappropriate use and improves user safety
- All SDS are available in up to 3 l languages from www.crcind.com



RISK REDUCTION MOBILE: REMOTE CHEMICAL ASSESSMENT

SAFETY



- Driving compliance
- Auto update SDS
- Audit trail
- Reduced site visitors

SUPPLY



- Inventory control
- Remove rogue ordering
- Consolidate orders

QUALITY



- No more duplication
- Best product for job
- 100% support from manufacturer
- Expert advice

← **TOTAL COST BENEFIT** →

3 EASY STEPS:

① CONTACT:

Identify your customers' use of maintenance chemicals, purchases and inventory control.

② SUBMISSION:

Simply take a clear photograph of the products in the chemical cabinet or a chemical stores list, & use the Information Form (see below) to submit the enquiry.

③ 48 HOUR GUARANTEE:

We will analyse your submission and reply with Safety, Supply and Quality recommendations.

BEFORE

AFTER



**ACHIEVING 'TOTAL COST BENEFIT'
HAS NEVER BEEN EASIER**





NSF EXPLAINED

NSF is an abbreviation for the National Sanitation Foundation, which was founded in 1944 as a not-for-profit, non-governmental organisation. NSF International is a global provider of public health and safety risk management solutions to companies, governments and consumers. In 1999, it launched its voluntary Nonfood Compounds Registration Program to re-introduce the previous authorisation program administered by the U.S Department of Agriculture (USDA). Product evaluation is based on formulation and label review. Products which comply with the relevant regulations and guidelines receive a registration letter and are included in the 'NSF White Book™ Listing of Proprietary Substances and Non-food Compounds'.

Halal certification

All CRC HI/MI lubricants are Halal certified, helping clients in the food & beverage sector meet their audit requirements for this fast-growing market.

The Halal certification has been granted by the European Certification Centre (ECC) for Halal, an independent European audit center, based in the Netherlands. The certificate can be downloaded from the CRC website www.crceurope.com.

CRC FPS (Food Processing Safe)

Depending on the application, all CRC FPS products are designed for use in the food processing areas. Restrictions might apply to products having double codes when used as a "general purpose" C1 cleaner.

All CRC FPS products are NSF registered.

Food contact

Only H1 lubricants can be used where incidental food contact is possible.

Mould Release Agents

M1 General Mould Release Agents

NSF CATEGORIES

Lubricants

Used on food processing equipment as :

- anti-rust film (removal of film before re-using equipment)
- release agent on gaskets or seals of tank closures
- lubricant

H1 Lubricant with incidental food contact (in compliance with FDA 21 CFR, section 178.3570).

H2 Lubricant with no food contact.

Specialty

P1 Miscellaneous.

Cleaning products

Food & packaging materials to be removed or protected. Potable water rinse. No noticeable odor and no visual residue.

A1 General use.

General cleaning on all surfaces in all departments.

A7 Metal cleaners & polishes for non-food contact surfaces in all departments. Odors to be dissipated before food & packaging materials are re-exposed in the area.

A8 Degreaser/carbon removers for food cooking or smoking equipment (hence in all departments).

Odors to be dissipated before food & packaging materials are re-exposed in the area.

Non-processing area cleaning products.

C1 Use of cleaning or sanitizing products on equipment.

Water rinse required before returning equipment to the food processing area.

Solvent cleaners

K1 Cleaners & degreasers for use in non-processing areas.

Detergent wash + water rinse required before returning equipment to the food processing area.

K2 Solvent for cleaning electronic instruments.

Food & packaging materials to be removed or protected.

Odors to be dissipated before food & packaging materials are re-exposed in the area.

K3 Adhesive & glue removers for food packaging materials.

Food & packaging materials to be removed or protected.

Detergent wash + water rinse required before re-using.

Odors to be dissipated before food & packaging materials are re-exposed in the area.



FOOD SAFE THROUGH THE LINE



PREVENTION. NOT DETECTION.

**Maximum food safety with:
CRC Food Processing Safe® Perma-Lock® system.**

Engineered for performance and durability, CRC's Perma-Lock® 2-Way Integrated Actuator is the most secure top on the market. It prevents food contamination and guarantees a safe and hygienic use of H1 lubricants in all food processing areas.

Locked in for safety:

- Secure spray straw locks into place
- Fixed Perma-Lock® actuator
- Useful catch curb prevents dripping

CRC Perma-Lock® system – You just can't lose!



Perma-Lock®
2-WAY INTEGRATED ACTUATOR

FOOD
PROCESSING
SAFE

H1

NSF

www.crceurope.com

HACCP

HAZARD ANALYSIS CRITICAL CONTROL POINTS

HACCP is a preventive risk inventory program, developed for companies involved in manufacturing, processing, handling, packaging, distribution and shipment of food products (from raw materials and consumables to finished products). **HACCP** is not a manual as such, but an inspection program, that involves **7 principles** :

1. Systematic inventory of all potential hazards / risks.
2. Identification of the critical control points (CCP's) : points in a stage where the risk can be avoided or minimized.
3. Select critical barriers / indicative values and tolerated nonconformities per CCP.
4. Monitoring the CCP's.
5. Capture corrective actions to reinsure safety.
6. Set up verification procedures : repeated inspection to make sure the HACCP approach is working properly.
7. Update documentary system : handbook - recordkeeping.

Origin

HACCP took its roots from US aerospace travel : overdue food products could not be returned to the factory to get fresh replacements. Possible failure of a high-priced mission through food intoxication would be an unacceptable risk.

Goals

- To guarantee and improve food safety : this requires high priority and is maintained by determining and keeping under control the hazardous health risks in manufacturing and handling processes.
- Minimize the risks : this control program, originated by the European Union, is designed to constrain the potential food contamination risks (microbiological, chemical, physical) in all food processing areas.
- Consideration of hazard's frequency and severity rate (risk = probability × effect).
- Fast and efficient interference in case of contamination problems.

Advantages

- Achieving a total quality management system.
- HACCP certificate: to be used as a quality standard.
- Manufacturer's actions are structurally monitored.
- Adequate hygienic working practices.
- Commercial advantage: this kind of food safety quality program is required by most customers.

CRC & HACCP

CRC Industries Europe launches a complete range of NSF registered products.

- These products will support existing HACCP programs or help establishing a new HACCP system.
- We are able to supply the food processing industry with a full range of required NSF registered products.
- We offer a full documentation and product training.
- The unique color coding CRC developed, enables a better control of the critical control points in the production process.



ENVIRONMENT

ECO FRIENDLY PRODUCTS



DEFINITION

The terms "ECO", "GREEN", "BIO" ...are often used referring to different kinds of products, but do not really have a clear, unmistakable meaning as long as these characteristic words do not get a legally binding definition.

In case of chemical products, proper registrations can only be provided through test analyses performed by internationally recognized testing laboratories.

CRC'S APPROACH

CRC has chosen to apply for registration of these products in accordance with OECD test guidelines (Organisation for Economic Co-operation and Development).

Particularly for our investment in sustainable innovation and our concern for our consumer's health, CRC now offers a full range of high performance products which have a low impact on our environment. This range of products has been currently categorised into 2 levels:

LEVEL 1



High level of biodegradability in accordance with the OECD 301B standard. Products meeting this standard will be labelled holding this logo. They will also carry the term "ECO" in their titles.

Biodegradation test OECD 301B

- A high concentration of the test material is mixed with a bacterial mixture and the ultimate degradation within 28 days period is evaluated based upon the CO₂ production. A product is considered "readily biodegradable" when 60% of the theoretical amount of CO₂ is produced within the 28-day period of the test.
- A negative result does not necessarily mean that the product will not be degraded under relevant environmental conditions. It is generally accepted that products reaching between 20 and 60% biodegradability can be considered as "inherently biodegradable".

LEVEL 2



Environmentally preferred products.

Each product will meet a certain selection of ecological criteria: The total of general criteria and a minimum of 3 extra specific criteria (see right column).

GENERAL CRITERIA (Exclusion Criteria)

1. Each formula will not contain:

- Heavy metals such as mercury (Hg), lead (Pb), cadmium (Cd) etc. known for their toxicity and persistence in the environment. (ref 1)
- Substances of Very High Concern (SVHC). (ref 2)
- Substances with a Global Warming Potential > 150 such as HFC's. (ref 3)
- RoHS listed substances. (ref 4)
- Nitrites.
- Aromatic hydrocarbons.
- Chlorides & bromides.
- Phosphates and Nonyl Phenols in case of cleaners.

2. Each formula will not be classified as "toxic or very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment".

3. Each formula will not be classified as "may cause sensitization by inhalation and skin contact".

PRODUCT SPECIFIC CRITERIA (Inclusion Criteria)

Each formulation will meet a minimum of three of the following criteria (product category depended).

1. Main component is water or contains at least 50% renewable materials (ref 5). In case of lubricants the amount of renewable material is at least 70%, in case of greases at least 45%. (ref 6)
2. Formula contains less than 10 % Volatile Organic Components (VOC).(ref 7)
3. Ecological packaging. (ref 8)
4. For products listed as corrosion protection, provide a Salt Spray protection of at least 250 hours. (ref 9)
5. Inherently biodegradable according to OECD 302C*. (ref 10)
6. Readily biodegradable according to OECD 301**. (ref 11)
7. Meets the criteria of the European Eco-Label (see also www.eco-label.com). (ref 12)

Ref 1. E. Lawrence, A. R. W. Jackson, J. M. Jackson (Eds.), Longman Dictionary of Environmental Science, Addison Wesley Longman, Harlow (1998). Ref 2. Annex XV, Regulation (EC) 1907/2006 concerning the Registration, Evaluation, Authorization and Restrictions on Chemicals Ref 3. Directive 2006/40/EC relating to emissions from air-conditioning systems in motor vehicles. Ref 4. Directive 2002/95/EC of the European Parliament and of the council of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. Ref 5. Commission decision 2005/360/EC establishing ecological criteria and the related assessment and verification requirements for the award of the Community eco-label to lubricants, Annex, paragraph 5 Ref 6. Commission Decision 2005/360/EC establishing ecological criteria and the related assessment and verification requirements for the award of the Community eco-label to lubricants, Annex, paragraph 5 Ref 7. Commission Decision 2005/344/EC establishing ecological criteria for the award of the Community eco-label to all-purpose cleaners and cleaners for sanitary facilities, Annex paragraph 8 - Volatile organic components with a boiling point lower than 150°C Ref 8. ecological packaging: Directive 94/62/EC on packaging and packaging waste. Ref 9. ASTM B117 Ref 10. inherently biodegradability (modified MITI test): OECD 302C Ref 11. readily biodegradability: OECD 301 (A-F) Ref 12. Commission decision 2005/360/EC for lubricants - Commission decision 2005/344/EC for cleaners








*/ ** BIODEGRADATION = the breakdown of chemical substances by living organisms. The end result of biodegradation is often the complete conversion of organic substance to CO₂ and water.

* INHERENT BIODEGRADABILITY (OECD 302): Test performed under more favourable conditions for biodegradation. Chemicals that pass an inherent biodegradability test are considered non-persistent, although the breakdown of the chemical in the environment may be slow.

** READY BIODEGRADABLE (OECD 301): Test performed in most stringent test conditions. Chemicals that are shown to pass a ready biodegradability test rapidly degrade in wastewater treatment plants and in the natural environment.

PRECISION

DUST REMOVAL

  	  	
DUST FREE 360 TURBO	DUST FREE 360	DUST CLEANER
Very powerful	Powerful	Powerful










CLEANING OF LIGHT CONTAMINANTS

  			  		
FLATSCREEN CLEANER	OXIDE CLEAN PLUS	CONTACT CLEANER PLUS	CONTACT CLEANER	QD-CONTACT CLEANER	N.F. ELECTRONIC CLEANER
Flatscreens	Degreases, de-oxidizes + protects	Degreases, de-oxidizes + protects Non flammable	Plastic safe: Yes	Plastic safe: Yes	Plastic safe: Yes Non-Flammable

HEAVY-DUTY

INDUSTRIAL DEGREASERS


	  	   		   
LECTRA CLEAN II	INDUSTRIAL DEGREASER	INDUSTRIAL ECO DEGREASER	FAST DRY DEGREASER	ECO COMPLEX BLUE
Very Powerful Drying: Slow	Powerful Drying: Medium	Powerful Drying: Medium/Fast	Plastic safe: Yes Drying: Fast	All type of surfaces

   		   
ECO FOAM CLEANER	PROFESSIONAL CLEANER	INOX KLEEN
Vertical surfaces	General cleaner	Shine metals & protects

HEAVY-DUTY

INK, GLUE, PAINT, PLASTIC & OXIDE REMOVERS

			
MOULD CLEAN	POLYMER REMOVER	GRAFFITI REMOVER	LABEL OFF SUPER
Plastic and polymer residues	Plastic and polymer residues Very powerful gel	For ink & paint	For paper labels.

	
INOX WELD KLEAN	FERROKLEEN
Pickling paste	Removes oxides

HAND CLEANERS, WIPES AND DISINFECTANTS

LIQUID SOAP

	
SUPER HANDCLEANER	CITRUS HANDCLEANER
Soft for the skin Tough with the contaminants	

WIPES

	
WIPES IND	
Skin care	For heavy contaminants

MULTI
PURPOSE

DISINFECTANTS

	
MULTI SURFACE CITRO CLEANER	MULTI SURFACE CITRO COVKLEEN
Cleans + >80% alcohol Plastic compatibility: Yes	Cleans + disinfects Plastic compatibility: Yes

CLEANERS - PRECISION

DUST FREE 360 TURBO

Extremely powerful non flammable dust remover for all de-dusting applications.

CRC Dust Free 360 TURBO is a dry inert gas which leaves no residue and offers an extra strong output to remove more stubborn dirt on all kinds of surfaces.

Benefits :

- Non-flammable for safe use (HFO propellant)
- Invertible: Can be used upside down
- Prevents errors & downtime
- Can be used in food processing areas
- Extension tube for hard to reach areas (15 cm)

Applications :

- Electro-mechanical assemblies
- Electrical aggregates
- Electronic components
- Printed circuit boards
- Coin mechanisms
- Precision instruments




Ref.	SIZE
33286	Aerosol 250 ml



DUST FREE 360

Non-flammable high pressure dust remover.

Efficient high pressure liquid gas that removes dust and cleans with a powerful jet of dry inert gas. It prevents errors, downtime and damage caused by microscopic dust. Leaves no residue or condensation. Designed for use as a cleaner for electrical or electronic equipment in food processing or non-processing areas.



Ref.	SIZE
33158	Aerosol 125 ml
33114	Aerosol 250 ml



DUST CLEANER

Flammable residue-free dust remover.

For use on electro-mechanical assemblies, electrical aggregates, electronic components, printed circuit boards, coin mechanisms and precision instruments. Clean, dry and non-oily. The CRC Dust Cleaner has no ozone depleting actions.



Ref.	SIZE
32613	Aerosol 500 ml





DUST FREE 360 TURBO

THE HURRICANE IN A CAN



www.crcind.com

FLATSCREEN CLEANER

Safe cleaning of all flat screen types, LCD or TFT displays and scanner glass.

Stable foam formulation that does not run or drip off. Will quickly remove numerous different types of soiling and contamination of touch screens and displays. Suitable for use on a wide variety of hard surfaces throughout industries.



Ref.	SIZE
32221	Aerosol 500 ml



OXIDE CLEAN PLUS

2 in 1 : Cleaner and lubricant for all types of high security contact treatment.

The non-flammable product allows usage even while the to be treated surface is under electrical tension. Quickly penetrates, removes oxides and deposits and loosens the contacts. Lubricates contact surfaces and provides optimum flow of electric current. Very safe to use thanks to its non-flammable mixture, eliminates the risk of arcing and leakage. After evaporation, Oxide Clean Plus restores the electrical flow and leaves a protective film.



Ref.	SIZE
33192	Aerosol 250 ml



CONTACT CLEANER

Effective precision cleaner.

Residue-free contact cleaner for use on PCB's and electronic equipment. Fast drying. Not for use on energized equipment. Developed for use as a cleaner for electrical or electronic equipment in food processing or non-processing areas.



Ref.	SIZE
32662	Aerosol 250 ml
12101	Aerosol 500 ml



CONTACT CLEANER PLUS

Cleaning, de-oxidation, lubrication and protection of electrical contacts.

Safe on plastic and rubber. CRC Contact Cleaner Plus provides long lasting lubrication which is safe to use on all metal surfaces, most rubbers, plastics and coatings. Contact Cleaner Plus is non corrosive. It also has a no ozone depleting action.

Ref.	SIZE
32704	Aerosol 250 ml
32180	Aerosol 500 ml



QD-CONTACT CLEANER

Quick drying solvent cleaner for light contaminants on electric or electronic parts.

Also compatible with sensitive plastics. Quick drying solvent blend for the cleaning of electronic equipment. It provides a suitable precision cleaning action for sensitive electronic and electrical components without risk of costly damage. CRC QD-Contact Cleaner is a stable, inert, high purity solvent cleaner; formulated for applications where lower flash point solvents may be used and where sensitive plastics are involved.

Ref.	SIZE
32671	Aerosol 250 ml
32429	Aerosol 500 ml



N.F. ELECTRONIC CLEANER

Non-flammable solvent cleaner for light contaminants on electrical or electronic parts.

A unique non-flammable precision cleaner suitable for cleaning and degreasing all types of electrical and electronic components where a shutdown is either impossible or very expensive. CRC N.F. Electronic Cleaner is free of chlorinated solvents, CFC's and HCFC's; solvent based, non-flammable, dries fast.

Ref.	SIZE
33116	Aerosol 250 ml



CLEANERS - INDUSTRIAL DEGREASERS

LECTRA CLEAN II

Solvent cleaner with high flashpoint for heavy contaminants on mechanical parts.

Heavy-duty cleaner with a high flashpoint of over 60°C for improved application safety. The extended drying time allows the product to act during a longer period and to dissolve heavy contaminations. Suitable for use in dip baths and ultrasonic dip tanks.

Ref.	SIZE
30449	Aerosol 500 ml
10314	Bulk 5 L
10315	Bulk 20 L
30450	Bulk 200 L



INDUSTRIAL DEGREASER

Solvent cleaner for heavy contaminants on mechanical parts.

Powerful, fast evaporating cleaner with a flash point of 25°C. Removes greases, oil, lubricants, non-cured adhesives and dirt from equipment, machines and metal parts. When applying to large surfaces or in dip baths, ensure explosion prevention. Test on plastics before use.

Ref.	SIZE
10321	Aerosol 500 ml
10325	Bulk 5 L
10326	Bulk 20 L



INDUSTRIAL ECO DEGREASER

Fast drying solvent cleaner, for dissolving heavy contaminants in food processing areas.

A solvent blend designed for use in the food industry; NSF A8,C1 registered. The flash point is 40°C for safe application. Dissolves grease, oil, lubricants, and non-cured adhesives.

Ref.	SIZE
33344	Aerosol 500 ml
33345	Bulk 5 L
33348	Bulk 20 L



FAST DRY DEGREASER

Fast drying solvent cleaner for heavy contaminants on mechanical parts, suitable for most plastics.

- Effectively removes all types of dirt, oil, grease and industrial dirt
- A very quick drying cleaner and leaves no residue after cleaning
- The sprayer is equipped with a comfortable gun spray head
- Has a high level of compatibility with materials
- Thanks to its high degreasing effect, it is particularly recommended for cleaning before gluing or painting.
- Spray head with 360 ° spray technology: easy to use even in hard to reach places
- Low flash point for better safety reducing working time

Ref.	SIZE
10227	Aerosol 500 ml
10230	Bulk 5 L
10233	Bulk 20 L
33262	Bulk 60 L
31927	Bulk 200 L



ECO COMPLEX BLUE

Non-flammable, slow drying water based cleaner for heavy contaminants in food processing areas.

A water based degreaser for use in the food industry; NSF A1 registered. It exists in concentrated and ready to use form for increased convenience and economy. Excellent product for use in dip tanks, pressure washer, ultrasonic and steam cleaning equipment. Dilute according to information on the datasheet. Safe on plastics. Rinse with water after application. Readily biodegradable concentrate according to OECD 301B: >64%.



Ref.	SIZE
10286	Handsprayer 750 ml
10282	Bulk 5 L
12127	Bulk 5 L + Sprayer
20123	Bulk 20 L
30431	Bulk 200 L



ECO FOAM CLEANER

Non-flammable, slow drying water based cleaner, suitable for removing heavy contaminants in vertical applications in food processing areas.

A concentrated, water based degreaser for use in the food industry; NSF A1 registered. The stable, non-dripping foam formula ensures a long contact with the contamination, especially on vertical surfaces. Rinse with water after application. Readily biodegradable according to OECD 301B: 64%.

Ref.	SIZE
10278	Aerosol 500 ml



PROFESSIONAL CLEANER

General cleaner for use in general engineering for fast results.

For precision work and re-assembling of new parts, use fast dry degreaser.

Ref.	SIZE
33364	Aerosol 500 ml



INOX KLEEN

Water based, foaming cleaner for degreasing and cleaning shiny metal surfaces.

CRC Inox Kleen is NSF A7,C1 registered for use in the food industry. It eliminates fingerprints, watermarks, dust and dirt from stainless steel. It leaves a protective non-greasy barrier for a long-term original aspect and provides metal surfaces with a long-term staining and contamination resistance. CRC Inox Kleen is also suitable for aluminum, chrome and most plastics (test prior to use).

Ref.	SIZE
20720	Aerosol 500 ml



CLEANERS - INK, GLUE, PAINT, PLASTIC & OXIDE REMOVERS

LABEL OFF SUPER

Label remover.

Solvent mixture, free of CFC's and HCFC's. Removes self-adhesive paper labels from most surfaces in 2-3 minutes after wetting (test on plastics prior to use). NSF listed as an adhesive and glue remover (NSF K3).

Ref.	SIZE
32668	Aerosol 250 ml
32314	Aerosol 400 ml



K3

INOX WELD KLEEN

Restores the original characteristics of Stainless Steel after welding.

CRC Inox Weld Kleen is a pickling paste that restores the original characteristics of stainless steel after welding or heat treatment. Degreasing, cleaning, pickling and passivating of austenitic and duplex stainless steel 303, 304, 316,... , nickel and aluminum. Fast-working, very efficient, economical and practical to use.



Ref.	SIZE
30379	Bulk 2 Kg



FERROKLEEN

Cleans painted and bare metal surfaces contaminated with rust, lime, algae, oils and tar.

Takes rust and rust stains on painted or plastic surfaces away. Effective against a wide range of scales. Non flammable. Slightly foaming. Composed of > 90% anorganic components and biodegradable organic components. Not classified as dangerous for the aquatic environment.

Ref.	SIZE
30112	Bulk 1 kg
30089	Bulk 5 kg
30199	Bulk 20 kg



MOULD CLEAN

General cleaner for mould tools

A powerful solvent blend formulated to remove a wide range of common soiling from moulds, tools and dies.

- Quickly and easily removes oils, grease, old protective films
- Perfect for removing old release agents. Takes away old build ups in the mould
- Leaves a clean, dry and residue free surface
- Dissolves residues of polymers



Ref.	SIZE
32840	Aerosol 500 ml

POLYMER REMOVER

Heavy duty mould cleaner

Highly effective and powerful solvent blend developed for use on heavily soiled moulds and dies to remove a variety of moulding deposits.

- Foaming action which clings to the mould surface and facilitates a good contact with the contamination
- Removes: plastics, rubbers and resin residues, even when carbonized
- Thixotropic formulation for maximum efficiency, even on vertical surfaces
- Leaves a clean and dry surface after application



Ref.	SIZE
32961	Aerosol 400 ml

GRAFFITI REMOVER

Removes all traces of paint and ink.

Dissolves and loosens unwanted paint and inks from aerosols, pens and markers. Safe to be used on most substrates. In case of doubt, test prior to application. Prevents damage to the original surface due to excessive scratching. Does not leave an acid or alkaline residue, which could damage concrete, plaster or cement.



Ref.	SIZE
20717	Aerosol 400 ml

CLEANERS - HANDCLEANERS & WIPES

SUPER HANDCLEANER

Handcleaner for heavily contaminated hands.

Contains beside the mild solvents and biodegradable surfactants, also small friction parts from natural sources. Very effective on grease, carbon and most stubborn contaminations.

Ref.	SIZE
30675	Tube 150 ml
30676	Bulk 2,5 L



CITRUS HANDCLEANER

Professional solvent-free hand cleaner with Aloe Vera, Jojoba and an environmentally friendly abrasive.

Mild for the skin. Fresh fragrance. Removing easily: lubricants, grease, tar, brake fluids and bitumen.

Integrated pump

Ref.	SIZE
32321	Bulk 3,8 L



WIPES IND

Multipurpose industrial strength cleaning wipes.

Removes oil, grease, paint, ink and adhesives of different surfaces. The textured side of the wipe will gently but efficiently remove all contamination. The smooth side of the wipe will effectively retain contamination.

High absorbency cleaning wipes layered with an effective polymer web to give all the cleaning power of pumice without the scratching. Highly effective on a range of soiling types adhesives, tar, bitumen, resins, silicone grease, oils, petrochemicals, paints, and more. Cleaner and towel together in one convenient wipe. Contains skin conditioner to replace natural oils removed in cleaning. No contamination from heavy perfumes.

Ref.	SIZE
20246	Tub 50 wipes
12006	Bucket 100 wipes



MULTI SURFACE CITRO CLEANER

Multi-functional cleaner & contaminant remover 2 in 1

Multi-Surface Citro Cleaner is a powerful, versatile, professional grade, extremely high alcohol content spray for cleaning and eliminating contamination from all common surfaces. It has been formulated specifically for use on high touch-point surfaces such as work benches, tool cases, tools, and as a general workplace cleaner. It quickly removes grime, dirt, oils, viruses, bacteria and germs from most surfaces, including metal, stone, fabrics and most plastics.

Ref.	SIZE
33343	Aerosol 500 ml
33361	Bulk 5 L



MULTI SURFACE CITRO COVKLEEN

Multi-functional cleaner & disinfectant 2 in 1

Multi-Surface Citro COVKleen is a powerful, versatile, professional grade, extremely high alcohol content spray for cleaning and disinfecting all common surfaces. It has been formulated specifically for use on high touch-point surfaces such as work benches, tool cases, tools, and as a general workplace cleaner. It quickly removes grime, dirt, oils, viruses, bacteria and germs from most surfaces, including metal, stone, fabrics and most plastics.

Ref.	SIZE
33342	Aerosol 500 ml



LUBRICANTS

CUTTING & DRILLING

CUTTING



THREADING



OILS

WOOD



METAL



METAL



PLASTIC SAFE



WIRES



SPINDLES & SLIDES



MULTIPURPOSE



CHAINS



DRY LUBRICATION

METAL & PLASTICS



FOOD PROCESSING AREAS



HIGH PRESSURE HIGH TEMPERATURE



GREASES

MULTIPURPOSE



HIGH LOADS



ADHESIVE



HIGH SPEED



SILICONE BASED



EXTREME PRESSURE



HIGH TEMPERATURE



PASTES

METAL BASED




CERAMIC BASED



ASSEMBLY



ROUGH TREADED AND SLIDING STEEL



POLYMER PROCESSING



LUBRICANTS - CUTTING FLUIDS

SUPERCUT

Low viscous cutting liquid for normal, metal cutting operations.

Non-chlorinated, high performance cutting liquid. Reduces heat created by friction, cools by transferring heat away from cutting tools and removes shavings out of the cutting area. Increases the tool life considerably and protects freshly machined parts from rusting.

Ref.	SIZE
32687	Aerosol 250 ml
32210	Aerosol 400 ml
30353	Bulk 1 L
20457	Bulk 5 L
30354	Bulk 20 L



ECO SUPERCUT

Biodegradable cutting oil.

Natural straight oil, free of chlorine, for cutting operations in ferro, non-ferro and aluminium. Cools by transferring heat away from cutting tools, reduces heat created by friction and removes shavings out of the cutting area. Protects freshly machined parts from rusting and increases the tool life considerably. Readily biodegradable according to OECD 301B: 87%.



Ref.	SIZE
31911	Aerosol 500 ml



LUB 21

Semi-synthetic cutting fluid for cutting and rectification operations on all kinds of metals (steel, copper, aluminum, stainless steel, etc.).

This cutting fluid provides a significant extension of the life time of cutting tools and gives a superb anti-corrosion coating to the machined parts. The cuttings are evacuated more easily. Compared to traditional fluids, CRC LUB 21 has a considerable extended life time.

Ref.	SIZE
20248	Bulk 5 L
30405	Bulk 25 L



SUPER TAPPING FLUID

High viscous cutting liquid for extreme metal tapping operations.

Non-chlorinated, high performance tapping fluid. Designed for high-pressure applications. Reduces heat created by friction, cools by transferring heat away from cutting tools and removes shavings out of the cutting area. Increases the tool life considerably and protects freshly machined parts from rusting.

Ref.	SIZE
32686	Aerosol 250 ml
30398	Bulk 1L
20552	Bulk 5 L



SUPER TAPPING COMPOUND

Specialist metal cutting compound.

CRC Super Tapping Compound is an instant, ready-to-use metal machining compound with excellent high cling and extreme pressure resistance properties. It provides an extreme-pressure resistant, tenacious film between the tool cutting edge and the work piece, ensuring an excellent surface finish and an extended tool life.

Ref.	SIZE
30706	Bulk 500 g



WOOD GLIDER

Improves the sliding of unprocessed wood on working tables of wood processing machines.

Colorless product without silicones. Produces a very low coefficient of friction. Suitable for all wood types. Safe on all metal surfaces, does not stain. Can be used on plastic drives and sliding mechanisms, guide rails, working and positioning tables of all wood working machines.

Ref.	SIZE
32244	Aerosol 400 ml



LUBRICANTS - OILS

3-36

Light lubricating oil, good penetration for general use.

A universal lubricating oil with excellent penetrating properties. Suitable as multipurpose lubricant for simple applications. Gives also a good corrosion protection for indoor stored parts.

Ref.	SIZE
32673	Aerosol 250 ml
10110	Aerosol 500 ml
10114	Bulk 5 L
30362	Bulk 20 L
30364	Bulk 200 L



5-56 + PTFE

Multifunctional service spray for use in the professional mechanical maintenance.

Contains PTFE for an extended lubrication function under industrial conditions. Performs extremely well when frequent start, stop or alternating movements occur. Displaces moisture and prevents electrical failure. Provides a good protection against corrosion. Ultimate penetration capacity for de-blocking threaded connections or clamped metal surfaces. Cleans and protects surfaces contaminated by machining or handling.

Ref.	SIZE
32703	Aerosol 250 ml
33199	Aerosol 500 ml Clever-Straw
32550	Bulk 5 L



POWER LUBE

Light lubrication oil with PTFE, for frequent start-up situations.

Superior lubricant for universal use, containing PTFE. Provides a long-lasting protection against wear, friction and corrosion.

Ref.	SIZE
32648	Aerosol 500 ml



ROST FLASH

Rust loosener with freeze shock effect.

When sprayed onto a rusted nut bolt connection, the rust cools down (-40°C) and cracks, leaving small fissures. The active liquid will rapidly penetrate into those small openings and blocked parts are separated easily. CRC Rost Flash loosens all kinds of threaded parts, hinges and sliding parts. Free of silicones and acids.

Ref.	SIZE
10864	Aerosol 500 ml



RUST OFF IND

A penetrating oil that quickly frees and lubricates seized mechanisms.

Quickly penetrates through corrosion and soil. Frees seized and rusted bolts, nuts and other metal components.

Leaves a lubricating MoS₂ film.

Ref.	SIZE
32688	Aerosol 250 ml
30507	Aerosol 500 ml



PEN OIL

A penetrating oil that quickly frees and lubricates seized mechanisms.

Quickly penetrates through corrosion and soil. Frees seized and rusted bolts, nuts and other metal components.

Especially designed for use in the food industry.

NSF H1 registered.

Ref.	SIZE
32606	Aerosol 500 ml



ECO PEN OIL

A biodegradable penetrating oil.

Lubricates and frees seized and rusted metal parts (bolts, screws,...). Facilitates dismantling. Penetrates easily through corrosion and soil. Readily biodegradable according OECD 301B: 89%.

Ref.	SIZE
31909	Aerosol 500 ml



SILICONE IND

Synthetic lubricating oil, suitable for plastic drives and applications at high temperatures.

Superior synthetic lubricant with a premium grade high quality silicone. CRC Silicone IND exhibits superior lubrication and temperature/viscosity characteristics.

Reduces friction and noise on non-metal parts.

Ref.	SIZE
32635	Aerosol 500 ml
30053	Bulk 5 L



SILICONE

Food Processing Safe, synthetic lubricating oil, suitable for plastic drives and applications at high temperatures.

Superior synthetic lubricant with a premium grade high quality silicone. CRC Silicone exhibits superior lubrication and temperature/viscosity characteristics.

NSF H1 registered. It reduces friction and noise on non-metal parts, throughout the food industry.

Ref.	SIZE
31262	Aerosol 500 ml
32679	Bulk 5 L



SILICONE EXTRA

Multi-use synthetic lubricant.

CRC Silicone Extra is based on a blend of high quality, stable silicone oils, ensuring superior lubrication and reducing friction in most metal and non-metal applications. It provides also excellent separation and release properties.

Ref.	SIZE
30769	Aerosol 500 ml
10529	Bulk 5 L



WIRE ROPE LUBE

Heavy-duty lubricant.

Formulated to provide protection and lubrication under all operating conditions. The product penetrates deeply for internal protection of wire ropes, racks and pinions, crown wheels and cams, driving mechanisms in the construction, shipyard, docks and marine, quarrying, heavy engineering, automotive and manufacturing industries.



Ref.	SIZE
32334	Aerosol 500 ml

SLIDEWAY OIL

Low viscosity oil for high speed spindle and slide ways lubrication.

Low viscosity, good affinity to metals, excellent water resistance, reduces stick and slip problems, high load capacity, thin durable lubricating film.

Applications:

Guide rails, adjustment mechanisms, ball-joints, rotating positioning surfaces.



Ref.	SIZE
32146	Aerosol 500 ml

MULTI OIL

Food Processing Safe, light multipurpose oil for general use.

Extremely efficient and effective general-purpose lubricant, for use in the food industry. CRC Multi Oil is NSF H1 registered, exhibits an excellent penetrating ability and loosens rust, scale, dirt and corrosion.



Ref.	SIZE
32605	Aerosol 500 ml
20157	Bulk 5 L

CHAIN LUBE

Food Processing Safe, heavy lubricating oil for driving and transport chains.

High performance, foaming lubricant, containing PTFE. CRC Chain Lube is compatible with o-rings, highly resistant to splash water and prevents corrosion to occur. The properties and the NSF H1 registration make the product an excellent lubricant for chains in the food industry.

Ref.	SIZE
33236	Aerosol 500 ml
30033	Bulk 5 L



CHAIN LUBE IND

Heavy lubricating oil for driving and transport chains.

High performance, foaming lubricant containing PTFE. CRC Chain Lube IND is compatible with o-rings, highly resistant to splash water and prevents corrosion to occur. An excellent lubricant for chains in an industrial environment.

Ref.	SIZE
33237	Aerosol 500 ml



HIGH SPEED CHAIN OIL

Water resistant chain lubricant.

A specially formulated blend of high quality mineral and synthetic oils, anti-oxidation and antiwear additives, friction modifiers and tackiness agents. Penetrates deeply into vital chain pin and bushing areas, then sets to form an adhering, long lasting lubricating film. Designed even for highly loaded fast running chains used in corrosive, high power and shock load conditions. Resists hot and cold water wash-off and high rpm sling-off. Reduces friction, wear, noise and vibration. Extends the chain life and is O-ring compatible. Harmless to metals, most plastics and rubbers.

Ref.	SIZE
33247	Aerosol 500 ml



LUBRICANTS – DRY

DRY LUBE

PTFE lubricant for dry lubrication and use on plastic friction points.

CRC Dry Lube is a fast drying dispersion of white, waxy PTFE particles, leaving a dry lubricating film on the surface. The product exhibits outstanding anti-stick and release properties. As a lubricant, it is most effective at reduced speeds and low loads.



Ref.	SIZE
30520	Aerosol 500 ml



DRY LUBE-F

PTFE lubricant for dry lubrication and use in food processing areas.

Grease- and oil-free lubricant for the lubrication of plastic, rubber or metal surfaces. Clean, dry and not sticky. Temperature resistance up to 250°C. As a lubricant, CRC Dry Lube-F is most effective where low speeds and light loads are involved. Recommended for use as a lubricant in food processing areas where incidental food contact may occur. NSF H1 registered.



Ref.	SIZE
32602	Aerosol 500 ml



DRY MOLY LUBE

High pressure resistant, dry MoS₂ film for metal-to-metal lubrication where a wet film cannot be tolerated. High temperature resistance. Reduces stick and slip problems. Displaces and seals out water and moisture. General corrosion protection. Prevents seizing and fretting. Produces a very low coefficient of friction.



Ref.	SIZE
32660	Aerosol 500 ml



MULTI GREASE

Lithium EP grease for general purpose.

An EP (extreme pressure)-lithium soap-based grease for rolling-element and sliding-contact bearings in all usual speed ranges. The chemically acting EP additives make the grease suitable for applications in which impact loads and vibrations occur.

Ref.	SIZE
30566	Tube 100 ml
30567	Cartridge 400 g
30568	Bulk 1 kg
30569	Bulk 5 kg



ECO MULTI GREASE

An EP biodegradable multipurpose grease with a synthetic ester oil and environment friendly additives.

Excellent mechanical stability and water resistance offering good anti corrosion properties. Extreme pressure and antiwear properties without toxic additives. Wide operating temperature range : - 40°C + 150°C, also adapted for high speed applications. The product is suited for bearings, joints and general lubrication (wheel bearings, roller bearings, joints and lubrication of any mechanical parts, farming equipment and off-road vehicles).

Ref.	SIZE
31912	Aerosol 500 ml



FOOD GREASE

Multipurpose grease for food processing equipment.

Long-term lubrication on food processing equipment where incidental food contact may occur. CRC Food Grease is NSF H1 registered for use in the food industry and can be applied on all metal constructions used in the food industry: hinges, valves, chains, gears, joints, ...

Ref.	SIZE
32317	Aerosol 500 ml
20158	Cartridge 400 ml (380g)
10291	Bulk 1 kg
30438	Bulk 20 L



EP FOOD GREASE

Synthetic bearing grease for food processing equipment.

-30°C to +160°C. Provides long-term lubrication with extreme pressure resistance. NLGI classification 2. Protects against corrosion in wet or saturated environments. Excellent extreme pressure performance. Extends lubrication intervals and working life of components. NSF H1 listed for use as a lubricant in food processing areas where incidental food contact may occur.

Ref.	SIZE
32457	Cartridge 400 g



LUBRICANTS - GREASES

HITEMP FOOD GREASE

High temperature synthetic bearing grease for food processing equipment.

-40°C to +180°C. Provides long-term high temperature. NLGI classification 2. Protects against corrosion in wet environments. Contains PTFE to improve anti-wear performance. Extends lubrication intervals and working life of components. Advised for use as a lubricant in food processing areas where incidental food contact may occur. NSF H1 registered.



Ref.	SIZE
32889	Cartridge 400 ml (380g)



HIGH TEMP GREASE

Lithium EP grease for low speed, high load applications with exposure to high temperatures.

-30°C to +200°C. Recommended on bearings of electric motors.



Ref.	SIZE
30570	Tube 100 ml
30572	Cartridge 400 g
30573	Bulk 1 kg



SUPER LONGTERM GREASE

Lithium EP grease with MoS₂ for low speed, high load applications.

This grease retains its lubricating properties under high surface pressure and impact loads.



Ref.	SIZE
30565	Tube 100 ml
30576	Cartridge 400 g
30578	Bulk 1 kg



SUPER ADHESIVE GREASE

Lithium EP grease for low speed, high load applications with occasional exposure to splash water.

When vibrations, oscillating movements and impact loads occur under outdoor conditions. The good sticking property allows vertical or overhead applications. Temperature range : -30°C to +140°C.

Ref.	SIZE
30585	Tube 100 ml
30587	Cartridge 400 g
30589	Bulk 1 kg



HIGH SPEED GREASE

Synthetic lithium complex grease for very high speed applications, even at low temperatures.

Designed for applications with a high speed factor. Excellent water resistance. Non corrosive. Very good oxidation stability. Extreme high dn-value. Low start torque. Fast accelerations possible. Enables fast response times. Allows start ups at extreme low temperatures.

Applications:

Spindle, linear bearings. Slides, fans, pumps, adjustment mechanisms, assembly of packings.

Ref.	SIZE
32142	Aerosol 500 ml



SILICONE GREASE

Seals valve seats from an aggressive environment.

Allows smooth assembly of elastomeric packing's and seals. CRC Silicone Grease forms a colourless, non-hardening film which eliminates squeaking, binding and sticking. Protects metal, alloys, plastics and rubbers.

Ref.	SIZE
32717	Syringe 10 g
32086	Tube 100 ml
30724	Aerosol 400 ml



LUBRICANTS - GREASES

WHITE LITHIUM GREASE

Lithium complex grease with PTFE for low speed and high load applications.

A high purity NLGI 2 white, lithium based grease with an advanced additive package including PTFE for superior lubrication. CRC White Lithium Grease has a smooth consistency for optimum surface coverage.

Ref.	SIZE
30515	Aerosol 500 ml



EXTREME LUBE

High pressure lubricant.

Synthetic NLGI 2 grease, highly charged with extreme pressure additives. Highly stable with long service life. Excellent water resistance. Functional over a wide temperature range: -40 °C to 180 °C. Provides long-lasting lubrication. Safe on most rubbers, plastics and coatings. Contains corrosion inhibitor. Very good oxidation stability. Acts like an oil, sets like a grease.

NSF H1 registered.

Ref.	SIZE
32603	Aerosol 500 ml
30088	Cartridge 400 g



SYNTHETIC GREASE

Multifunctional, synthetic, high performance general purpose grease.

Applicable like an oil and sets as a grease. Excellent water resistance, contains a corrosion inhibitor. Functional over a broad temperature range. Provides long-term lubrication with very good stability to oxidation. Safe on most rubbers, plastics and coatings.

Ref.	SIZE
32637	Aerosol 500 ml



COPPER PASTE

Paste with copper particles for heavy loads at start-up situations.

Also acts as anti-seize. Contains micronized copper powder; anti-oxidant and anti-wear additives. Prevents metal-to-metal contact, seizing, galling and fretting corrosion, especially on sliding bearings.

Ref.	SIZE
10690	Tube 100 ml
32684	Aerosol 250 ml
32340	Aerosol 500 ml
10699	Bulk 500 g



CERAMIC PASTE

Ceramic paste for heavy loads and high temperatures during start-up conditions.

Also acts as anti-seize. A ceramic separating and mounting paste for applications from -40°C to +1.400°C. Preventing metal-to-metal contact as cause for seizing, galling and fretting corrosion, during heavy start-up conditions or high temperature application.

Ref.	SIZE
30344	Tube 100 g
32690	Aerosol 250 ml
32351	Aerosol 500 ml
32322	Bulk 500 g



GRAPHITE ASSEMBLY PASTE

Assembly paste with solid graphite particles and MoS₂ for easy assembly and smooth start-up situations. Has a good affinity to metals and resists high pressure and elevated temperatures (+650°C). Excellent water resistance. Does not run or drip off, prevents seizing and fretting. High EP (Extreme Pressure)- and anti-wear properties. Produces a very low coefficient of friction. Reduces stick and slip problems and provides long lasting lubrication.

Ref.	SIZE
32639	Aerosol 500 ml



ASSEMBLY PASTE

Anti-seize compound for lubrication of bushes, sliding surfaces and small open gears.

Prevents damage at start-up and protects during running-in. Protects against seizing of threaded components. Effective from -30°C to +150°C as a lubricant and to +1100°C as an anti-seize. Developed for use as a lubricant in food processing areas where incidental food contact may occur. NSF H1 registered.

Ref.	SIZE
32604	Aerosol 500 ml
20120	Tin 500 g



ALU PASTE




Assists with assembly of rough threaded parts and sliding steel surfaces.

Prevents seizing. Takes up high loads. Supports extreme slow movements. Smoothens rugged surfaces. High temperature resistance. Convenient 360° (including inverted position) spray valve for aerosols.

Applications: Rugged thread, guide rails, assembly of rugged parts, sliding surfaces.

Ref.	SIZE
32147	Aerosol 500 ml



PRODUCT	Min. temp. (°C)	Max. temp. (°C)	DN (mm/min)	DIN 51 825
CRC Multi Grease	-30	130	400.000	KP 2 K-30
CRC Super Longterm Grease	-30	130	280.000	KPF 2 K-30
CRC Super Adhesive Grease	-30	140	250.000	KP 2 N-30
CRC Low Temp Grease	-50	160	400.000	KP 2 P-50
CRC High Temperature Grease	-30	200	400.000	KP 2 P-30
CRC High Speed Grease	-60	130	1.000.000	KP 2K-60
CRC Food Grease 	-20	140	500.000	K 2 K-20
CRC EP Food Grease 	-30	160	400.000	KP 2 P-50
CRC HiTemp Food Grease 	-40	180	200.000	K 2 U-20
CRC Graphite Assembly Paste	-30	650	-	-
CRC Alu Paste	-25	650	-	-



EJECTOR LUBE

Long lasting high performance lubricant for ejector pins

Ejector lube has exceptional lubricating power, even under extreme conditions: high temperatures, high pressures, high linear speeds. NSF H1 certified.

- Eliminates seizing problems of ejectors or drawers
- Eliminates creeping of greasy products and contamination on the aesthetic side of moulded parts
- Promotes gas tightness on the ejector level
- Does not carbonize, leaving black imprints on the finished part



Ref.	SIZE
33265	Aerosol 500 ml

TRIFLOW

Durable general lubricant

Multipurpose fluid with PTFE for mould and precision mechanism.

- Penetrates into hard-to-reach areas, displaces moisture and cleans
- Contains micro particles of PTFE
- Durable lubrication thanks to its high quality oils, extreme pressure additives and solid (PTFE) lubricants
- Protects against corrosion and humidity
- Seals out dirt, dust, sand and other abrasive particles



Ref.	SIZE
31343	Aerosol 400 ml

NON SILICONE BASED RELEASE AGENTS (NSR)

Non silicone based release agents



NSR MULTI

General Use



NSR DRY

Dry Film



NSR FOOD

M1 Registered



NSR ULTRA THIN

Minimum Product Transfer



NSR THERMO

High Temperature



NSR RUBBER

Water Based



NSR WET

Wet Film



NSR SENSITIVE

Paintable Plastics



NSR MULTI

General use non-silicone release agent

Excellent release for thermoplastics and thermosets, e.g. polyurethane elastomers, flexible polymers and PVC.

- A wet film mould release that imparts a gloss finish to moulded parts
- Will not interfere with post moulding operations (painting, printing, bonding, plating)
- Operational temperature to +200°C
- Does not build up in the Mould



Ref.	SIZE
33234	Aerosol 500 ml

NSR DRY

Medium duty, non-silicone release agent

A medium duty, dry film mould release agent. Does not contain silicone. Provides an easy release for all types of thermoplastics and especially silicone and rubber.

- Will not interfere with post moulding treatments such as painting, printing, bonding or plating
- Operational to +150°C
- Does not build up in the mould
- Limited transfer to the moulded parts



Ref.	SIZE
32841	Aerosol 500 ml

NSR FOOD

Food grade non-silicone based release agent

A non-silicone release agent with NSF registration for use during moulding of food contact plastic packaging.

- NSF registered M1
- Use on moulds for food packaging which is intended for direct food contact
- Will not interfere with post moulding operations such as bonding and labelling
- Translucent film
- Operational temperature to +200°C



Ref.	SIZE
32957	Aerosol 500 ml



NON SILICONE BASED RELEASE AGENTS (NSR)

NSR ULTRA THIN

Non silicone based release agent with minimal product transfer

Balanced formulation to provide an excellent slip during demoulding without contaminating transparent surfaces by product transfer. Ideal for use with transparent plastics such as Polycarbonate, ABS and polyamides.

- Ideal for mould applications where fine details and precision are requested
- Will not stop post moulding operations (anti reflection coatings , gluing anti-fog screens,...)
- Contains Zinc Stearate which results in excellent slip properties



Ref.	SIZE
32962	Aerosol 500 ml

NSR THERMO

Semi-permanent non-silicone release agent

Non silicone release agent formulated to release a wide variety of thermosets in high temperature transformation

- Forms a thin, homogeneous, inert and thermally stable coating from which multiple releases can be expected
- Fast cure time. Moulding can start 30 minutes after application
- Operational temperature to +250°C



Ref.	SIZE
32977	Aerosol 500 ml

NSR RUBBER

Non silicone based release agent for rubbers

A water based release agent for use in a wide variety of rubber moulding operations.

- Used for the release of all natural and synthetic grades of rubber
- Fast curing with lower mould build-up
- Non-flammable and environmental 'safe'
- Does not affect the rubbers



Ref.	SIZE
32980	Bulk 25 kg



NSR WET

Heavy duty, non-transfer silicone release agent

A wet film, which provides an excellent release on a wide range of thermoplastics and thermoset materials.

- Will not interfere with post molding operations such as painting, printing, bonding or plating
- Operational temperature to + 150°C
- Does not build up in the mold
- The wet film offers an excellent "slip" for complicated parts



Ref.	SIZE
32842	Aerosol 500 ml

NSR SENSITIVE

Non-transfer silicone release agent for sensitive paintable plastics

Mould release agent for plastics and rubbers.

- Colorless film
- Will not interfere with post molding operations such as painting, printing, bonding or plating
- Operational temperature to + 150°C
- Offers an outstanding slip during release of stress crack sensitive polymers
- The first-rate slip allows complicated shapes to be released by fast shot



Ref.	SIZE
32960	Aerosol 500 ml
32964	Bulk 5 L



SILICONE BASED RELEASE AGENTS (SR)

SR MULTI

General use silicone based release agent

A general purpose release agent for all thermoplastics and many types of rubber. It is highly versatile as a release agent, ensuring accurate mould detail and improving surface finish without building up in the mould.

- Improves surface finish, minimizes imperfections and enhances even well-polished tool release properties
- Operational to +200°C
- Can also be used as an anti-stick agent in the textile, foam converting, printing and shoe industries
- Fabulous slip properties for fast demoulding
- Provides a smooth surface finish

Ref.	SIZE
32836	Aerosol 500 ml



SR SEMI PER

Semi-permanent silicone based release agent

Air curing silicone resin, used as polymer release agent on bigger surfaces.

- Excellent performance on rotational moulding production facilities
- Developed for rubbers, elastomers and thermosets
- Performs well as release agent for casting resins on flat bed and wet plastering applications

Ref.	SIZE
32958	Aerosol 500 ml



SR THERMO

Heavy duty silicone based release agent

Heavy duty, high silicone concentration, mould release agent.

- Specifically to be used on polyester and epoxy moulds
- Withstands the high temperatures (up to +200°C) during exothermic reactions of the resins
- Smooth surface finish
- Very good thixotropy

Ref.	SIZE
32978	Aerosol 500 ml



SR FOOD

Food grade silicone based release agent

A high purity silicone release agent for moulding of food contact plastic packaging.

- NSF registered M1
- Maximum operational temperature: +200°C
- Provides good brilliance at transparent plastics
- Excellent slip for uncomplicated release of light weight mouldings

Ref.	SIZE
32956	Aerosol 500 ml



LOST WAX RELEASE

Paintable mould release agent

Ideal for lost wax moulding and precision moulding.

- Based on a copolymer
- Silicone residues on the casting can be rinsed away with water
- Will not interfere with post moulding treatments such as painting, printing, bonding or plating



Ref.	SIZE
32954	Aerosol 500 ml

PU RELEASE AGENT

Silicone based release agent for polyurethanes (PU)

A silicone release agent formulated as a fine release film for integral skin and elastomeric polyurethanes.

- High quality, high gloss and excellent surface finish
- Colorless
- Operational temperature to +200°C
- No build up on mould surface



Ref.	SIZE
32959	Aerosol 500 ml

RELEASE EMULSION

Ready to use water-based silicone emulsion release agent

Releases many types of plastic and rubber, especially PVC and rubber profile extrusions.

- Economical in use and environmentally 'safe & friendly'
- Operational temperature up to +150°C



Ref.	SIZE
32979	Bulk 5 kg

Thermoplastics

Process Plastics	Rotational moulding	Extrusion blow moulding	Vacuum forming	Injection moulding
ABS	SR Semi Per	SR Multi	NSR Wet	NSR Ultra Thin / (N)SR Multi
PA				NSR Multi / SR Multi
PC				SR Multi / NSR Dry
PE				NSR Sensitive / (N)SR Multi
PET				NSR Dry / SR Multi
PLA				NSR Ultra Thin / (N)SR Multi
PMMA				NSR Multi / SR Multi
POM				
PP				
PS				NSR Rubber
PVC				

When other criteria then plastic & process are involved and considered important, the first selection has to be finetuned with the help of the technical datasheets.

Thermosets

Process Plastics	Lost wax	Extrusion profile & sheets	Resin transfer moulding	Flat bed moulding	Pultrusion
UP	NSR Thermo	NSR Thermo	SR Thermo	NSR Dry	NSR Thermo
AMC			NSR Thermo		
EP			SR Thermo		
FUR			NSR Thermo		
M					
PF	NSR Thermo	NSR Thermo	NSR Thermo	PU Release Agent	PU Release Agent
PU					
VE					
neoprene	NSR Thermo	Release Emulsion	NSR Thermo		NSR Thermo


When other criteria then plastic & process are involved and considered important, the first selection has to be finetuned with the help of the technical datasheets.

Injection gas moulding	Injection blow moulding	Injection stretch blowing	Thermoforming	Insert moulding
NSR Ultra Thin	NSR Ultra Thin	NSR Ultra Thin		
	NSR Ultra Thin	NSR Ultra Thin		
NSR Sensitive	NSR Sensitive	NSR Sensitive	NSR Food	NSR Sensitive
NSR Food	SR Food	NSR Sensitive	SR Food	NSR Sensitive
NSR Ultra Thin	NSR Food			
NSR Food			NSR Food	NSR Sensitive
NSR Rubber	SR Food	NSR Rubber	SR Food	NSR Rubber

Glossary Plastics

	Code	Chemical name	Mould Temp. [°C]
THERMOPLASTICS	ABS	Acrylonitrile Butadiene Styrene	85
	PS	Polystyrene	82
	PC	Polycarbonate	93
	PP	Polypropylene	60
	PVC	Polyvinyl Chloride	rig 60 / flex 82
	PE	Polyethylene (LD=Low Density, HD=High Density)	LD 27 / HD 43
	PA	Polyamide (Nylon)	204
	PET	Polyethylene Terephthalate	99
	PMMA	Acrylic	65
	POM	Polyoxymethylene	
	PLA	Polylactid Acid	
THERMOSETS	UP	Unsaturated Polyester	Temperature triggered chemical reaction
	AMC	Alkyd	
	EP	Epoxies	
	FUR	Furan	
	M	Melamine (MF, UF)	
	PF	Phenolics	
	PU	Polyurethane	
	VE	Vinyl Esters	

SELECTION GUIDE POLYMER INDUSTRY



*Depending on environmental circumstances.

TEMPORARY PROTECTION

INDOOR STORAGE

OUTDOOR STORAGE






3-36

SP 350





SP 350

SP 400

LONG-TERM PROTECTION

COATINGS



ZINC PRIMER



GALVA BRITE



GALVA SHINE



INOX 200



ALU HITEMP

CATHODIC PROTECTION

ELECTRONICS

COATINGS



ZINC



URETHANE ISOLATION



VARNISH E200




GALVACOLOR


RUST TREATMENT

RUST PRIMER


REMOVER



RUST SEAL



RUST REMOVER



FERROKLEEN

POLYMER PROCESSING



MOULD PROTECT




BLUE MOULD PROTECT





CLEAR MOULD PROTECT

ANTI-CORROSION - TEMPORARY

3-36

Short-term corrosion inhibitor. Indoor protection up to 6 months.

Multipurpose corrosion inhibitor with water repellent and lubricating properties. Forms a thin, almost invisible and long-lasting protective film against water and oxygen. Exceptional penetrating properties, allowing the product to work even into the smallest pores and cracks. CRC 3-36 protects metal parts from corrosion when stored indoors, during a shorter period.

Ref.	SIZE
32673	Aerosol 250 ml
10110	Aerosol 500 ml
10114	Bulk 5 L
30362	Bulk 20 L
30364	Bulk 200 L



SP 350

Long-term corrosion inhibitor.

Indoor protection up to 2 years. Outdoor protection when covered, up to 1 year. Highly viscous protective oil. Forms a thin penetrating protective film, which does not dry. Protects against moisture and corrosive vapors. Displaces moisture and does not drip off. Covers both smooth surfaces and sharp edges. Provides a relatively long corrosion protection. Do not store the protected parts in outdoor and uncovered conditions.

Ref.	SIZE
32672	Aerosol 250 ml
32659	Aerosol 500 ml
20294	Bulk 5 L
30407	Bulk 20 L



SP 400

Long-term outdoor, corrosion inhibitor.

Outdoor protection up to 2 years. Waxy corrosion protector. Provides an effective corrosion protection in outdoor conditions, for a long period. The waxy protective film does not become brittle and protects against heavy corrosive circumstances as moisture and salt water.

Ref.	SIZE
32661	Aerosol 250 ml
32350	Aerosol 500 ml
20324	Bulk 5 L
20327	Bulk 20 L



ZINC PRIMER

Corrosion protective primer, easy to paint over.

A Zinc-Phosphate primer for metal surfaces. Dries quickly. Improves adhesion of the finishing coating. A corrosion protective additive slows down corrosion. Can be painted over with all kinds of single component paints, already after one hour. Ideal topcoat: Galva Brite or Galva Shine.



Ref.	SIZE
30419	Aerosol 500 ml

GALVA BRITE

Protective, final coating with a shiny aluminum aspect.

A single component Zinc-Aluminum coating. Protects against corrosion and forms a glossy aluminum look on the coated surface. Good adhesion to metal surfaces. Results in a unique combination of flexibility and hardness. For perfect results please use CRC Zinc Primer first.



Ref.	SIZE
30423	Aerosol 500 ml

GALVA SHINE

Touch-up paint for hot galvanised pieces.

Protective coating with an exceptional gloss. Gives the work piece the aspect of a freshly hot galvanised piece. The film is very resistant and keeps its brilliance in time. Ideal paint for touch-ups of freshly galvanised pieces. The paint can also be used to give pieces a new zinc look. For perfect results please use CRC Zinc Primer first.



Ref.	SIZE
32319	Aerosol 500 ml

INOX 200

Anti-corrosion coating for stainless steel surfaces.

Coating with good anti-corrosion properties and a nice look, identical to stainless steel (inox). The coating is fast drying, resistant to high temperatures and has excellent adhesion properties. Ideal touch-up paint : to be used after welding or when mounting a stainless steel construction. Will cover and protect discolored welding seams.



Ref.	SIZE
32337	Aerosol 500 ml

ALU HITEMP

Protective coating with aluminum look.

Resists high temperatures. Paint that resists high peak temperatures up to 600°C. Provides a hard and durable surface, which does not burn, crack or scale down, even at high temperatures. Withstands large fluctuations in temperature. Excellent weather resistance.



Ref.	SIZE
32421	Aerosol 500 ml

ZINC

Cathodic protection, even for damaged galvanised parts.

Zinc based coating with excellent adhesion to metal surfaces. The high zinc content is sacrificed during the corrosion process and so provides a galvanic protection of the treated metal. The dry coating contains a maximum amount of zinc (purity 98%), ensuring a self-healing effect when the coating gets scratched. The dry coating is matt and has an excellent surface structure to be painted.



Ref.	SIZE
30563	Aerosol 500 ml
30564	Bulk 750 ml

URETHANE ISOLATION

Protective, urethane based varnish for electronic components.

Clear transparent or red colored one-component, urethane type coating. Urethane coating seals out water and moisture and acts as a barrier for contaminants. The coating dries fast and adheres well to most surfaces. After curing, the protective film has a high flexibility, is durable and resists abrasion and contamination.



Ref.	SIZE
32669	Aerosol 250 ml Clear
10630	Bulk 4 L Clear
32670	Aerosol 250 ml Red
10641	Bulk 4 L Red

VARNISH E200

Protective varnish that seals for environmental influences.

Use it on printed circuits boards and electrical windings. Recommended to cover solid contact assemblies.

- Outstanding electric insulation.
- Fast drying at ambient conditions. Speed up the drying in an oven.
- Excellent thermal conductivity.
- Resists mechanical shocks.
- Allows soldering without removal.
- Contains a UV tracer for quick control by an UV light.



Ref.	SIZE
32915	Aerosol 400 ml

GALVACOLOR

Aerosol paint that protects the metal from corroding.

Zinc-phosphate protective coating. Ideal for identification of utility conduits. Primer and topcoat in one. Short drying time. Official RAL identification colors. Conform to the protect category C3 (ISO 12944-2).

Ref.	SIZE	COLOR	RAL
20563	Aerosol 500 ml	Yellow	1004
32170	Aerosol 500 ml	Orange	2011
20566	Aerosol 500 ml	Red	3000
32079	Aerosol 500 ml	Blue	5005
20572	Aerosol 500 ml	Blue	5012
33351	Aerosol 500 ml	Green	6005
32702	Aerosol 500 ml	Anthracite	7016
32080	Aerosol 500 ml	Grey	7035
20581	Aerosol 500 ml	Black	9005
20584	Aerosol 500 ml	Silver	9006
20587	Aerosol 500 ml	White	9010



RUST SEAL

Rust Seal is the ideal pretreatment before painting rusted metal.

CRC Rust Seal stops the corrosion process by forming a black protective barrier that seals off the rust from moisture. This way, it transforms corroded metal into an easily paintable surface without any time-consuming sandblasting. Can be directly applied on rusted metal. Paintable with any top coat (e.g. CRC Galva Color) after 2 hours of drying. Eco-friendly and safe-to-use.

Ref.	SIZE
33349	Bulk 750 ml



RUST REMOVER

Removes corrosion and/or rust from metals.

CRC Rust Remover is a concentrated scale and rust remover. Based on acid, it removes rust and cleans metal surfaces from scale, tarnish, oxidation and stains.

Ref.	SIZE
30610	Bottle 250 ml
10752	Bulk 5 L
30611	Bulk 20 L




FERROKLEEN

Cleans painted and bare metal surfaces contaminated with rust, lime, algae, oils and tar.

Takes rust and rust stains on painted or plastic surfaces away. Effective against a wide range of scales. Non flammable. Slightly foaming. Composed of > 90% anorganic components and biodegradable organic components. Not classified as dangerous for the aquatic environment.

Ref.	SIZE
30112	Bulk 1 kg
30089	Bulk 5 kg
30199	Bulk 20 kg





MOULD PROTECT

Long term waxy corrosion protection

Non silicone corrosion protection for moulding tools and dies. Repels and displaces moisture, leaving a durable, high quality protective wax-like film. Long-lasting efficient protection.

- Ideal for mould tools, dies and parts stored for indefinite period
- High covering, translucent film
- Displaces humidity on metal surfaces
- Resists to the affects of condensation due to big temperature changes in the storage place
- Silicone free



Ref.	SIZE
32839	Aerosol 500 ml

BLUE MOULD PROTECT

Short term blue colored corrosion inhibitor for mould tools

Non silicone corrosion protection for moulding tools. NSF registered for use in food packaging industry.

- NSF registered H2
- Ideal for short-term inactivity of mould tools, dies and jigs
- Highly visible blue dye provides an easy visual method for ensuring complete coverage
- Displaces humidity on metal surfaces
- Silicone-free
- No need for cleaning as the product moulds off during the first cycles



Ref.	SIZE
32837	Aerosol 500 ml

CLEAR MOULD PROTECT

Short term clear corrosion inhibitor for mould tools

Non silicone corrosion protection for moulding tools. NSF registered for use in food packaging industry.


- NSF registered H2
- Ideal for short-term inactivity of mould tools, dies and jigs
- Will weaken carbonized polymer residues, during the inactivity time
- Displaces humidity on metal surfaces
- Silicone-free
- No need for cleaning as the product moulds off during the first cycles




Ref.	SIZE
32838	Aerosol 500 ml

MARKING AND SIGNALISATION

TEMPORARY



PERMANENT



OTHER

RAL PAINTS



CORROSION PROTECTION



ACCESSORIES

STRIPING PAINT MACHINE













MARKER PAINT

Special multi position paint for manual marking and signaling.

A fast drying paint, formulated for temporary signaling and marking jobs for all types of outdoor works. CRC Marker Paint can be used in all positions, no need to purge after use. Due to the special resin the product has a very good adherence to any type of substrate (asphalt, rock, concrete, wood, ...), even under severe weather conditions (humidity, cold,...). The special formula ensures a good (fluorescent) aspect over light and dark areas.



Ref.	SIZE	COLOR	
10158	Aerosol 500 ml		Fluo Yellow
10165	Aerosol 500 ml		Fluo Orange
10155	Aerosol 500 ml		Fluo Red
10167	Aerosol 500 ml		Fluo Violet
10160	Aerosol 500 ml		Fluo Blue
10157	Aerosol 500 ml		Fluo Green
10163	Aerosol 500 ml		Fluo Fuchsia
10164	Aerosol 500 ml		Black
10154	Aerosol 500 ml		Yellow
10162	Aerosol 500 ml		White











AQUA PAINT MARKER

Water based paint for manual marking and signaling.

A special water based paint formulated for signaling and marking jobs for all types of outdoor and indoor works. Due to the special resin the product has a very good adherence to any type of substrate (asphalt, rock, ground, concrete), even under severe weather conditions (humidity, cold,...). The special formula ensures a good (fluorescent) aspect over light and dark areas. Ecological paint.



Ref.	SIZE	COLOR	
30010	Aerosol 500 ml		Fluo Yellow
30011	Aerosol 500 ml		Fluo Orange
30009	Aerosol 500 ml		Fluo Red
30013	Aerosol 500 ml		Fluo Blue
30012	Aerosol 500 ml		Fluo Green
32462	Aerosol 500 ml		Fluo Fuchsia
32461	Aerosol 500 ml		Black
30014	Aerosol 500 ml		White











PAINTS - MARKING & IDENTIFICATION

STRIPING PAINT

Special paint for line marking.

CRC Striping Paint is especially developed to trace lines either indoors or outdoors. The chosen resins offer a high resistance to wear and extreme bad weather conditions. Equal and precise line tracing and long lasting coverage over flat surfaces.










Ref.	SIZE	COLOR	
11671	Aerosol 500 ml		Yellow
11675	Aerosol 500 ml		Red
11676	Aerosol 500 ml		Blue
11677	Aerosol 500 ml		Green
11673	Aerosol 500 ml		Black
11668	Aerosol 500 ml		White
30474	Aerosol 750 ml		Yellow Long Life
30473	Aerosol 750 ml		White Long Life



MARKER PEN

Marker Pens for multi surface use.

Excellent coverage thanks to the use of correction fluid technology. Can be used on wood, metal, rubber, glass, textile, paper, enamel, plastic, cardboard, tiles, ... Easy and clean application.







Ref.	SIZE	COLOR	
20400	Pen		Yellow
20384	Pen		Orange
20388	Pen		Red
30211	Pen		Violet
20369	Pen		Blue
20380	Pen		Green
30210	Pen		Brown
20365	Pen		Black
20395	Pen		White



MARKER BALL

Indelible paint. Industrial use only.

Tip with steel ball. For all types of surfaces. Functions on wet, oily, greasy and rusted surfaces. UV resistant. Excellent water resistance. Functional over a wide temperature range.












Ref.	SIZE	COLOR	
30160	Tube		Yellow
30161	Tube		Red
30163	Tube		Blue
30162	Tube		Green
30159	Tube		Black
30158	Tube		White



GALVACOLOR

Aerosol paint that protects the metal from corroding.

Zinc-phosphate protective coating. Ideal for identification of utility conduits. Primer and topcoat in one. Short drying time. Official RAL identification colors. Conform to the protect category C3 (ISO 12944-2).

Ref.	SIZE	COLOR	RAL
20563	Aerosol 500 ml	 Yellow	1004
32170	Aerosol 500 ml	 Orange	2011
20566	Aerosol 500 ml	 Red	3000
32079	Aerosol 500 ml	 Blue	5005
20572	Aerosol 500 ml	 Blue	5012
33351	Aerosol 500 ml	 Green	6005
32702	Aerosol 500 ml	 Anthracite	7016
32080	Aerosol 500 ml	 Grey	7035
20581	Aerosol 500 ml	 Black	9005
20584	Aerosol 500 ml	 Silver	9006
20587	Aerosol 500 ml	 White	9010






AQUA RAL

Environmentally friendly, acrylic based paint with an optimized use of water as solvent.

Fast drying paint with good flexibility. High UV resistance once the paint is polymerized. Good adhesion on stone, concrete, wood, glass, paintable plastics and metal. Good covering ability. Does not contain any heavy metals. Long lasting, intensive shine. Available in several RAL colors.



 Signal Yellow RAL 1003 Ref.: 32182	 Cadmium Yellow RAL 1021 Ref.: 32184	 Yellow Orange RAL 2000 Ref.: 32185	 Carmin Red RAL 2004 Ref.: 32187	 Flame Red RAL 3000 Ref.: 32186
 Traffic Red RAL 3020 Ref.: 31457	 UltraMarine Blue RAL 5002 Ref.: 32188	 Gentian Blue RAL 5010 Ref.: 32189	 Leaf Green RAL 6002 Ref.: 32190	 Moss Green RAL 6005 Ref.: 32191
 Yellow Green RAL 6018 Ref.: 31459	 Silver Grey RAL 7001 Ref.: 32193	 Grey Anthracite RAL 7016 Ref.: 32194	 Nut Brown RAL 8011 Ref.: 32196	 Black Glossy RAL 9005 Ref.: 32197
 Black Mat RAL 9005 Ref.: 32205	 White Aluminium RAL 9006 Ref.: 32418	 White Glossy RAL 9010 Ref.: 32204	 White Mat RAL 9010 Ref.: 32198	 White RAL 9016 Ref.: 32199
 Varnish Clear Brilliant Ref.: 32206				

Three Step Paint System

The CRC Acrylic Paint range offers maximum protection and vibrant colours for your to-be painted surfaces in three simple steps. Thanks to the practical ready-to-use 400 ml aerosols, the paint can be easily applied on nearly all surfaces.

PRIME



CRC Acrylic Primer prepares the surface before application of Acrylic Paint:

- Ensures best adhesion of Acrylic Paint for economical application
- Protects from corrosion
- Optimizes gloss of the top coat

1
PRIMER



PAINT



CRC Acrylic Paint colours the surface in the desired colour while protecting it against external influences:

- Very good coverage
- Weather-resistant, UV-resistant
- Scratch- and shock-resistant

2
PAINT

PROTECT




CRC Acrylic Varnish gives an extra layer of protection so that the top coat stays immaculate for a long time :

- Maximum gloss
- Maximum corrosion protection
- Maximum protection against UV, scratches and shocks

3
VARNISH

MAXIMUM PROTECTION IN



STEPS



STEP 1: PRIME

ACRYLIC METAL PRIMER

Acrylic Metal Primer is specifically designed as a primer for metal but can also be used on a wide variety of materials, such as wood, ceramics, eternit, cardboard,...

- Fast-drying: dust-dry after +/- 15 minutes
- High filling properties
- Protects against corrosion
- For indoor and outdoor use
- Adjustable direction and output thanks to flexible nozzle

References:



Metal Primer

Ref.: 31091



ACRYLIC PLASTIC PRIMER

Acrylic Plastic Primer is specifically designed as a primer for hard plastic, such as polyurethane, polystyrene, polyamide, hard polyvinyl chloride (PVC),...

- Very fast-drying: Topcoat can be applied after +/- 15 minutes
- Results in a smooth surface
- For indoor and outdoor use
- Adjustable direction and output thanks to flexible nozzle

References:



Plastic Primer

Ref.: 33274



CHOOSE YOUR SPRAY DIRECTION AND OUTPUT!

Twist the button at the front of the nozzle horizontally or vertically for the desired spray pattern.



Slide the button at the back of the nozzle left or right for the desired level of output.

STEP 2: PAINT

ACRYLIC PAINT
























































CRC Acrylic Paint is a high quality paint that protects your surface while giving it an intensive, long-lasting colour. Thanks to its unique combination of flexibility and hardness, CRC Acrylic Paint is very resistant to external influences, making it an excellent protection paint for a wide variety of hard surfaces throughout industries. It can be used on metal, paintable hard plastics, wood, concrete, paper, glass,...

- Fast-drying: dust-dry after +/- 15 minutes*
- Very good coverage
- Adjustable spray direction thanks to flexible nozzle
- Weather- and UV-resistant
- Shock- and scratch-proof
- For indoor and outdoor use



CHOOSE YOUR SPRAY DIRECTION!

CRC Acrylic Primer is equipped with a special nozzle: with one simple movement, you can arrange the output and the spray direction (horizontal or vertical) for easy application.

 Signal Yellow RAL 1003 Ref.: 31084	 Golden Yellow RAL 1004 Ref.: 31069	 Light Ivory RAL 1015 Ref.: 31073	 Zinc Yellow RAL 1018 Ref.: 31080	 Colza Yellow RAL 1021 Ref.: 11679	 Traffic Yellow RAL 1023 Ref.: 32151
 Melon Yellow RAL 1028 Ref.: 33269	 Yellow Orange RAL 2000 Ref.: 11685	 Vermillion RAL 2002 Ref.: 31070	 Pure Orange RAL 2004 Ref.: 32152	 Traffic Orange RAL 2009 Ref.: 32161	 Flame Red RAL 3000 Ref.: 11678
 Signal Red RAL 3001 Ref.: 33270	 Carmine Red RAL 3002 Ref.: 30475	 Ruby Red RAL 3003 Ref.: 31081	 Traffic Red RAL 3020 Ref.: 32153	 Ultramarine Blue RAL 5002 Ref.: 11681	 Signal Blue RAL 5005 Ref.: 33271
 Gentian Blue RAL 5010 Ref.: 31068	 Steel Blue RAL 5011 Ref.: 31085	 Light Blue RAL 5012 Ref.: 32140	 Sky Blue RAL 5015 Ref.: 30476	 Traffic Blue RAL 5017 Ref.: 32155	 Capri Blue RAL 5019 Ref.: 32156
 Emerald Green RAL 6001 Ref.: 11684	 Leaf Green RAL 6002 Ref.: 31067	 Moss Green RAL 6005 Ref.: 31077	 Fir Green RAL 6009 Ref.: 31071	 Reseda Green RAL 6011 Ref.: 30477	 Yellow Green RAL 6018 Ref.: 31082
 Traffic Green RAL 6024 Ref.: 30478	 Silver Grey RAL 7001 Ref.: 11680	 Grey Signal RAL 7004 Ref.: 32162	 Basalt Grey RAL 7012 Ref.: 33272	 Anthracite Grey RAL 7016 Ref.: 31078	 Black Grey RAL 7021 Ref.: 30479
 Blue Grey RAL 7031 Ref.: 32163	 Pebble Grey RAL 7032 Ref.: 12017	 Grey RAL 7035 Ref.: 31079	 Grey Widow RAL 7040 Ref.: 31088	 Ochre Brown RAL 8001 Ref.: 33273	 Nut Brown RAL 8011 Ref.: 31072
 Mahogany brown RAL 8016 Ref.: 31058	 Cream RAL 9001 Ref.: 32159	 Grey White RAL 9002 Ref.: 31076	 Signal White RAL 9003 Ref.: 32165	 Jet Black Glossy RAL 9005 Ref.: 31063	 Jet Black Mat Silk RAL 9005 Ref.: 31062
 Jet Black Matt RAL 9005 Ref.: 31075	 White Aluminium RAL 9006 Ref.: 31065	 Pure White Glossy RAL 9010 Ref.: 31064	 Pure White Mat RAL 9010 Ref.: 31066	 Pure White Silky Mat RAL 9010 Ref.: 32149	 Graphite Black RAL 9011 Ref.: 11686
 Traffic White RAL 9016 Ref.: 11683					


STEP 3: PROTECT

ACRYLIC VARNISH


CRC Acrylic Varnish offers an extra protective layer for surfaces that are painted with CRC Acrylic Paint. It makes the top coat even more resistant against external influences, like scratches, bumps, (UV) light, corrosion,.... Not only does it offer extra protection, it also gives your surface a glossy or matt finish for that perfect finishing touch.

- Fast-drying: dust-dry after +/- 10 minutes
- Protective layer for Acrylic Paint
- Glossy or matt finish
- Excellent adhesion
- Shock-and scratch-proof
- Weather- and UV-resistant
- For indoor and outdoor use

References:



Varnish Clear Brilliant Glossy
Ref.: 11682



Varnish Silky Mat
Ref.: 31087



EFFECT SPRAYS

Next to the three-step paint system, CRC also offers a range of effect sprays to restore the metallic or chrome look of all kinds of surfaces. Thanks to its intensive colour and shine, your surface will look brand new.

ACRYLIC METALLIC EFFECT

Metallic effect spray for a glossy and sparkling metallic look. Can be used on a wide variety of surfaces, such as metal, coatable hard plastics, wood, stone, glass, cardboard, ceramics,...

- Long-lasting shine and intensive colour
- Very good coverage
- Fast-drying: dust-dry after +/- 10 minutes*
- Shock- and scratch-proof
- Suitable for use on a wide variety of hard surfaces through industries
- Weather resistant when coated with CRC Acrylic Varnish.
- For indoor and outdoor use

References:



Metallic Silver
Ref.: 11688



Metallic Black
Ref.: 31093



ACRYLIC CHROME EFFECT

Chrome effect spray of high-grade acrylic quality that offers a long-lasting decorative chrome finish. Can be used on all smooth surfaces, such as metal, coatable plastics, wood, glass,... Apply CRC Acrylic Primer on absorbing surfaces for optimal result.

- Long-lasting look similar to polished chrome
- Very good coverage
- Fast-drying: dust-dry after +/- 10 minutes*
- Resistant to water and common cleaners
- Suitable for use on a wide variety of smooth surfaces through industries For indoor and outdoor use

References:



Chrome Silver
Ref.: 30481



HEAT-RESISTANT PAINTS

ACRYLIC HITEMP PAINT

CRC Acrylic Hitemp Paint protects metal from high temperatures up to 800° C, which makes it ideal for painting engines, pipelines, heat shields, ovens, pipes,... It can be used on metal, cast iron and aluminium. For full temperature-resistance, the coating should be gradually heated up to 160°C to 200°C and stay at that temperature for +/- 30 minutes.

- Fast-drying: dust-dry after +/- 10 minutes*
- Resistant to very high heat (up to 800°C)
- Very good coverage and filling properties
- Scratch-proof
- Weather-resistant
- For indoor and outdoor use

References:



High Temp Silver
Ref.: 31096



High Temp Black
Ref.: 30483



*At 20°C and 50% relative air humidity

ACCESORIES

ROUND NOZZLE SET

To make every paint job possible, CRC offers a set of 6 round nozzles in different sizes. Can only be used on the Acrylic RAL Paints.

Consists of:

2 thin round nozzles (white)

Thin spray jet for or paint jobs that require high precision. Optimal spray distance: 1 to 3 cm



2 medium round nozzles (black)

Medium spray jet or paint jobs that require medium precision. Optimal spray distance: 5 to 10 cm



2 large round nozzles (gold)

Large spray jet for paint jobs on big surfaces. Optimal spray distance: 15 to 25 cm



Ref.	SIZE
33291	Nozzle Set



SPRAY PAINT GUN

The spray paint pistol can easily be snapped on paint aerosol cans, transforming them into a professional paint gun for an easy and pain-free paint job. It allows accurate and controlled spraying in a very efficient way. The spray paint pistol fits on the whole Acrylic Paint range.

Ref.	SIZE
32556	Spray Paint Gun



SPECIALTY

2-26

Repels any humidity left after water damage, protects against friction and corrosion.

CRC 2-26 is a multipurpose lubricant, preventing electric and electronic malfunction due to water penetration, humidity, condensation or corrosion. Displaces water; cleans, removes current leaks, lubricates and protects.

Ref.	SIZE
32663	Aerosol 250 ml
30348	Aerosol 500 ml
10089	Bulk 5 L
10093	Bulk 20 L
30350	Bulk 200 L



BELT GRIP

Food Processing Safe adhesive belt lubricant.

Water resistant. Aids transmission efficiency and gives extra pulling power. Stops slipping and squeaking. Designed for use in food processing areas where incidental food contact may occur. Prevents slip on all kinds of belts, except toothed belts. CRC Belt Grip increases the transmission of power between belts and pulley. Gives an improved traction and allows running in at reduced belt tension.

Ref.	SIZE
32601	Aerosol 500 ml



BELT GRIP IND

Adhesive belt lubricant.

Water resistant. Aids transmission efficiency and gives extra pulling power. Stops slipping and squeaking. Prevents slip on all kinds of belts, except toothed belts. CRC Belt Grip IND increases the transmission of power between belts and pulley. Gives an improved traction and allows running in at reduced belt tension.

Ref.	SIZE
32336	Aerosol 500 ml



SUGAR DISSOLVING FLUID

Dissolves fondants and sugars from a variety of surfaces in the food processing industry.

Quickly dissolves and removes sugars, fondants and derivatives. Leaves a light lubricating film that inhibits re-adhesion. Quickly penetrates and lifts sugar layer. Does not contain nut oils or nut oil derivatives. Helps prevent sugar build-up on fasteners. NSF H1 Registered No. 144180.

Ref.	SIZE
30204	Bulk 5 L



PEEL OFF

Protective Varnish.

Red color. Easy to remove, CRC Peel Off will form a protective flexible coating. The homogeneous and non-porous thin film will protect pieces against humidity, corrosion and other weather influences. Ideal for intermediate protection during transport or periods of inactivity. It can also be used to protect paint cabinets. The film can easily and rapidly be removed just by peeling off (without the use of solvents).

Ref.	SIZE
20240	Aerosol 500 ml
20491	Bulk 5 L



ECO LEAK FINDER

Allows detecting leaks in gas conducts and installations.

Water based detector for gasses. Meets the requirements of EN 14291 and DVGW (Deutsche Vereinigung des Gas- und Wasserfaches) registration number NG-5170AS0069. CRC ECO Leak Finder detects gas leaks in pressurized pipe work and pressurized systems. At the location of a gas leak, it forms highly visible bubbles. Biodegradable according to OECD 301B: 31%.

Ref.	SIZE
10732	Aerosol 500 ml
30058	Bulk 5 L



LEAK FINDER PMUC

Water based gas leak detector.

Quick and reliable water based gas leak detector. Can be used for almost all types of gases. Contains anti-corrosion agents and stabilisers. Stable foam formulation. PMUC agreement Nr 70-071.

Ref.	SIZE
20609	Aerosol 500 ml



LOW TEMP LEAK FINDER

Locates gas leaks in low temperature applications.

- Withstands temperatures of minus 20°C.
- The eye-catching foam stays stable over a long time.
- Can be used on almost every type of gas, except oxygen.
- Pressurized with soluble gas thus offering the highest possible active product content.
- The unique valve system allows an upside down use.
- Non staining and non corrosive.
- Safe on plastics, steel, copper, aluminum and most coupling alloys.

Ref.	SIZE
32656	Aerosol 500 ml



MINUS 45

Inert, non-flammable coolant.

Strong non-flammable inert dry coolant, down to -45°C, for electrical and electronic maintenance. CRC Minus 45 can be used for maintenance, fault detecting and repairs in the electric and electronic field.



Ref.	SIZE
33115	Aerosol 250 ml
33164	Aerosol 500 ml



ROM 300

Aqueous based protection for pantographs.

An aqueous based semi-permanent protective film to prevent the formation of ice and the accumulation of snow on pantographs. Directions: Apply to the surface to be treated. Allow to dry completely prior to operation.

Ref.	SIZE
30056	Bulk 5 L



GD 265

Protection of electrical equipment against weather influences.

CRC GD 265 is a viscous silicone with the consistency of a thick vaseline.

- Self leveling translucent coating.
- Operating temperature from -50°C till +200°C.
- Chemical inert to most substrates.
- Allows to apply an even coating with uniform coat weight , keeping the original viscosity.
- Good thixotropy on vertical surfaces.

Ref.	SIZE
32916	Aerosol 250 ml



CHECK OUT OUR NEW ANIMATED PRODUCT VIDEOS!

YouTube



CRC INDUSTRIES EUROPE CAN NOW BE FOUND ON YOUTUBE!

Search for CRC Industries Europe on Youtube and you will be able to view all our new animated product videos! Subscribe to the channel and you will automatically receive updates on new videos!

OR FIND OUR ANIMATED MOVIES ON THE WEBSITE!

- Go to www.crcind.com
- Click on the Industry tab
- Click on videos



WWW.CRCIND.COM

SPATTER RELEASE

**SOLVENT BASED
NON-FLAMMABLE**



ANTI SPATTER

**SOLVENT
BASED**



EASY WELD

**WATER
BASED**



ECO BIO WELD

PASTE



ANTI SPATTER
PASTE

TORCH



TORCH CERAMIC
ANTI SPATTER

CLEANERS

PICKLING PASTE



INOX WELD
KLEEN



ROBOSURE



NON-DESTRUCTIVE TESTING (NDT)

**SOLVENT
CLEANER**



CRICK 110

**PENETRATING
COLORANT**



CRICK 120

DEVELOPER



CRICK 130



ANTI-SPATTER PRODUCTS

Ensure an easy removal of spatter on metal surfaces and protect the area around the welding seam from spatter.

CRC anti-spatter products also prevent the obstruction of the nozzle of automatic and semi-automatic welding equipment, thus ensuring a free gas flow and a free supply of welding material.

ANTI SPATTER

Non-flammable, solvent based anti spatter, for use on site.

Does not affect post welding operations. No silicones or flammable solvents. Anti-Spatter film is easily wiped away.



Ref.	SIZE
32318	Aerosol 500 ml



EASY WELD

Economic anti spatter, for use in the workshop.

Provides a quick, easy way to prevent adherence of spatter to metal surfaces, and eliminates the need for chiselling, grinding or wire brushing after welding. Economical in use due to its thin film performance. Non-silicone, heat resistant barrier.



Ref.	SIZE
30738	Aerosol 500 ml



ECO BIO WELD

Non-flammable water based anti spatter, ideal when galvanising will be performed afterwards.

Readily biodegradable according to OECD 301B: 68% (Bulk, 74%). Odourless, non-flammable and safe in use. Fine spray pattern ensures total control and economical coverage. Allows post welding operations, painting, plating, galvanising etc to be undertaken without interference. Contains a rust inhibiting agent.



Ref.	SIZE
31913	Aerosol 500 ml
10742	Bulk 5 L
30606	Bulk 20 L
30607	Bulk 200 L



WELDING-ANTI-SPATTER & CLEANERS

TORCH CERAMIC ANTI SPATTER

High-performance ceramic anti-spatter spray providing a long lasting protection against spatter build-up on the torch and on your welding equipment.

Prevents the build-up of welding material on the torch. The ceramic coating protects gas nozzles, contact tips and the contact tip holders during MIG/MAG welding, even at higher amperages and temperatures. CRC Torch Ceramic Anti Spatter guarantees the ultimate protection and eliminates the excessive spatter build-up on your consumables. CRC Torch Ceramic Anti Spatter is a Boron Nitride coating with high temperature adhesive properties.



Ref.	SIZE
33289	Aerosol 250 ml



ANTI SPATTER PASTE

Pasty anti spatter for protection of the welding torch.

Prevents the build-up of welding material on the torch.

Ref.	SIZE
10747	Tin 500 ml



INOX WELD KLEEN

Restores the original characteristics of Stainless Steel after welding.

CRC Inox Weld Kleen is a pickling paste that restores the original characteristics of stainless steel after welding or heat treatment. Degreasing, cleaning, pickling and passivating of austenitic and duplex stainless steel 303, 304, 316, ..., nickel and aluminum. Fast-working, very efficient, economical and practical to use.



Ref.	SIZE
30379	Bulk 2 Kg



CRICK NON DESTRUCTIVE TESTING SYSTEM (NDT)

CRC Crick is a high-quality dye penetrant testing system that detects **cracks up to 30µm**. The system is developed to ensure that almost anyone can easily learn to use it; with only three ready-to-use aerosols, you can perform the complete test. Combine this with the extraordinary quality of the Crick products and you can be confident that every crack will be detected.

WHY USE THE CRICK SYSTEM?

- Highly sensitive testing method: **detects cracks up to 30µm!**
- Applicable on most materials and complex geometric shapes
- Easy-to-use & easy-to-learn.
- Quick results thanks to fast-drying formula.
- Low sulphur and low halogen content.



All Crick batches are sample tested according to **EN ISO 3452-2** and **ASME Code Section V**.

EN ISO 3452-2: This ISO-norm specifies the technical requirements and test procedures for penetrant materials for their type testing and batch testing.

ASME Code Section V: Specifies the requirements for the NDT methods, specifically for boilers and pressure vessels.

CRICK SET

This convenient testing kit provides everything you need for dye penetrant testing. Ideal for trying the CRC Crick NDT system out.

This kit includes:

- **Crick 110 Cleaner** – Aerosol 500 ml
- **Crick 120 Penetrant** – Aerosol 500 ml
- **Crick 130 Developer** – Aerosol 500 ml



Ref.	SIZE
30763	Aerosol 500 ml Set of 3



WELDING - NON-DESTRUCTIVE TESTING

The CRC Crick system detects in a quick and reliable way, small cracks or failures in welding seams, without expensive equipment or destructive testing. (NDT - Non-destructive testing)

CRICK 110

A solvent-based cleaner/degreaser specifically developed for the thorough removal of all contaminants before inspection with Crick 120 penetrant.

- Effective: cleans deep into the cracks
- Efficient: fast-drying formula



Ref.	SIZE
30723	Aerosol 500 ml



CRICK 120

A red coloured penetrant that flows into tiny surface cracks within a time frame of 10 to 20 minutes. Visible with natural white light.

- Highly sensitive dye: flows into tiny cracks
- Water-washable



Ref.	SIZE
30205	Aerosol 500 ml



CRICK 130

Highly absorbant developer that highlights cracks and failures. Cracks up to 30 µm can be detected. Easy to clean with Crick 110.

- Effective: Detects cracks up to 30µm
- Efficient: cracks detected in less than 7 minutes* after applying.



Ref.	SIZE
20790	Aerosol 500 ml



* Depending on the environmental conditions


Step-by-step guide



Step 1 CRICK 110 – CLEAN THE SURFACE


Before testing, the surface must be clean, degreased and dry. All soiling that can mask imperfections must be removed.

- Spray the Crick 110 cleaner generously on the surface
- Wipe the surface clean with an absorbent cloth
- Allow to dry thoroughly




Step 2 CRICK 120 – APPLY PENETRANT

- Shake the can of Crick 120 prior to use.
- Spray the penetrant in a light, even film on the surface, covering all areas that need to be tested.
- Allow to penetrate for 10 to 20 minutes.




Step 3 CRICK 110 – REMOVE EXCESS PENETRANT

- Apply Crick 110 cleaner on a lint-free cloth
- Wipe the surface until all visible, coloured traces are removed. Make sure that you do not wash the penetrant out of the cracks.




Step 4 CRICK 130 – APPLY DEVELOPER

- Shake the can of Crick 130 thoroughly prior to use, for at least 1 minute.
- Spray a light, homogeneous coat of developer from a distance of about 20 cm. Avoid any excess of developer to avoid masking the finest flaws.
- Allow to develop for at least 7 minutes*.



Step 5 VISUAL INSPECTION OF DEFECTS

- Inspect the surface for red spots or line
- After the drying time, defects appear as red spots or lines on the white background. The wider and more intense the colouring is, the wider and deeper the crack is.



Step 6 POST-TREATMENT (IF REQUIRED)

Cleaning: Crick 110 can be used to post-clean the surface by spraying the cleaner on the surface and wipe it off.

Protection: Protect your metals with one of CRC's corrosion protection products (see www.crcind.com for the complete product range).



Check the step-by-step Crick application video.



SOFT LOCK

Dismountable locker for threaded metal connections.

A blue colored medium strength anaerobic adhesive. CRC Soft Lock is used to lock those threaded connections that will have to be dismantled in the future, by use of normal tools and without damaging the parts or fittings. Recommended for use on threaded connections from M5 till M16.

Ref.	SIZE
30111	Bottle 10 ml
30696	Bottle 50 ml



Temporary

EXTRA LOCK

Permanent locker for threaded metal connections and fixation of bearings.

A green colored high strength anaerobic adhesive. CRC Extra Lock is used to lock those threaded connections that need a certain fixation and may not loosen during operation. CRC Extra Lock is also suitable for locking bearings and axes. Recommended for use on threaded connections from M5 till M16, as well as on bearings and bushings.

Ref.	SIZE
30697	Bottle 50 ml



Permanent

EASY SEAL

Liquid seal for threaded metal couplings.

A white colored low strength anaerobic adhesive, used to seal threaded connections in hydraulic or pneumatic installations, as well as threaded connections in the plumbing business. The position of components can be adjusted during an extended period, even under low pressure. Recommended for use till 3" BSP connections.

Ref.	SIZE
30698	Squeeze Bottle 50 ml



Thread

RIGID SEAL

Liquid seal for machined metal flanges.

An orange colored high strength anaerobic adhesive. CRC Rigid Seal is used to seal stiff, machined metal flanges that are used in industrial piping, engine covers, gearbox covers and hydraulic or pneumatic installations. Excess of material can be wiped off with a dry cloth or is dissolved in oil.

Ref.	SIZE
30699	Squeeze Bottle 50 ml



Flange

QUICK FIX

Cyanoacrylate adhesive for general, non-structural bonding on metals and plastics.

Designed for general use. CRC Quick Fix has a relatively slow curing time, enabling correct positioning for precise work during some seconds.

Ref.	SIZE
30710	Tube in Blister 3 g
30709	Bottle 20 g



FAST STICK

Fast tacking, non-chlorinated spray adhesive.

This specialist formulation will provide instant 'grab', allowing stress to be exerted on the bond before full cure strength is achieved. Especially useful for vertical surfaces where instant grab avoids slippage. Tack time approximately 30 seconds.

Ref.	SIZE
30383	Aerosol 500 ml



POWER STICK

High strength adhesive.

Does not contain Methylene Chloride or other chlorinated solvents. CRC Power Stick has a long open bond time, allowing large areas to be covered before the film dries. Use where a high strength adhesive is required e.g. upholstery, warning and information signs. Tack time approximately 2-10 minutes.

Ref.	SIZE
30454	Aerosol 500 ml



HAND SPRAYER

Simple refillable spraybottle.

The spray pressure is generated by a trigger movement. The hand sprayer can be used for all CRC bulk products except the cleaners.

Ref.	SIZE
32168	Handsprayer 500 ml



PUMP SPRAYER

Refillable spraybottle.

The pressure for spraying is generated by a manual pump system. The pressure available in the bottle allows a constant spray pattern for a longer time. The pump sprayer can be used for most CRC bulk products.

Ref.	SIZE
30463	Pumpsprayer 1L





Counter display
Ref. 91101100



Markerpen display
Ref. 30244-AA



Wooden floor display
Ref. 91101098



Rollup Banner IND
Ref. 91101069



Metal Floor Display 0,5m
Ref. 32973-ME

GLOSSARY OF TERMS

AEROSOL

A self-contained sprayable product comprising of a mixture of active ingredients, carriers and propellant contained in a steel or aluminium container which discharges the formulation under pressure. Aerosols are hermetically sealed, ensuring risk of spillage is removed, storage simplified, and combustion risks minimised - all benefiting Health & Safety guidelines. Assists with precise and controlled application.

BARRIER PROTECTION

Barrier protection is one of two primary methods of protecting metals from corrosion. By coating the metal with a suitable product (e.g. Acrylic Paints; Bright, Cold Galvanise; Inox 200, etc), corrosion is unable to take place because electrolytes (such as rain water) are unable to come into contact with the metal and an electron flow cannot be established, thus preventing galvanic corrosion.

BIODEGRADATION / BIODEGRADABLE

The process by which organic substances are broken down into harmless constituents by the natural action of living micro-organisms.

CATHODIC PROTECTION

Cathodic protection is based on the ionic charge of the metal and the reversal or mitigation of the flow of electrons as found in galvanic corrosion. The protective coating applied should have a lower potential (volts) than the metal it is to protect so that the coating is corroded in preference to the base metal - with protection often extending beyond the physical edge of the coating. By offering itself for corrosion instead of the base metal, this type of coating is often termed 'sacrificial' and is, in essence, how galvanised steel is protected.

DIELECTRIC STRENGTH

The maximum electrical field strength that an insulating material can withstand intrinsically without decomposing, usually specified in volts per millimetre of thickness. Also known as the breakdown voltage.

EDTA

EDTA is the chemical compound ethylenediaminetetraacetic acid, also known as diaminoethanetetraacetic acid disodium salt. It is most commonly used as a constituent in water based cleaning chemicals to bind with a water soluble compound. This use has now become less prominent due to concerns over the biodegradability and EDTA has also found some specialist uses as a preservative in some processed foods and cosmetics.

EMULSION

A combination of water-soluble and water-insoluble chemical groups held together by a surfactant. Emulsions are usually milky white.

EPP

See page 5.

EVAPORATION RATE

The rate at which a material will vaporise (evaporate) when compared to the known rate of vaporisation of a standard material. The designated standard material is usually n-butyl acetate, with a vaporisation rate designated as 1.0. The higher the number, the faster the evaporation rate.

FDA

The FDA (Food and Drugs Administration) ensures that all ingredients used in foods are safe, and that food is free of contaminants such as disease-causing organisms, chemicals, or other harmful substances. The FDA reviews the results of laboratory, animal and human clinical testing conducted by companies to determine if the product they wish to place on the market is safe and effective. The FDA does not develop or test products itself, nor issue approvals.

FILM STRENGTH

The measurement of a lubricant's ability to keep an unbroken film during operation (load) conditions.

FLASH POINT

The lowest temperature at which the vapors of a solvent will flash (ignite) under specific test conditions.

GALLING

The process by which metal components 'cold weld' and seize. When two metals are brought together under pressure, the action of forcing the surfaces together can cause the contacting faces to begin to combine at an atomic level, fusing the pieces

together. Where stainless steel or aluminum alloys are used, the friction can scour off the thin, non-reactive protective oxide layer, exposing clean reactive material - allowing atomic fusing to occur. Galling can be prevented by the use of a lubricant, such as bearing grease, however, grease needs to be 'worked' before full lubrication is achieved, therefore a running-in paste should be used to prevent galling in this start-up period.

GALVANIC CORROSION

Is an electrochemical process which occurs when two metals with differing electrical potentials are in contact with each other in the presence of an electrolytic solution (such as rain water).

GALVANISING

Galvanising is the process by which clean, degreased ferrous metal (i.e. steel) has a layer of zinc applied to its surface using extreme heat to form an inseparable alloy at the point where the two layers are fused. Zinc will be corroded in preference to the ferrous substrate thereby preventing structural corrosion. This type of coating is referred to as a 'sacrificial coating'.

ISO 9001

Internationally recognised Quality Management system standard, indicating our commitment to quality and continuous improvement. The standard has been developed to provide a framework around which a quality management system can effectively be implemented.

KB VALUE

The Kauri Butanol (KB) value is a measure of the relative solvent power of a hydrocarbon liquid. The higher the KB value, the more powerful the solvent.

MODULUS

Where two substrates/surfaces are bonded together with either an adhesive or sealant, they are often subject to forces which could, with enough pressure, result in the bond failing. Modulus is measured in Pascal's. Low modulus means the bond is more flexible and has more 'give' in it, i.e. good for expansion joints. High modulus means that the bond is stiffer and less flexible.

MRO

Abbreviation for the term "Maintenance, Repair, and Overhaul". Typically associated with the service and repair sectors, including plant and site maintenance / engineering.

NLGI GRADE

A widely used classification for lubricating greases established by the National Lubricating Grease Institute and a reference to the measure of the consistency of a particular grease. The most common consistency number is #2. Softer grades, especially #0 and #1, are often used for improved low-temperature service. High consistency numbers, #3 through #6 are used for certain high-speed bearings where leakage and sealing are particular concerns. The higher the number, the more viscous the grease.

NSF

See page 8.

OZONE DEPLETERS

Halogen-containing substances known to reduce the protective effects of the stratospheric ozone layer. Aerosols manufactured within Europe have been free of ozone depleting substances for many years.

pH

A scale ranging from 0 to 14 used to measure acidity and alkalinity. The lower the number the more acidic; the higher the number, the more alkaline; 7 is neutral.

POTABLE WATER

Water of sufficient quality to serve as drinking water is called potable water whether it is used as such or not. Although most fresh water sources are drinkable by humans, they can be a disease vector or cause long-term health problems if they do not meet certain water quality guidelines.

POUR POINT (PP)

The lowest temperature at which a fluid still can be pumped.

PTFE

PTFE is the abbreviation for polytetrafluoroethylene. PTFE appears in the Guinness Book of Records as having the lowest coefficient of static and dynamic friction of any solid. This value, at 0.02, is equivalent to wet ice on wet ice, indicating its extreme anti-friction properties.

REACH

Registration, Evaluation and Authorisation of Chemicals. REACH is an EU-wide reform of the regulatory environment in which chemicals are used and will eventually replace and update many other pieces of chemical control legislation. The aim is to reduce the risks to human health and the environment through the methodical and accurate identification of the properties of chemical substances. Whilst there is no definitive list of 'approved' chemicals as yet, a series of deadlines will ensure that the highest volume and most harmful are evaluated first. REACH relies on end-user application information to be filtered up through the supply chain to establish accurate registration and evaluation. More information can be found at: www.hse.gov.uk/reach.

RAL

In 1925, the private sector and the German government founded the "Reichsausschuss für Lieferbedingungen" - RAL - (Committee of the German Reich for Terms and Conditions of Sale). RAL's original task was to standardise precise technical terms of delivery and sale. The RAL color collection comprises over 200 colors with a four-digit numbering. The registers also include safety and signal colors and they comply with the requirements of the DIN standards (German Industrial Standards). The basic collection for matt color shades is the register RAL 840 HR while it is the RAL 841 GL register for gloss colors. RAL 840 HR is the European-wide 'registered' standard colors for the coatings industry.

RTV - ROOM TEMPERATURE VULCANISATION

Vulcanisation refers to a specific curing process of rubber involving high heat and the addition of sulphur. It is a chemical process in which polymer molecules are linked to other polymer molecules resulting in springy rubber molecules which become cross-linked. This makes the material harder, much more durable and also more resistant to chemical attack. Vulcanisation which occurs without the need for heat and sulphur, usually by the action of activating chemicals, is known as Room Temperature Vulcanisation as the rubber 'cures' at around 25°C.

SHELL 4-BALL WELD

An industry standard test which provides an indication of the load bearing capability of a lubricant. A steel ball is loaded and rotated against 3 fixed steel balls for 10 seconds. At the end of each 10 second run, a further weight is loaded onto the balls, and the test re-run using fresh lubricant. The test is complete when the balls weld together. The weld point is the load at which this occurs. The higher the weld point, the greater the lubricity (lubricating ability) of the grease.

SURFACTANT

A descriptive term derived from 'Surface Active Agent', a specialised compound that is typically used to connect water soluble and water-insoluble chemical groups. Can be used to improve the emulsifying, foaming, dispersing and wetting properties of a product

THIXOTROPIC

A term used to describe fluids which are shear thinning. In essence, most thixotropic substances are gel-like, meaning that they retain their shape upon application, but when heated or subjected to shear stress, their shape will change and they will become thinner. The word comes from the Greek 'thixis' for touch and -tropy, from 'tropos' meaning changeable.

USDA

See page 8.

VISCOSITY

A term used to describe the resistance to flow or degree of 'thickness' of a liquid, usually expressed in units of poise or stokes. The more viscous a product, the thicker its consistency.


VISCOSITY INDEX (VI)

Relationship of viscosity in function of temperature.

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

FPS PRODUCT SELECTION GUIDE





Product		NSF code	Use where		Food Contact		Pre-treatment	Post-treatment	
			Food processing area	Incidental	No	Removal food & packaging	Water rinse	Odor dissipation	
LUBRICANTS									
Multi Oil	H1	x	x						
Chain Lube	H1	x	x						
Silicone	H1	x	x						
Pen Oil	H1	x	x						
Dry Lube-F	H1	x	x						
Extreme Lube	H1	x	x						
3-36	H2	x			x				
GREASES									
Assembly Paste	H1	x	x						
EP Food Grease	H1	x	x						
HiTemp Food Grease	H1	x	x						
Food Grease	H1	x	x						
SPECIALTY									
Belt Grip	H1	x	x						
Sugar Dissolving Fluid	H1	x	x						
ECO Leak Finder	P1	x			x	x			
CLEANERS									
ECO Complex Blue	A1	x			x	x		x	
ECO Foam Cleaner	A1	x			x	x		x	
Inox Kleen	A7 C1	x			x	x	x	x	
Industrial ECO Degreaser	A8 K1	x			x	x	x	x	
Industrial Degreaser	A8 K1	x			x	x	x	x	
Dust Free 360 & Turbo	K2	x			x	x		x	
Contact Cleaner	K2	x			x	x		x	
Flatscreen Cleaner	K2	x			x	x		x	
Label Off Super	K3	x			x	x	x	x	

INDEX

2-26	66	ECO LEAK FINDER.....	67
3-36	28	ECO MULTI GREASE	33
3-36	50	ECO PEN OIL	29
5-56 + PTFE	28	ECO SUPERCUT	26
ACRYLIC CHROME EFFECT	64	EJECTOR LUBE.....	39
ACRYLIC HITEMP PAINT	64	EP FOOD GREASE	33
ACRYLIC METALLIC EFFECT	64	EXTRA LOCK	76
ACRYLIC METAL PRIMER.....	61	EXTREME LUBE	36
ACRYLIC PAINT	62	FAST DRY DEGREASER	18
ACRYLIC PLASTIC PRIMER	61	FAST STICK	77
ACRYLIC VARNISH	63	FERROKLEEN	20
ALU HITEMP	52	FERROKLEEN	53
ALU PASTE	37	FLATSCREEN CLEANER.....	16
ANTI SPATTER	71	FOOD GREASE	33
ANTI SPATTER PASTE.....	72	GALVA BRITE.....	51
ANTI-SPATTER PRODUCTS.....	71	GALVACOLOR.....	53
AQUA PAINT MARKER	57	GALVACOLOR.....	59
AQUA RAL	59	GALVA SHINE	51
ASSEMBLY PASTE.....	37	GD 265.....	68
BELT GRIP.....	66	GRAFFITI REMOVER.....	21
BELT GRIP IND.....	66	GRAPHITE ASSEMBLY PASTE	37
BLUE MOULD PROTECT	55	HAND SPRAYER	78
CERAMIC PASTE.....	37	HIGH SPEED CHAIN OIL.....	31
CHAIN LUBE.....	31	HIGH SPEED GREASE	35
CHAIN LUBE IND	31	HIGH TEMP GREASE.....	34
CITRUS HANDCLEANER	22	HITEMP FOOD GREASE	34
CLEAR MOULD PROTECT	55	INDUSTRIAL DEGREASER	18
CONTACT CLEANER.....	16	INDUSTRIAL ECO DEGREASER.....	18
CONTACT CLEANER PLUS.....	17	INOX 200.....	51
COPPER PASTE	37	INOX KLEEN	19
CRICK 110.....	74	INOX WELD KLEEN	20
CRICK 120.....	74	INOX WELD KLEEN	72
CRICK 130.....	74	LABEL OFF SUPER.....	20
CRICK SET.....	73	LEAK FINDER PMUC.....	67
DRY LUBE	32	LECTRA CLEAN II.....	18
DRY LUBE-F.....	32	LOST WAX RELEASE	45
DRY MOLY LUBE	32	LOW TEMP LEAK FINDER	67
DUST CLEANER	14	LUB 21.....	27
DUST FREE 360.....	14	MARKER BALL.....	58
DUST FREE 360 TURBO.....	14	MARKER PAINT	57
EASY SEAL	76	MARKER PEN.....	58
EASY WELD	71	MINUS 45.....	68
ECO BIO WELD	71	MOULD CLEAN.....	21
ECO COMPLEX BLUE	19	MOULD PROTECT	55
ECO FOAM CLEANER.....	19	MULTI GREASE.....	33

MULTI OIL.....	30
MULTI SURFACE CITRO CLEANER.....	23
MULTI SURFACE CITRO COVKLEEN	23
N.F. ELECTRONIC CLEANER	17
NSR DRY	41
NSR FOOD.....	41
NSR MULTI	41
NSR RUBBER.....	42
NSR SENSITIVE.....	43
NSR THERMO	42
NSR ULTRA THIN	42
NSR WET	43
OXIDE CLEAN PLUS.....	16
PEEL OFF.....	67
PEN OIL.....	29
POLYMER REMOVER.....	21
POWER LUBE	28
POWER STICK	77
PROFESSIONAL CLEANER.....	19
PUMP SPRAYER	78
PU RELEASE AGENT	45
QD-CONTACT CLEANER	17
QUICK FIX	77
RELEASE EMULSION.....	45
RIGID SEAL.....	76
ROM 300.....	68
ROST FLASH	28
ROUND NOZZLE SET.....	65
RUST OFF IND	29
RUST REMOVER	53
RUST SEAL.....	53
SILICONE.....	29
SILICONE EXTRA.....	29
SILICONE GREASE.....	35
SILICONE IND.....	29
SLIDEWAY OIL	30
SOFT LOCK.....	76
SP 350	50
SP 400	50
SPRAY PAINT GUN.....	65
SR FOOD	44
SR MULTI.....	44
SR SEMI PER.....	44
SR THERMO.....	44
STRIPING PAINT.....	58

SUGAR DISSOLVING FLUID	66
SUPER ADHESIVE GREASE.....	35
SUPERCUT	26
SUPER HANDCLEANER.....	22
SUPER LONGTERM GREASE.....	34
SUPER TAPPING COMPOUND	27
SUPER TAPPING FLUID	27
SYNTHETIC GREASE	36
TORCH CERAMIC ANTI SPATTER	72
TRIFLOW	39
URETHANE ISOLATION.....	52
VARNISH E200.....	52
WHITE LITHIUM GREASE	36
WIPES IND	22
WIRE ROPE LUBE.....	30
WOOD GLIDER	27
ZINC.....	52
ZINC PRIMER	51




CLEANERS



LUBRICANTS



RELEASE AGENT



ANTI-CORROSION




PAINTS



SPECIALTY



WELDING



ADHESIVES



ACCESSORIES

Your CRC Distributor



CRC Industries Europe
Touwslagerstraat 1
BE-9240 Zele
Belgium
Tel.: +32 (0) 52 45 60 11

www.crcind.com